

ENGINEERING
EXPRESS®

CORPORATE OFFICE:
160 SW 12th AVE., SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0650 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM

BUILDING CODE SEVENTH EDITION (2020)
PRODUCT APPROVAL FL#16921.1




REMARKS	DRWN	CHKD	DATE
INIT ISSUE	TSB	FLB	07-08-09
REV 2010 FBC	CSL	TSB	05-11-12
REV FBC 5TH (2014)	CSL	CSL	06-15-15
REV FBC 6TH (2017)	LAO	FLB	08-02-17
REV FBC 7TH (2020)	CSL	RWN	12-15-20

31 TITLATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

SCALE:

1

1. THIS SYSTEM HAS BEEN DESIGNED AND SHALL BE FABRICATED IN ACCORDANCE WITH THE STRUCTURAL PROVISIONS OF THE FLORIDA BUILDING CODE SEVENTH EDITION (2020) THE 2018 INTERNATIONAL BUILDING CODE FOR USE WITHIN AND OUTSIDE OF THE HIGH VELOCITY HURRICANE ZONE.
2. CONTRACTOR SHALL ENSURE THAT EACH INSTALLATION ASSEMBLY MEET THE MINIMUM CLEARANCE HEIGHT PER FBC SECTION 1510.10 FOR NON-HVHZ APPLICATIONS AND SECTION 1522.2 FOR HVHZ APPLICATIONS.
3. SEISMIC DESIGN DOES NOT GOVERN. SEISMIC PARAMETERS CHECKED: RISK CATEGORY II, IMPORTANCE FACTOR 1.0, $S_s=0.057$, $S_1=0.022$, SITE CLASS D, $S_d=0.061$, $S_d1=0.0355$, SEISMIC DESIGN CATEGORY D, SEISMIC DEMANDS ON NON-STRUCTURAL COMPONENTS (MECHANICAL COMPONENTS AC UNITS), $F_pMAX = 46$ LBS, $A_p=2.5$, $R_p=6.0$, UP TO 200' MRH.
4. MAXIMUM DIMENSIONS AND WEIGHT OF A/C UNIT SHALL CONFORM TO SPECIFICATIONS STATED HEREIN, MINIMUM 75LB OR MAXIMUM AS LISTED HEREIN.
5. THE ARCHITECT/ENGINEER OF RECORD FOR THE PROJECT SUPERSTRUCTURE WITH WHICH THIS DESIGN IS USED SHALL BE RESPONSIBLE FOR THE INTEGRITY OF ALL SUPPORTING SURFACES TO THIS DESIGN WHICH SHALL BE COORDINATED BY THE PERMITTING CONTRACTOR.
6. REACTION FORCES LISTED FOR USE WITH HOST STRUCTURE VERIFICATION ARE CALCULATED USING ASD METHODOLOGY. DESIGN PROFESSIONAL OF RECORD TO VERIFY APPLICABILITY AND/OR ADDITIONAL FACTORS FOR USE WITH HOST STRUCTURE VERIFICATION.
7. ALL FASTENERS TO BE #14 OR GREATER SAE GRADE 5, UNLESS NOTED OTHERWISE, CADMIUM PLATED OR OTHERWISE CORROSION RESISTANT MATERIAL AND SHALL COMPLY WITH ANY APPLICABLE FEDERAL, STATE, AND LOCAL CODES. PROVIDE (5) PITCHES MIN PAST THREAD PLANE.
8. ALL EXTRUDED MEMBERS SHALL BE ALUMINUM ALLOY TYPE 6061-T6 OR 6005-T5.
9. ALL EXISTING CONCRETE SUBSTRATE SHALL HAVE MINIMUM f_c COMPRESSIVE STRENGTH OF 3000 PSI AS VERIFIED BY OTHERS.
10. ALUMINUM WELDING SHALL BE PERFORMED IN ACCORDANCE WITH FBC SECTION 2003.8.1.4 WITH WELD FILLER ALLOYS MEETING ANSI/AWS A5.10 STANDARDS TO ACHIEVE ULTIMATE DESIGN STRENGTH IN ACCORDANCE WITH THE ALUMINUM DESIGN MANUAL, TABLE A.3.6 WELD FILLER: 5383 ELECTRODES. ALL ALUMINUM CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE TOLERANCES, QUALITY AND METHODS OF CONSTRUCTION AS SET FORTH IN FBC SECTION 2003.2 AND THE AMERICAN WELDING SOCIETY'S STRUCTURAL WELDING CODE-ALUMINUM. MINIMUM WELD IS $\frac{1}{8}$ " THROAT FULL PERIMETER FILLET WELD UNLESS OTHERWISE NOTED.
11. THE CONTRACTOR IS RESPONSIBLE TO INSULATE MEMBERS FROM DISSIMILAR MATERIALS TO PREVENT ELECTROLYSIS.
12. ELECTRICAL GROUND, WHEN REQUIRED, TO BE DESIGNED & INSTALLED BY OTHERS. ALL MECHANICAL SPECIFICATIONS (CLEAR SPACE, TONNAGE, ETC.) SHALL BE AS PER MANUFACTURER RECOMMENDATIONS AND ARE THE EXPRESS RESPONSIBILITY OF THE CONTRACTOR.
13. ENGINEER SEAL AFFIXED HERETO VALIDATES STRUCTURAL DESIGN AS SHOWN ONLY. USE OF THIS SPECIFICATION BY CONTRACTOR, et. al. INDEMNIFIES & SAVES HARMLESS THIS ENGINEER FOR ALL COST & DAMAGES INCLUDING LEGAL FEES & APPELLATE FEES RESULTING FROM MATERIAL FABRICATION, SYSTEM ERECTION, CONSTRUCTION PRACTICES BEYOND THAT WHICH IS CALLED FOR BY LOCAL, STATE, & FEDERAL CODES & FROM DEVIATIONS OF THIS PLAN.
14. THE SYSTEM DETAILED HEREIN IS GENERIC AND DOES NOT PROVIDE INFORMATION FOR A SPECIFIC SITE. FOR SITE CONDITIONS DIFFERENT FROM THE CONDITIONS DETAILED HEREIN, A LICENSED ENGINEER OR REGISTERED ARCHITECT SHALL PREPARE SITE SPECIFIC DOCUMENTS FOR USE IN CONJUNCTION WITH THIS DOCUMENT.
15. EXCEPT AS EXPRESSLY PROVIDED HEREIN, NO ADDITIONAL CERTIFICATIONS OR AFFIRMATIONS ARE INTENDED.
16. AC STANDS SHALL BE LABELED CONTAINING:
PRECISION ALUMINUM PRODUCTS, INC.
DEERFIELD BEACH, FL
FLORIDA PRODUCT APPROVAL NUMBER



STAND COMPONENTS

STAND TYPE/COMPONENT SCHEDULE					
PART	DESCR.	STAND TYPE			
		STD	HD	XHD	FIXED-HD
②	OUTER TUBE SIZE (B1 x B1 x t1)	1.25" x 1.25" x 0.093"	1.50" x 1.50" x 0.093"	2.00" x 2.00" x 0.093"	N/A
②*	OUTER TUBE SIZE (B1 x B1 x t1)	N/A	N/A	N/A	2.00" x 2.00" x 0.093"
②.1	INNER TUBE SIZE (B2 x B2 x t2)	1.00" x 1.00" x 0.125"	1.25" x 1.25" x 0.125"	1.75" x 1.75" x 0.125"	N/A
④	POST SIZE (OD X THK)	1.5" x 0.090"	1.9" x 0.145"	1.9" x 0.200"	1.9" x 0.145"
⑤	BASEPLATE SIZE (P1 X P1)	4" X 4"	• 4" X 4" UP TO 24" STAND HT • 5" X 5" FOR 30" STAND HT	6" X 6"	5" X 5"



- LEGEND:
- "HD" = HEAVY DUTY
 - "STD" = STANDARD
 - "XHD" = EXTRA HEAVY DUTY
- ②* SHALL BE UTILIZED FOR HD FIXED ASSEMBLY ONLY

MEAN UNIT HEIGHT & MAX FACE AREA CALCULATION DIRECTIVE: THIS DIRECTIVE SHALL BE USED TO CALCULATE THE MEAN UNIT HEIGHT & MAXIMUM FACE AREA OF ANY MULTIPLE UNIT CONFIGURATION.



EXAMPLE CONFIGURATIONS:

- †NOTE
- UNIT WEIGHT MAY BE INCREASED TO 800# MAX FOR "XHD" STANDS
 - MAX RAIL SPAN LENGTH IS LIMITED TO 5' FOR "XHD" STANDS



2 UNITS: 2 FRAME CONFIGURATION



3 UNITS: 3 FRAME CONFIGURATION



4 UNITS: 4 FRAME CONFIGURATION



NOTE: THE NUMBER OF UNITS PER STAND CONFIGURATION MAY BE UNLIMITED PROVIDED THAT MULTIPLE UNITS CONFORM TO THE MEAN UNIT HEIGHT & MAXIMUM UNIT FACE AREA RESTRICTIONS UTILIZED IN THE DESIGN SCHEDULES.

*MAXIMUM ALLOWABLE HEIGHT DIFFERENCE BETWEEN ANY UNITS IN A MULTIPLE UNIT CONFIGURATION IS RESTRICTED TO 16" MAX.

FORMULAS USED FOR DETERMINING MEAN UNIT HEIGHT & MAXIMUM UNIT FACE AREA:

1. CALCULATE THE MEAN UNIT HEIGHT BY THE FOLLOWING EQUATION:

- TWO UNITS: $\frac{H1+H2}{2}$
- THREE UNITS: $\frac{H1+H2+H3}{3}$
- FOUR UNITS: $\frac{H1+H2+H3+H4}{4}$
- "n" UNITS: $\frac{H1+H2+H3+...Hn}{n}$

2. CALCULATE THE MAXIMUM UNIT FACE AREA BY THE FOLLOWING EQUATION:

- TWO UNITS: $(H1 \times W1) + (H2 \times W2)$
- THREE UNITS: $(H1 \times W1) + (H2 \times W2) + (H3 \times W3)$
- FOUR UNITS: $(H1 \times W1) + (H2 \times W2) + (H3 \times W3) + (H4 \times W4)$
- "n" UNITS: $(H1 \times W1) + ... (Hn \times Wn)$

EXAMPLE SCENARIO:


- CONSIDER A FOUR UNIT CONFIGURATION WITH THE DIMENSIONS AS SHOWN BELOW.
- CALCULATE THE MEAN UNIT HEIGHT.

$$\text{FOUR UNITS: } \frac{H1+H2+H3+H4}{4} = \frac{20''+29''+22''+25''}{4} = 24'' \text{ MEAN UNIT HEIGHT}$$

3. CALCULATE THE MAXIMUM FACE AREA.

$$\text{FOUR UNITS: } (H1 \times W1) + (H2 \times W2) + (H3 \times W3) + (H4 \times W4) = (20'' \times 21'') + (29'' \times 25'') + (22'' \times 22'') + (25'' \times 27'')$$

$$= 2304 \text{ in}^2$$



FL# 16921.1

ENGINEERING EXPRESS
CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM

PRECISION ALUMINUM PRODUCTS, INC.

1339 SW 1ST WAY
DEERFIELD BEACH, FL 33441
PH: (954) 480-6919
ALUMINUM A/C STANDS HVHZ & NON-HVHZ APPLICATIONS
FLORIDA BUILDING CODE SEVENTH EDITION (2020)
PRODUCT APPROVAL FL# 16921.1

REMARKS	DATE	DRWN	CHKD
INIT ISSUE	07-08-09	TSB	FLB
REV 2010 FBC	05-11-12	CSL	TSB
REV 2015 FBC	06-15-15	CSL	CSL
REV 2017 FBC	08-02-17	LAO	FLB
REV 2020 FBC	12-15-20	CSL	IRWN

20-32768

SCALE:

"STD" STAND DESIGN SCHEDULES & STAND DIRECTIVE EXAMPLE

FRANK BENNARDO, PE
PE# 0046549 CA# 9885



FL# 16921.1

ENGINEERING EXPRESS
CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM

24" STAND DEPTH: MAX FACE AREA (2760in² - 11520in²), FRAME QUANTITY (5-8 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 8 FRAMES				MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2760 in ²	87.3 PSF	68.9 PSF	87.3 PSF	68.9 PSF	76.4 PSF	60.3 PSF	76.4 PSF	60.3 PSF	65.5 PSF	51.7 PSF	65.5 PSF	51.7 PSF	54.6 PSF	43.1 PSF	54.6 PSF	43.1 PSF	100.40 LB-FT	104.6 LB	356.4 LB	373.2 LB
24 "			68.4 PSF	54.0 PSF	68.4 PSF	54.0 PSF	59.8 PSF	47.2 PSF	59.8 PSF	47.2 PSF	51.3 PSF	40.5 PSF	51.3 PSF	40.5 PSF	42.7 PSF	33.7 PSF	42.7 PSF	33.7 PSF	100.40 LB-FT	81.9 LB	317.0 LB	362.5 LB
30 "			56.4 PSF	44.5 PSF	56.4 PSF	44.5 PSF	49.3 PSF	38.9 PSF	49.3 PSF	38.9 PSF	42.3 PSF	33.4 PSF	42.3 PSF	33.4 PSF	35.2 PSF	27.8 PSF	35.2 PSF	27.8 PSF	100.40 LB-FT	67.5 LB	292.7 LB	356.4 LB
36 "			48.0 PSF	37.9 PSF	48.0 PSF	37.9 PSF	42.0 PSF	33.2 PSF	42.0 PSF	33.2 PSF	36.0 PSF	28.4 PSF	36.0 PSF	28.4 PSF	30.0 PSF	23.7 PSF	30.0 PSF	23.7 PSF	100.40 LB-FT	57.6 LB	276.2 LB	352.5 LB
18 "	30 "	4650 in ²	51.8 PSF	40.9 PSF	51.8 PSF	40.9 PSF	45.3 PSF	35.8 PSF	45.3 PSF	35.8 PSF	38.8 PSF	30.7 PSF	38.8 PSF	30.7 PSF	32.4 PSF	25.5 PSF	32.4 PSF	25.5 PSF	100.40 LB-FT	104.6 LB	382.5 LB	399.4 LB
24 "			40.6 PSF	32.0 PSF	40.6 PSF	32.0 PSF	35.5 PSF	28.0 PSF	35.5 PSF	28.0 PSF	30.4 PSF	24.0 PSF	30.4 PSF	24.0 PSF	25.3 PSF	20.0 PSF	25.3 PSF	20.0 PSF	100.40 LB-FT	81.9 LB	337.5 LB	383.0 LB
30 "			33.4 PSF	26.4 PSF	33.4 PSF	26.4 PSF	29.3 PSF	23.1 PSF	29.3 PSF	23.1 PSF	25.1 PSF	19.8 PSF	25.1 PSF	19.8 PSF	20.9 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	67.5 LB	309.6 LB	373.3 LB
36 "			28.5 PSF	22.5 PSF	28.5 PSF	22.5 PSF	24.9 PSF	19.7 PSF	24.9 PSF	19.7 PSF	21.4 PSF	16.9 PSF	21.4 PSF	16.9 PSF					100.40 LB-FT	57.6 LB	290.6 LB	344.4 LB
18 "	36 "	6300 in ²	38.2 PSF	30.2 PSF	38.2 PSF	30.2 PSF	33.4 PSF	26.4 PSF	33.4 PSF	26.4 PSF	28.7 PSF	22.6 PSF	28.7 PSF	22.6 PSF	23.9 PSF	18.8 PSF	23.9 PSF	18.8 PSF	100.40 LB-FT	104.6 LB	408.7 LB	425.5 LB
24 "			29.9 PSF	23.6 PSF	29.9 PSF	23.6 PSF	26.2 PSF	20.7 PSF	26.2 PSF	20.7 PSF	22.4 PSF	17.7 PSF	22.4 PSF	17.7 PSF					100.40 LB-FT	81.9 LB	358.0 LB	381.0 LB
30 "			24.7 PSF	19.5 PSF	24.7 PSF	19.5 PSF	21.6 PSF	17.0 PSF	21.6 PSF	17.0 PSF									100.40 LB-FT	67.5 LB	326.5 LB	351.6 LB
36 "			21.0 PSF	16.6 PSF	21.0 PSF	16.6 PSF													100.40 LB-FT	57.6 LB	305.0 LB	330.7 LB
18 "	42 "	8400 in ²	28.7 PSF	22.6 PSF	28.7 PSF	22.6 PSF	25.1 PSF	19.8 PSF	25.1 PSF	19.8 PSF	21.5 PSF	16.9 PSF	21.5 PSF	16.9 PSF					100.40 LB-FT	104.6 LB	434.9 LB	429.2 LB
24 "			22.4 PSF	17.7 PSF	22.4 PSF	17.7 PSF													100.40 LB-FT	81.9 LB	378.5 LB	373.4 LB
30 "																			0.00 LB-FT	0.0 LB	0.0 LB	135.0 LB
36 "																			0.00 LB-FT	0.0 LB	0.0 LB	135.0 LB
18 "	48 "	11520 in ²	20.9 PSF	16.5 PSF	20.9 PSF	16.5 PSF													100.40 LB-FT	104.6 LB	461.0 LB	427.3 LB
24 "																			0.00 LB-FT	0.0 LB	0.0 LB	135.0 LB
30 "																			0.00 LB-FT	0.0 LB	0.0 LB	135.0 LB
36 "																			0.00 LB-FT	0.0 LB	0.0 LB	135.0 LB

DESIGN SCHEDULE NOTES:

1. MAXIMUM CALCULATED FACE AREA SHALL BE EQUAL TO OR LESS THAN THE MAXIMUM ALLOWABLE FACE AREA FOR EACH CONFIGURATION.
2. REFERENCE ANCHOR SCHEDULE FOR ANCHOR TYPES LISTED HEREIN.


STAND EXAMPLE

(THE FOLLOWING EXAMPLE ILLUSTRATES THE PROCEDURE USED TO DETERMINE THE MAXIMUM ALLOWABLE WIND PRESSURE & UPLIFT FOR ANY GIVEN MECHANICAL UNIT CONFIGURATION THAT CONFORMS TO THE DIMENSION RESTRICTIONS LISTED HEREIN. SEE SHEET 2 FOR MEAN UNIT HEIGHT & MAXIMUM FACE AREA CALCULATION DIRECTIVE. SEE SHEET 2 FOR COMPONENT SCHEDULE. SEE SHEET 16 FOR ANCHOR SCHEDULES.)

MECHANICAL UNIT/STAND CRITERIA:

CONSIDER THE INSTALLATION OF (4) MECHANICAL UNITS, (1)-20" TALL x 24" DEEP x 21" WIDE, (1)-29" TALL x 24" DEEP x 25" WIDE, (1)-22" TALL x 24" DEEP x 22" WIDE, (1)-25" TALL x 27" DEEP x 27" WIDE, [350 LB MAX WEIGHT] INSTALLED WITH THE FOLLOWING CRITERIA:

- NUMBER OF LEG FRAMES= (5) FRAMES
- STAND HEIGHT= 18" HEIGHT
- STAND DEPTH= 24" STAND DEPTH SPREAD
- HOST STRUCTURE TYPE= 3,000 PSI CONCRETE (AS VERIFIED BY OTHERS).



PROCEDURE:

		RESULT:
1	DETERMINE THE MEAN UNIT HEIGHT FOR THE GIVEN CONFIGURATION	SEE SHEET 2, CALCULATION DIRECTIVE STEP #1 FOR METHOD OF CALCULATING THE MEAN UNIT HEIGHT. FOR CLARIFICATION, THIS CONFIGURATION HAS BEEN WORKED OUT IN THE EXAMPLE SCENARIO. (MEAN UNIT HEIGHT = 24 in)
2	DETERMINE THE MAXIMUM FACE AREA FOR THE GIVEN CONFIGURATION	SEE SHEET 2, CALCULATION DIRECTIVE STEP #2 FOR METHOD OF CALCULATING THE MAXIMUM TOTAL UNIT FACE AREA. FOR CLARIFICATION, THIS CONFIGURATION HAS BEEN WORKED OUT IN THE EXAMPLE SCENARIO. (MAXIMUM UNIT FACE AREA = 2304 in²)
3	LOCATE DESIGN SCHEDULE THAT APPLIES TO THE GIVEN CONFIGURATION	SEE SHEET 3 FOR THE 24" STAND DEPTH WITH A MAXIMUM FACE AREA OF 2304 in ² .
4	DETERMINE THE MAXIMUM ALLOWABLE LATERAL & UPLIFT WIND LOADS	FOR A 2304 in ² MAX TOTAL UNIT FACE AREA ON A 18" STAND HEIGHT WITH (5) SUPPORTING FRAMES, THE ALLOWABLE WIND LOADS ARE AS FOLLOWS: • ALLOWABLE LATERAL WIND LOAD: 54.6 PSF (FROM TABLE ABOVE) • ALLOWABLE UPLIFT WIND LOAD: 43.1 PSF
5	INSTALL STAND PER PERMISSIBLE ANCHOR TYPES AND VERIFY HOST STRUCTURE TYPE	UTILIZE ANCHOR TYPES FROM DESIGN SCHEDULE ASSOCIATED WITH THE ALLOWABLE WIND VALUES DETERMINED IN STEP 4. FOR THE TABLE LISTING, ANCHOR TYPES 2 & 3 MAY BE APPLIED . FOR THIS EXAMPLE UTILIZE ANCHOR TYPE 2 FOR CONCRETE HOST STRUCTURE TYPE. INSTALL STANDS PER ANCHOR SCHEDULE AND DETAILS AS ILLUSTRATED ON SHEETS 16 & 17.

CONCLUSION:

6	MAXIMUM ALLOWABLE LATERAL DESIGN PRESSURE=	= 54.6 PSF (FROM TABLE ABOVE)
	MAXIMUM ALLOWABLE UPLIFT DESIGN PRESSURE=	= 43.1 PSF
7	COMPARE TO SITE SPECIFIC DESIGN CONDITIONS	COMPARE VALUES FROM STEP #6 TO THE SEPARATE SITE SPECIFIC REQUIRED DESIGN WIND PRESSURE PROVIDED BY A LICENSED ENGINEER OR REGISTERED ARCHITECT; NOT INCLUDED IN THIS CERTIFICATION. SITE-SPECIFIC PRESSURE REQUIREMENTS SHALL BE LESS THAN OR EQUAL TO THE LATERAL AND UPLIFT DESIGN PRESSURE ALLOWABLE CAPACITY VALUES LISTED.

DESIGN SCHEDULE NOTES:

1. MAXIMUM CALCULATED FACE AREA SHALL BE EQUAL TO OR LESS THAN THE MAXIMUM ALLOWABLE FACE AREA FOR EACH CONFIGURATION.
2. REFERENCE ANCHOR SCHEDULE FOR ANCHOR TYPES LISTED HEREIN.

TABLE LEGEND:

○ - DENOTES EXAMPLE VALUE FOR USE WITH COVER PAGE DIRECTIVE

PRECISION ALUMINUM PRODUCTS, INC.

1339 SW 1ST WAY
DEERFIELD BEACH, FL 33441
PH: (954)-480-6919

ALUMINUM A/C STANDS HVHZ & NON-HVHZ APPLICATIONS
FLORIDA BUILDING CODE SEVENTH EDITION (2020)
PRODUCT APPROVAL FL# 16921.1

REMARKS	DATE	DRWN	CHKD
INIT ISSUE	07-08-09	TSB	FLB
REV 2010 FBC	05-11-12	CSL	TSB
REV FBC 5TH (2014)	06-15-15	CSL	CSL
REV FBC 6TH (2017)	08-02-17	LAO	FLB
REV FBC 7TH (2020)	12-15-20	CSL	FRWN

ALTERATIONS, ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

20-32768

SCALE:

OF 17

3

"STD" STAND DESIGN SCHEDULE CONTINUED

36" STAND DEPTH: MAX FACE AREA (2760in² - 11520in²), FRAME QUANTITY (5-8 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 8 FRAMES				MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2760 in²	81.7 PSF	64.5 PSF	81.7 PSF	64.5 PSF	71.5 PSF	56.4 PSF	71.5 PSF	56.4 PSF	61.3 PSF	48.3 PSF	61.3 PSF	48.3 PSF	51.0 PSF	40.3 PSF	51.0 PSF	40.3 PSF	100.40 LB-FT	97.9 LB	242.7 LB	268.1 LB
24 "			64.3 PSF	50.7 PSF	64.3 PSF	50.7 PSF	56.2 PSF	44.4 PSF	56.2 PSF	44.4 PSF	48.2 PSF	38.0 PSF	48.2 PSF	38.0 PSF	40.1 PSF	31.7 PSF	40.1 PSF	31.7 PSF	100.40 LB-FT	77.0 LB	213.6 LB	265.4 LB
30 "			53.2 PSF	42.0 PSF	53.2 PSF	42.0 PSF	46.6 PSF	36.8 PSF	46.6 PSF	36.8 PSF	39.9 PSF	31.5 PSF	39.9 PSF	31.5 PSF	33.3 PSF	26.2 PSF	33.3 PSF	26.2 PSF	100.40 LB-FT	63.8 LB	195.9 LB	264.3 LB
36 "			45.6 PSF	36.0 PSF	45.6 PSF	36.0 PSF	39.9 PSF	31.5 PSF	39.9 PSF	31.5 PSF	34.2 PSF	27.0 PSF	34.2 PSF	27.0 PSF	28.5 PSF	22.5 PSF	28.5 PSF	22.5 PSF	100.40 LB-FT	54.6 LB	183.9 LB	263.9 LB
18 "	30 "	4650 in²	48.5 PSF	38.2 PSF	48.5 PSF	38.2 PSF	42.4 PSF	33.5 PSF	42.4 PSF	33.5 PSF	36.3 PSF	28.7 PSF	36.3 PSF	28.7 PSF	30.3 PSF	23.9 PSF	30.3 PSF	23.9 PSF	100.40 LB-FT	97.9 LB	259.0 LB	284.4 LB
24 "			38.1 PSF	30.1 PSF	38.1 PSF	30.1 PSF	33.4 PSF	26.3 PSF	33.4 PSF	26.3 PSF	28.6 PSF	22.6 PSF	28.6 PSF	22.6 PSF	23.8 PSF	18.8 PSF	23.8 PSF	18.8 PSF	100.40 LB-FT	77.0 LB	226.5 LB	278.2 LB
30 "			31.6 PSF	24.9 PSF	31.6 PSF	24.9 PSF	27.6 PSF	21.8 PSF	27.6 PSF	21.8 PSF	23.7 PSF	18.7 PSF	23.7 PSF	18.7 PSF					100.40 LB-FT	63.8 LB	206.5 LB	252.4 LB
36 "			27.0 PSF	21.3 PSF	27.0 PSF	21.3 PSF	23.6 PSF	18.7 PSF	23.6 PSF	18.7 PSF	20.3 PSF	16.0 PSF	20.3 PSF	16.0 PSF					100.40 LB-FT	54.6 LB	193.0 LB	250.5 LB
18 "	36 "	6300 in²	35.8 PSF	28.2 PSF	35.8 PSF	28.2 PSF	31.3 PSF	24.7 PSF	31.3 PSF	24.7 PSF	26.8 PSF	21.2 PSF	26.8 PSF	21.2 PSF	22.3 PSF	17.6 PSF	22.3 PSF	17.6 PSF	100.40 LB-FT	97.9 LB	275.3 LB	300.7 LB
24 "			28.1 PSF	22.2 PSF	28.1 PSF	22.2 PSF	24.6 PSF	19.4 PSF	24.6 PSF	19.4 PSF	21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF					100.40 LB-FT	77.0 LB	239.3 LB	268.6 LB
30 "			23.3 PSF	18.4 PSF	23.3 PSF	18.4 PSF	20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF									100.40 LB-FT	63.8 LB	217.2 LB	247.0 LB
36 "																						
18 "	42 "	8400 in²	26.8 PSF	21.2 PSF	26.8 PSF	21.2 PSF	23.4 PSF	18.5 PSF	23.4 PSF	18.5 PSF	20.1 PSF	15.9 PSF	20.1 PSF	15.9 PSF					100.40 LB-FT	97.9 LB	291.6 LB	294.5 LB
24 "			21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF													100.40 LB-FT	77.0 LB	252.1 LB	253.3 LB
30 "																						
36 "																						
18 "	48 "	11520 in²																				
24 "																						
30 "																						
36 "																						

24" STAND DEPTH: MAX FACE AREA (2208in² - 9216in²), FRAME QUANTITY (4-7 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2208 in²	95.5 PSF	75.4 PSF	95.5 PSF	75.4 PSF	81.9 PSF	64.6 PSF	81.9 PSF	64.6 PSF	68.2 PSF	53.8 PSF	68.2 PSF	53.8 PSF	54.6 PSF	43.1 PSF	54.6 PSF	43.1 PSF	100.40 LB-FT	104.6 LB	357.6 LB	373.2 LB
24 "			74.8 PSF	59.0 PSF	74.8 PSF	59.0 PSF	64.1 PSF	50.6 PSF	64.1 PSF	50.6 PSF	53.4 PSF	42.2 PSF	53.4 PSF	42.2 PSF	42.7 PSF	33.7 PSF	42.7 PSF	33.7 PSF	100.40 LB-FT	81.9 LB	318.2 LB	362.5 LB
30 "			61.7 PSF	48.7 PSF	61.7 PSF	48.7 PSF	52.8 PSF	41.7 PSF	52.8 PSF	41.7 PSF	44.0 PSF	34.8 PSF	44.0 PSF	34.8 PSF	35.2 PSF	27.8 PSF	35.2 PSF	27.8 PSF	100.40 LB-FT	67.5 LB	293.9 LB	356.4 LB
36 "			52.5 PSF	41.5 PSF	52.5 PSF	41.5 PSF	45.0 PSF	35.5 PSF	45.0 PSF	35.5 PSF	37.5 PSF	29.6 PSF	37.5 PSF	29.6 PSF	30.0 PSF	23.7 PSF	30.0 PSF	23.7 PSF	100.40 LB-FT	57.6 LB	277.4 LB	352.5 LB
18 "	30 "	3720 in²	56.7 PSF	44.7 PSF	56.7 PSF	44.7 PSF	48.6 PSF	38.3 PSF	48.6 PSF	38.3 PSF	40.5 PSF	31.9 PSF	40.5 PSF	31.9 PSF	32.4 PSF	25.5 PSF	32.4 PSF	25.5 PSF	100.40 LB-FT	104.6 LB	383.7 LB	399.4 LB
24 "			44.4 PSF	35.0 PSF	44.4 PSF	35.0 PSF	38.0 PSF	30.0 PSF	38.0 PSF	30.0 PSF	31.7 PSF	25.0 PSF	31.7 PSF	25.0 PSF	25.3 PSF	20.0 PSF	25.3 PSF	20.0 PSF	100.40 LB-FT	81.9 LB	338.7 LB	383.0 LB
30 "			36.6 PSF	28.9 PSF	36.6 PSF	28.9 PSF	31.3 PSF	24.7 PSF	31.3 PSF	24.7 PSF	26.1 PSF	20.6 PSF	26.1 PSF	20.6 PSF	20.9 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	67.5 LB	310.8 LB	373.3 LB
36 "			31.2 PSF	24.6 PSF	31.2 PSF	24.6 PSF	26.7 PSF	21.1 PSF	26.7 PSF	21.1 PSF	22.2 PSF	17.6 PSF	22.2 PSF	17.6 PSF	///	///	///	///	100.40 LB-FT	57.6 LB	291.8 LB	339.9 LB
18 "	36 "	5040 in²	41.8 PSF	33.0 PSF	41.8 PSF	33.0 PSF	35.8 PSF	28.3 PSF	35.8 PSF	28.3 PSF	29.9 PSF	23.6 PSF	29.9 PSF	23.6 PSF	23.9 PSF	18.8 PSF	23.9 PSF	18.8 PSF	100.40 LB-FT	104.6 LB	409.9 LB	425.5 LB
24 "			32.7 PSF	25.8 PSF	32.7 PSF	25.8 PSF	28.1 PSF	22.1 PSF	28.1 PSF	22.1 PSF	23.4 PSF	18.4 PSF	23.4 PSF	18.4 PSF	///	///	///	///	100.40 LB-FT	81.9 LB	359.2 LB	376.5 LB
30 "			27.0 PSF	21.3 PSF	27.0 PSF	21.3 PSF	23.1 PSF	18.2 PSF	23.1 PSF	18.2 PSF	///	///	///	///	///	///	///	///	100.40 LB-FT	67.5 LB	327.7 LB	345.2 LB
36 "			23.0 PSF	18.1 PSF	23.0 PSF	18.1 PSF	///	///	///	///	///	///	///	///	///	///	///	///	///	100.40 LB-FT	57.6 LB	306.2 LB
18 "	42 "	6720 in²	31.4 PSF	24.7 PSF	31.4 PSF	24.7 PSF	26.9 PSF	21.2 PSF	26.9 PSF	21.2 PSF	22.4 PSF	17.7 PSF	22.4 PSF	17.7 PSF	///	///	///	///	100.40 LB-FT	104.6 LB	436.1 LB	424.7 LB
24 "			24.5 PSF	19.4 PSF	24.5 PSF	19.4 PSF	21.0 PSF	16.6 PSF	21.0 PSF	16.6 PSF	///	///	///	///	///	///	///	///	100.40 LB-FT	81.9 LB	379.7 LB	379.0 LB
30 "			20.2 PSF	16.0 PSF	20.2 PSF	16.0 PSF	///	///	///	///	///	///	///	///	///	///	///	///	100.40 LB-FT	67.5 LB	344.6 LB	349.2 LB
36 "			///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///
18 "	48 "	9216 in²	22.8 PSF	18.0 PSF	22.8 PSF	18.0 PSF	///	///	///	///	///	///	///	///	///	///	///	///	100.40 LB-FT	104.6 LB	462.2 LB	420.0 LB
24 "			///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///
30 "			///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///
36 "			///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///	///

36" STAND DEPTH: MAX FACE AREA (2208in² - 9216in²), FRAME QUANTITY (4-7 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2208 in²	89.3 PSF	70.5 PSF	89.3 PSF	70.5 PSF	76.6 PSF	60.4 PSF	76.6 PSF	60.4 PSF	63.8 PSF	50.4 PSF	63.8 PSF	50.4 PSF	51.0 PSF	40.3 PSF	51.0 PSF	40.3 PSF	100.40 LB-FT	97.9 LB	243.9 LB	268.1 LB
24 "			70.3 PSF	55.5 PSF	70.3 PSF	55.5 PSF	60.2 PSF	47.5 PSF	60.2 PSF	47.5 PSF	50.2 PSF	39.6 PSF	50.2 PSF	39.6 PSF	40.1 PSF	31.7 PSF	40.1 PSF	31.7 PSF	100.40 LB-FT	77.0 LB	214.8 LB	265.4 LB
30 "			58.2 PSF	46.0 PSF	58.2 PSF	46.0 PSF	49.9 PSF	39.4 PSF	49.9 PSF	39.4 PSF	41.6 PSF	32.8 PSF	41.6 PSF	32.8 PSF	33.3 PSF	26.2 PSF	33.3 PSF	26.2 PSF	100.40 LB-FT	63.8 LB	197.1 LB	264.3 LB
36 "			49.8 PSF	39.3 PSF	49.8 PSF	39.3 PSF	42.7 PSF	33.7 PSF	42.7 PSF	33.7 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	28.5 PSF	22.5 PSF	28.5 PSF	22.5 PSF	100.40 LB-FT	54.6 LB	185.1 LB	263.9 LB
18 "	30 "	3720 in²	53.0 PSF	41.8 PSF	53.0 PSF	41.8 PSF	45.4 PSF	35.9 PSF	45.4 PSF	35.9 PSF	37.9 PSF	29.9 PSF	37.9 PSF	29.9 PSF	30.3 PSF	23.9 PSF	30.3 PSF	23.9 PSF	100.40 LB-FT	97.9 LB	260.2 LB	284.4 LB
24 "			41.7 PSF	32.9 PSF	41.7 PSF	32.9 PSF	35.7 PSF	28.2 PSF	35.7 PSF	28.2 PSF	29.8 PSF	23.5 PSF	29.8 PSF	23.5 PSF	23.8 PSF	18.8 PSF	23.8 PSF	18.8 PSF	100.40 LB-FT	77.0 LB	227.7 LB	278.2 LB
30 "			34.5 PSF	27.3 PSF	34.5 PSF	27.3 PSF	29.6 PSF	23.4 PSF	29.6 PSF	23.4 PSF	24.7 PSF	19.5 PSF	24.7 PSF	19.5 PSF					100.40 LB-FT	63.8 LB	207.7 LB	247.9 LB
36 "			29.6 PSF	23.3 PSF	29.6 PSF	23.3 PSF	25.3 PSF	20.0 PSF	25.3 PSF	20.0 PSF	21.1 PSF	16.7 PSF	21.1 PSF	16.7 PSF					100.40 LB-FT	54.6 LB	194.2 LB	246.0 LB
18 "	36 "	5040 in²	39.1 PSF	30.9 PSF	39.1 PSF	30.9 PSF	33.5 PSF	26.5 PSF	33.5 PSF	26.5 PSF	27.9 PSF	22.0 PSF	27.9 PSF	22.0 PSF	22.3 PSF	17.6 PSF	22.3 PSF	17.6 PSF	100.40 LB-FT	97.9 LB	276.5 LB	300.7 LB
24 "			30.8 PSF	24.3 PSF	30.8 PSF	24.3 PSF	26.4 PSF	20.8 PSF	26.4 PSF	20.8 PSF	22.0 PSF	17.3 PSF	22.0 PSF	17.3 PSF					100.40 LB-FT	77.0 LB	240.5 LB	264.1 LB
30 "			25.5 PSF	20.1 PSF	25.5 PSF	20.1 PSF	21.8 PSF	17.2 PSF	21.8 PSF	17.2 PSF									100.40 LB-FT	63.8 LB	218.4 LB	240.6 LB
36 "			21.8 PSF	17.2 PSF	21.8 PSF	17.2 PSF														100.40 LB-FT	54.6 LB	203.3 LB
18 "	42 "	6720 in²	29.3 PSF	23.1 PSF	29.3 PSF	23.1 PSF	25.1 PSF	19.8 PSF	25.1 PSF	19.8 PSF	20.9 PSF	16.5 PSF	20.9 PSF	16.5 PSF					100.40 LB-FT	97.9 LB	292.8 LB	290.0 LB
24 "			23.1 PSF	18.2 PSF	23.1 PSF	18.2 PSF													100.40 LB-FT	77.0 LB	253.3 LB	246.0 LB
30 "																						
36 "																						
18 "	48 "	9216 in²	21.4 PSF	16.9 PSF	21.4 PSF	16.9 PSF													100.40 LB-FT	97.9 LB	309.2 LB	275.5 LB
24 "																						
30 "																						
36 "																						

"STD" STAND DESIGN SCHEDULE CONTINUED

FRANK BENNARD, PE
PE# 0046549 CA# 9885



FL# 16921.1

ENGINEERING EXPRESS
CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM



PRECISION ALUMINUM PRODUCTS, INC.

1339 SW 1ST WAY

DEERFIELD BEACH, FL 33441

PH: (954)-480-6919

ALUMINUM A/C STANDS HVHZ & NON-HVHZ APPLICATIONS
FLORIDA BUILDING CODE SEVENTH EDITION (2020)
PRODUCT APPROVAL FL# 16921.1

24" STAND DEPTH: MAX FACE AREA (1656in² - 6912in²), FRAME QUANTITY (3-6 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	1656 in²	109.2 PSF	86.2 PSF	109.2 PSF	86.2 PSF	91.0 PSF	71.8 PSF	91.0 PSF	71.8 PSF	72.8 PSF	57.4 PSF	72.8 PSF	57.4 PSF	54.6 PSF	43.1 PSF	54.6 PSF	43.1 PSF	100.40 LB-FT	104.6 LB	359.2 LB	373.2 LB
24 "			85.5 PSF	67.5 PSF	85.5 PSF	67.5 PSF	71.2 PSF	56.2 PSF	71.2 PSF	56.2 PSF	57.0 PSF	45.0 PSF	57.0 PSF	45.0 PSF	42.7 PSF	33.7 PSF	42.7 PSF	33.7 PSF	100.40 LB-FT	81.9 LB	319.8 LB	362.5 LB
30 "			70.5 PSF	55.6 PSF	70.5 PSF	55.6 PSF	58.7 PSF	46.4 PSF	58.7 PSF	46.4 PSF	47.0 PSF	37.1 PSF	47.0 PSF	37.1 PSF	35.2 PSF	27.8 PSF	35.2 PSF	27.8 PSF	100.40 LB-FT	67.5 LB	295.5 LB	356.4 LB
36 "			60.1 PSF	47.4 PSF	60.1 PSF	47.4 PSF	50.0 PSF	39.5 PSF	50.0 PSF	39.5 PSF	40.0 PSF	31.6 PSF	40.0 PSF	31.6 PSF	30.0 PSF	23.7 PSF	30.0 PSF	23.7 PSF	100.40 LB-FT	57.6 LB	279.0 LB	352.5 LB
18 "	30 "	2790 in²	64.8 PSF	51.1 PSF	64.8 PSF	51.1 PSF	54.0 PSF	42.6 PSF	54.0 PSF	42.6 PSF	43.2 PSF	34.1 PSF	43.2 PSF	34.1 PSF	32.4 PSF	25.5 PSF	32.4 PSF	25.5 PSF	100.40 LB-FT	104.6 LB	385.3 LB	399.4 LB
24 "			50.7 PSF	40.0 PSF	50.7 PSF	40.0 PSF	42.3 PSF	33.4 PSF	42.3 PSF	33.4 PSF	33.8 PSF	26.7 PSF	33.8 PSF	26.7 PSF	25.3 PSF	20.0 PSF	25.3 PSF	20.0 PSF	100.40 LB-FT	81.9 LB	340.3 LB	383.0 LB
30 "			41.8 PSF	33.0 PSF	41.8 PSF	33.0 PSF	34.8 PSF	27.5 PSF	34.8 PSF	27.5 PSF	27.9 PSF	22.0 PSF	27.9 PSF	22.0 PSF	20.9 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	67.5 LB	312.4 LB	373.3 LB
36 "			35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	29.7 PSF	23.4 PSF	29.7 PSF	23.4 PSF	23.7 PSF	18.7 PSF	23.7 PSF	18.7 PSF					100.40 LB-FT	57.6 LB	293.4 LB	333.1 LB
18 "	36 "	3780 in²	47.8 PSF	37.7 PSF	47.8 PSF	37.7 PSF	39.8 PSF	31.4 PSF	39.8 PSF	31.4 PSF	31.8 PSF	25.1 PSF	31.8 PSF	25.1 PSF	23.9 PSF	18.8 PSF	23.9 PSF	18.8 PSF	100.40 LB-FT	104.6 LB	411.5 LB	425.5 LB
24 "			37.4 PSF	29.5 PSF	37.4 PSF	29.5 PSF	31.2 PSF	24.6 PSF	31.2 PSF	24.6 PSF	24.9 PSF	19.7 PSF	24.9 PSF	19.7 PSF					100.40 LB-FT	81.9 LB	360.8 LB	369.8 LB
30 "			30.8 PSF	24.3 PSF	30.8 PSF	24.3 PSF	25.7 PSF	20.3 PSF	25.7 PSF	20.3 PSF	20.5 PSF	16.2 PSF	20.5 PSF	16.2 PSF					100.40 LB-FT	67.5 LB	329.3 LB	356.5 LB
36 "			26.3 PSF	20.7 PSF	26.3 PSF	20.7 PSF	21.9 PSF	17.3 PSF	21.9 PSF	17.3 PSF									100.40 LB-FT	57.6 LB	307.8 LB	327.3 LB
18 "	42 "	5040 in²	35.8 PSF	28.3 PSF	35.8 PSF	28.3 PSF	29.9 PSF	23.6 PSF	29.9 PSF	23.6 PSF	23.9 PSF	18.8 PSF	23.9 PSF	18.8 PSF					100.40 LB-FT	104.6 LB	437.7 LB	418.0 LB
24 "			28.1 PSF	22.1 PSF	28.1 PSF	22.1 PSF	23.4 PSF	18.4 PSF	23.4 PSF	18.4 PSF									100.40 LB-FT	81.9 LB	381.3 LB	370.0 LB
30 "			23.1 PSF	18.2 PSF	23.1 PSF	18.2 PSF													100.40 LB-FT	67.5 LB	346.2 LB	339.6 LB
36 "																						
18 "	48 "	6912 in²	26.1 PSF	20.6 PSF	26.1 PSF	20.6 PSF	21.8 PSF	17.2 PSF	21.8 PSF	17.2 PSF									100.40 LB-FT	104.6 LB	463.9 LB	423.9 LB
24 "			20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF													100.40 LB-FT	81.9 LB	401.8 LB	377.0 LB
30 "																						
36 "																						

36" STAND DEPTH: MAX FACE AREA (1656in² - 6912in²), FRAME QUANTITY (3-6 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)	
			MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES								
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3						
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT					
18 "	24 "	1656 in²	102.1 PSF	80.6 PSF	102.1 PSF	80.6 PSF	85.1 PSF	67.2 PSF	85.1 PSF	67.2 PSF	68.1 PSF	53.7 PSF	68.1 PSF	53.7 PSF	51.0 PSF	40.3 PSF	51.0 PSF	40.3 PSF	100.40 LB-FT	97.9 LB	245.5 LB	268.1 LB	
24 "			80.3 PSF	63.4 PSF	80.3 PSF	63.4 PSF	66.9 PSF	52.8 PSF	66.9 PSF	52.8 PSF	53.5 PSF	42.3 PSF	53.5 PSF	42.3 PSF	40.1 PSF	31.7 PSF	40.1 PSF	31.7 PSF	100.40 LB-FT	77.0 LB	216.4 LB	265.4 LB	
30 "			66.6 PSF	52.5 PSF	66.6 PSF	52.5 PSF	55.5 PSF	43.8 PSF	55.5 PSF	43.8 PSF	44.4 PSF	35.0 PSF	44.4 PSF	35.0 PSF	33.3 PSF	26.2 PSF	33.3 PSF	26.2 PSF	100.40 LB-FT	63.8 LB	198.7 LB	264.3 LB	
36 "			57.0 PSF	45.0 PSF	57.0 PSF	45.0 PSF	47.5 PSF	37.5 PSF	47.5 PSF	37.5 PSF	38.0 PSF	30.0 PSF	38.0 PSF	30.0 PSF	28.5 PSF	22.5 PSF	28.5 PSF	22.5 PSF	100.40 LB-FT	54.6 LB	186.7 LB	263.9 LB	
18 "	30 "	2790 in²	60.6 PSF	47.8 PSF	60.6 PSF	47.8 PSF	50.5 PSF	39.8 PSF	50.5 PSF	39.8 PSF	40.4 PSF	31.9 PSF	40.4 PSF	31.9 PSF	30.3 PSF	23.9 PSF	30.3 PSF	23.9 PSF	100.40 LB-FT	97.9 LB	261.8 LB	284.4 LB	
24 "			47.7 PSF	37.6 PSF	47.7 PSF	37.6 PSF	39.7 PSF	31.3 PSF	39.7 PSF	31.3 PSF	31.8 PSF	25.1 PSF	31.8 PSF	25.1 PSF	23.8 PSF	18.8 PSF	23.8 PSF	18.8 PSF	100.40 LB-FT	77.0 LB	229.3 LB	278.2 LB	
30 "			39.5 PSF	31.2 PSF	39.5 PSF	31.2 PSF	32.9 PSF	26.0 PSF	32.9 PSF	26.0 PSF	26.3 PSF	20.8 PSF	26.3 PSF	20.8 PSF	20.8 PSF	17.8 PSF	14.8 PSF	14.8 PSF	100.40 LB-FT	63.8 LB	209.3 LB	241.2 LB	
36 "			33.8 PSF	26.7 PSF	33.8 PSF	26.7 PSF	28.2 PSF	22.2 PSF	28.2 PSF	22.2 PSF	22.5 PSF	17.8 PSF	22.5 PSF	17.8 PSF	17.8 PSF	14.8 PSF	11.8 PSF	11.8 PSF	100.40 LB-FT	54.6 LB	195.8 LB	239.3 LB	
18 "	36 "	3780 in²	44.7 PSF	35.3 PSF	44.7 PSF	35.3 PSF	37.2 PSF	29.4 PSF	37.2 PSF	29.4 PSF	29.8 PSF	23.5 PSF	29.8 PSF	23.5 PSF	22.3 PSF	17.6 PSF	22.3 PSF	17.6 PSF	100.40 LB-FT	97.9 LB	278.1 LB	300.7 LB	
24 "			35.2 PSF	27.8 PSF	35.2 PSF	27.8 PSF	29.3 PSF	23.1 PSF	29.3 PSF	23.1 PSF	23.4 PSF	18.5 PSF	23.4 PSF	18.5 PSF	18.5 PSF	14.8 PSF	11.8 PSF	11.8 PSF	100.40 LB-FT	77.0 LB	242.1 LB	257.3 LB	
30 "			29.1 PSF	23.0 PSF	29.1 PSF	23.0 PSF	24.3 PSF	19.1 PSF	24.3 PSF	19.1 PSF	24.3 PSF	18.5 PSF	14.8 PSF	11.8 PSF	11.8 PSF	11.8 PSF	9.8 PSF	9.8 PSF	100.40 LB-FT	63.8 LB	220.0 LB	231.6 LB	
36 "			24.9 PSF	19.7 PSF	24.9 PSF	19.7 PSF	20.8 PSF	16.4 PSF	20.8 PSF	16.4 PSF	20.8 PSF	16.4 PSF	16.4 PSF	13.8 PSF	10.8 PSF	10.8 PSF	10.8 PSF	9.8 PSF	9.8 PSF	100.40 LB-FT	54.6 LB	204.9 LB	228.1 LB
18 "	42 "	5040 in²	33.5 PSF	26.5 PSF	33.5 PSF	26.5 PSF	27.9 PSF	22.0 PSF	27.9 PSF	22.0 PSF	22.3 PSF	17.6 PSF	22.3 PSF	17.6 PSF	17.6 PSF	14.8 PSF	11.8 PSF	11.8 PSF	100.40 LB-FT	97.9 LB	294.5 LB	283.3 LB	
24 "			26.4 PSF	20.8 PSF	26.4 PSF	20.8 PSF	22.0 PSF	17.3 PSF	22.0 PSF	17.3 PSF	22.0 PSF	17.3 PSF	17.3 PSF	14.8 PSF	11.8 PSF	11.8 PSF	11.8 PSF	9.8 PSF	9.8 PSF	100.40 LB-FT	77.0 LB	255.0 LB	249.9 LB
30 "			21.8 PSF	17.2 PSF	21.8 PSF	17.2 PSF	22.0 PSF	17.3 PSF	22.0 PSF	17.3 PSF	22.0 PSF	17.3 PSF	17.3 PSF	14.8 PSF	11.8 PSF	11.8 PSF	11.8 PSF	9.8 PSF	9.8 PSF	100.40 LB-FT	63.8 LB	230.6 LB	228.7 LB
36 "			17.3 PSF	13.8 PSF	17.3 PSF	13.8 PSF	17.3 PSF	13.8 PSF	17.3 PSF	13.8 PSF	17.3 PSF	13.8 PSF	13.8 PSF	11.8 PSF	9.8 PSF	9.8 PSF	9.8 PSF	9.8 PSF	9.8 PSF	100.40 LB-FT	54.6 LB	204.9 LB	228.1 LB
18 "	48 "	6912 in²	24.4 PSF	19.3 PSF	24.4 PSF	19.3 PSF	20.3 PSF	16.1 PSF	20.3 PSF	16.1 PSF	20.3 PSF	16.1 PSF	20.3 PSF	16.1 PSF	16.1 PSF	13.8 PSF	10.8 PSF	10.8 PSF	100.40 LB-FT	97.9 LB	310.8 LB	279.3 LB	
24 "			19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	19.3 PSF	15.3 PSF	
30 "			15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	15.3 PSF	12.3 PSF	
36 "			12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	12.3 PSF	9.8 PSF	

24" STAND DEPTH: MAX FACE AREA (1104in² - 4608in²), FRAME QUANTITY (2-5 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	1104 in²	136.5 PSF	107.7 PSF	136.5 PSF	107.7 PSF	109.2 PSF	86.2 PSF	109.2 PSF	86.2 PSF	81.9 PSF	64.6 PSF	81.9 PSF	64.6 PSF	54.6 PSF	43.1 PSF	54.6 PSF	43.1 PSF	100.40 LB-FT	104.6 LB	361.4 LB	373.2 LB
24 "			108.9 PSF	84.4 PSF	106.9 PSF	84.4 PSF	85.5 PSF	67.5 PSF	85.5 PSF	67.5 PSF	64.1 PSF	50.6 PSF	64.1 PSF	50.6 PSF	42.7 PSF	33.7 PSF	42.7 PSF	33.7 PSF	100.40 LB-FT	81.9 LB	322.1 LB	362.5 LB
30 "			88.1 PSF	69.6 PSF	88.1 PSF	69.6 PSF	70.5 PSF	55.6 PSF	70.5 PSF	55.6 PSF	52.8 PSF	41.7 PSF	52.8 PSF	41.7 PSF	35.2 PSF	27.8 PSF	35.2 PSF	27.8 PSF	100.40 LB-FT	67.5 LB	297.8 LB	356.4 LB
36 "			75.1 PSF	59.3 PSF	75.1 PSF	59.3 PSF	60.1 PSF	47.4 PSF	60.1 PSF	47.4 PSF	45.0 PSF	35.5 PSF	45.0 PSF	35.5 PSF	30.0 PSF	23.7 PSF	30.0 PSF	23.7 PSF	100.40 LB-FT	57.6 LB	281.2 LB	352.5 LB
18 "	30 "	1860 in²	81.0 PSF	63.9 PSF	81.0 PSF	63.9 PSF	64.8 PSF	51.1 PSF	64.8 PSF	51.1 PSF	48.6 PSF	38.3 PSF	48.6 PSF	38.3 PSF	32.4 PSF	25.5 PSF	32.4 PSF	25.5 PSF	100.40 LB-FT	104.6 LB	387.6 LB	399.4 LB
24 "			63.4 PSF	50.1 PSF	63.4 PSF	50.1 PSF	50.7 PSF	40.0 PSF	50.7 PSF	40.0 PSF	38.0 PSF	30.0 PSF	38.0 PSF	30.0 PSF	25.3 PSF	20.0 PSF	25.3 PSF	20.0 PSF	100.40 LB-FT	81.9 LB	342.6 LB	383.0 LB
30 "			52.3 PSF	41.3 PSF	52.3 PSF	41.3 PSF	41.8 PSF	33.0 PSF	41.8 PSF	33.0 PSF	31.3 PSF	24.7 PSF	31.3 PSF	24.7 PSF	20.9 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	67.5 LB	314.7 LB	373.3 LB
36 "			44.5 PSF	35.2 PSF	44.5 PSF	35.2 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	26.7 PSF	21.1 PSF	26.7 PSF	21.1 PSF	21.1 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	57.6 LB	295.7 LB	321.9 LB
18 "	36 "	2920 in²	59.8 PSF	47.2 PSF	59.8 PSF	47.2 PSF	47.8 PSF	37.7 PSF	47.8 PSF	37.7 PSF	35.8 PSF	28.3 PSF	35.8 PSF	28.3 PSF	23.9 PSF	18.8 PSF	23.9 PSF	18.8 PSF	100.40 LB-FT	104.6 LB	413.8 LB	425.5 LB
24 "			46.8 PSF	36.9 PSF	46.8 PSF	36.9 PSF	37.4 PSF	29.5 PSF	37.4 PSF	29.5 PSF	28.1 PSF	22.1 PSF	28.1 PSF	22.1 PSF	21.1 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	81.9 LB	363.1 LB	358.5 LB
30 "			38.6 PSF	30.4 PSF	38.6 PSF	30.4 PSF	30.8 PSF	24.3 PSF	30.8 PSF	24.3 PSF	23.1 PSF	18.2 PSF	23.1 PSF	18.2 PSF	21.1 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	67.5 LB	331.6 LB	345.2 LB
36 "			32.9 PSF	25.9 PSF	32.9 PSF	25.9 PSF	26.3 PSF	20.7 PSF	26.3 PSF	20.7 PSF	21.1 PSF	16.5 PSF	21.1 PSF	16.5 PSF	21.1 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	57.6 LB	310.1 LB	313.8 LB
18 "	42 "	3360 in²	44.8 PSF	35.4 PSF	44.8 PSF	35.4 PSF	35.8 PSF	28.3 PSF	35.8 PSF	28.3 PSF	26.9 PSF	21.2 PSF	26.9 PSF	21.2 PSF	21.1 PSF	16.5 PSF	20.9 PSF	16.5 PSF	100.40 LB-FT	104.6 LB	439.9 LB	406.7 LB
24 "			35.1 PSF	27.7 PSF	35.1 PSF	27.7 PSF	28.1 PSF	22.1 PSF	28.1 PSF	22.1 PSF	21.0 PSF	16.6 PSF	21.0 PSF	16.6 PSF	21.0 PSF	16.6 PSF	20.9 PSF	16.6 PSF	100.40 LB-FT	81.9 LB	383.5 LB	379.0 LB
30 "			28.9 PSF	22.8 PSF	28.9 PSF	22.8 PSF	23.1 PSF	18.2 PSF	23.1 PSF	18.2 PSF	21.0 PSF	16.6 PSF	21.0 PSF	16.6 PSF	21.0 PSF	16.6 PSF	20.9 PSF	16.6 PSF	100.40 LB-FT	67.5 LB	348.5 LB	339.6 LB
36 "			24.6 PSF	19.4 PSF	24.6 PSF	19.4 PSF	24.6 PSF	19.4 PSF	24.6 PSF	19.4 PSF	24.6 PSF	19.4 PSF	24.6 PSF	19.4 PSF	24.6 PSF	19.4 PSF	24.6 PSF	19.4 PSF	24.6 PSF	100.40 LB-FT	57.6 LB	324.5 LB
18 "	48 "	4608 in²	32.7 PSF	25.8 PSF	32.7 PSF	25.8 PSF	26.1 PSF	20.6 PSF	26.1 PSF	20.6 PSF	21.0 PSF	16.6 PSF	21.0 PSF	16.6 PSF	21.0 PSF	16.6 PSF	20.9 PSF	16.6 PSF	100.40 LB-FT	104.6 LB	466.1 LB	410.4 LB
24 "			25.6 PSF	20.2 PSF	25.6 PSF	20.2 PSF	20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF	100.40 LB-FT	81.9 LB	404.0 LB	377.0 LB
30 "			21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF	21.1 PSF	16.6 PSF	100.40 LB-FT	67.5 LB	365.4 LB	343.0 LB
36 "			18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF	18.2 PSF	14.6 PSF

"STD" STAND DESIGN SCHEDULE CONTINUED

36" STAND DEPTH: MAX FACE AREA (1104in² - 4608in²), FRAME QUANTITY (2-5 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	1104 in ²	127.7 PSF	100.8 PSF	127.7 PSF	100.8 PSF	102.1 PSF	80.6 PSF	102.1 PSF	80.6 PSF	76.6 PSF	60.4 PSF	76.6 PSF	60.4 PSF	51.0 PSF	40.3 PSF	51.0 PSF	40.3 PSF	100.40 LB-FT	97.9 LB	247.8 LB	268.1 LB
24 "			100.4 PSF	79.3 PSF	100.4 PSF	79.3 PSF	80.3 PSF	63.4 PSF	80.3 PSF	63.4 PSF	60.2 PSF	47.5 PSF	60.2 PSF	47.5 PSF	40.1 PSF	31.7 PSF	40.1 PSF	31.7 PSF	100.40 LB-FT	77.0 LB	218.7 LB	265.4 LB
30 "			83.2 PSF	65.7 PSF	83.2 PSF	65.7 PSF	66.6 PSF	52.5 PSF	66.6 PSF	52.5 PSF	49.9 PSF	39.4 PSF	49.9 PSF	39.4 PSF	33.3 PSF	26.2 PSF	33.3 PSF	26.2 PSF	100.40 LB-FT	63.8 LB	200.9 LB	264.3 LB
36 "			71.2 PSF	56.2 PSF	71.2 PSF	56.2 PSF	57.0 PSF	45.0 PSF	57.0 PSF	45.0 PSF	42.7 PSF	33.7 PSF	42.7 PSF	33.7 PSF	28.5 PSF	22.5 PSF	28.5 PSF	22.5 PSF	100.40 LB-FT	54.6 LB	188.9 LB	263.9 LB
18 "	30 "	1860 in ²	75.8 PSF	59.8 PSF	75.8 PSF	59.8 PSF	60.6 PSF	47.8 PSF	60.6 PSF	47.8 PSF	45.4 PSF	35.9 PSF	45.4 PSF	35.9 PSF	30.3 PSF	23.9 PSF	30.3 PSF	23.9 PSF	100.40 LB-FT	97.9 LB	264.1 LB	284.4 LB
24 "			59.6 PSF	47.0 PSF	59.6 PSF	47.0 PSF	47.7 PSF	37.6 PSF	47.7 PSF	37.6 PSF	35.7 PSF	28.2 PSF	35.7 PSF	28.2 PSF	23.8 PSF	18.8 PSF	23.8 PSF	18.8 PSF	100.40 LB-FT	77.0 LB	231.5 LB	278.2 LB
30 "			49.4 PSF	39.0 PSF	49.4 PSF	39.0 PSF	39.5 PSF	31.2 PSF	39.5 PSF	31.2 PSF	29.6 PSF	23.4 PSF	29.6 PSF	23.4 PSF					100.40 LB-FT	63.8 LB	211.6 LB	229.9 LB
36 "			42.3 PSF	33.4 PSF	42.3 PSF	33.4 PSF	33.8 PSF	26.7 PSF	33.8 PSF	26.7 PSF	25.3 PSF	20.0 PSF	25.3 PSF	20.0 PSF					100.40 LB-FT	54.6 LB	198.0 LB	228.0 LB
18 "	36 "	2520 in ²	55.9 PSF	44.1 PSF	55.9 PSF	44.1 PSF	44.7 PSF	35.3 PSF	44.7 PSF	35.3 PSF	33.5 PSF	26.5 PSF	33.5 PSF	26.5 PSF	22.3 PSF	17.6 PSF	22.3 PSF	17.6 PSF	100.40 LB-FT	97.9 LB	280.4 LB	300.7 LB
24 "			44.0 PSF	34.7 PSF	44.0 PSF	34.7 PSF	35.2 PSF	27.8 PSF	35.2 PSF	27.8 PSF	26.4 PSF	20.8 PSF	26.4 PSF	20.8 PSF					100.40 LB-FT	77.0 LB	244.4 LB	248.1 LB
30 "			36.4 PSF	28.7 PSF	36.4 PSF	28.7 PSF	29.1 PSF	23.0 PSF	29.1 PSF	23.0 PSF	21.8 PSF	17.2 PSF	21.8 PSF	17.2 PSF					100.40 LB-FT	63.8 LB	222.2 LB	240.6 LB
36 "			31.2 PSF	24.6 PSF	31.2 PSF	24.6 PSF	24.9 PSF	19.7 PSF	24.9 PSF	19.7 PSF									100.40 LB-FT	54.6 LB	207.1 LB	214.6 LB
18 "	42 "	3360 in ²	41.9 PSF	33.1 PSF	41.9 PSF	33.1 PSF	33.5 PSF	26.5 PSF	33.5 PSF	26.5 PSF	25.1 PSF	19.8 PSF	25.1 PSF	19.8 PSF					100.40 LB-FT	97.9 LB	296.7 LB	272.0 LB
24 "			33.0 PSF	26.0 PSF	33.0 PSF	26.0 PSF	26.4 PSF	20.8 PSF	26.4 PSF	20.8 PSF									100.40 LB-FT	77.0 LB	257.2 LB	236.4 LB
30 "			27.3 PSF	21.5 PSF	27.3 PSF	21.5 PSF	21.8 PSF	17.2 PSF	21.8 PSF	17.2 PSF									100.40 LB-FT	63.8 LB	232.9 LB	228.7 LB
36 "			23.4 PSF	18.4 PSF	23.4 PSF	18.4 PSF														100.40 LB-FT	54.6 LB	216.2 LB
18 "	48 "	4608 in ²	30.5 PSF	24.1 PSF	30.5 PSF	24.1 PSF	24.4 PSF	19.3 PSF	24.4 PSF	19.3 PSF									100.40 LB-FT	97.9 LB	313.0 LB	265.8 LB
24 "			24.0 PSF	19.0 PSF	24.0 PSF	19.0 PSF													100.40 LB-FT	77.0 LB	270.0 LB	235.7 LB
30 "																						
36 "																						

TABLE LEGEND:

 -DENOTES VALUES NOT APPROVED FOR USE

DESIGN SCHEDULE NOTES:

1. MAXIMUM CALCULATED FACE AREA SHALL BE EQUAL TO OR LESS THAN THE MAXIMUM ALLOWABLE FACE AREA FOR EACH CONFIGURATION.
2. REFERENCE ANCHOR SCHEDULE FOR ANCHOR TYPES LISTED HEREIN.

24" STAND DEPTH: MAX FACE AREA (552in² - 2304in²), FRAME QUANTITY (2-3 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO								MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	552 in²	163.8 PSF	129.3 PSF	163.8 PSF	129.3 PSF	109.2 PSF	86.2 PSF	109.2 PSF	86.2 PSF	100.40 LB-FT	104.6 LB	362.9 LB	305.7 LB
24 "			128.3 PSF	101.2 PSF	128.3 PSF	101.2 PSF	85.5 PSF	67.5 PSF	85.5 PSF	67.5 PSF	100.40 LB-FT	81.9 LB	323.6 LB	295.0 LB
30 "			105.7 PSF	83.5 PSF	105.7 PSF	83.5 PSF	70.5 PSF	55.6 PSF	70.5 PSF	55.6 PSF	100.40 LB-FT	67.5 LB	299.3 LB	288.9 LB
36 "			90.1 PSF	71.1 PSF	90.1 PSF	71.1 PSF	60.1 PSF	47.4 PSF	60.1 PSF	47.4 PSF	100.40 LB-FT	57.6 LB	282.7 LB	285.0 LB
18 "	30 "	930 in²	97.2 PSF	76.7 PSF	97.2 PSF	76.7 PSF	64.8 PSF	51.1 PSF	64.8 PSF	51.1 PSF	100.40 LB-FT	104.6 LB	389.1 LB	331.9 LB
24 "			76.1 PSF	60.1 PSF	76.1 PSF	60.1 PSF	50.7 PSF	40.0 PSF	50.7 PSF	40.0 PSF	100.40 LB-FT	81.9 LB	344.1 LB	315.5 LB
30 "			62.7 PSF	49.5 PSF	62.7 PSF	49.5 PSF	41.8 PSF	33.0 PSF	41.8 PSF	33.0 PSF	100.40 LB-FT	67.5 LB	316.2 LB	305.8 LB
36 "			53.5 PSF	42.2 PSF	53.5 PSF	42.2 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	100.40 LB-FT	57.6 LB	297.2 LB	299.4 LB
18 "	36 "	1260 in²	71.7 PSF	56.6 PSF	71.7 PSF	56.6 PSF	47.8 PSF	37.7 PSF	47.8 PSF	37.7 PSF	100.40 LB-FT	104.6 LB	415.3 LB	358.0 LB
24 "			56.2 PSF	44.3 PSF	56.2 PSF	44.3 PSF	37.4 PSF	29.5 PSF	37.4 PSF	29.5 PSF	100.40 LB-FT	81.9 LB	364.6 LB	336.0 LB
30 "			46.3 PSF	36.5 PSF	46.3 PSF	36.5 PSF	30.8 PSF	24.3 PSF	30.8 PSF	24.3 PSF	100.40 LB-FT	67.5 LB	333.1 LB	322.7 LB
36 "			39.5 PSF	31.1 PSF	39.5 PSF	31.1 PSF	26.3 PSF	20.7 PSF	26.3 PSF	20.7 PSF	100.40 LB-FT	57.6 LB	311.6 LB	313.8 LB
18 "	42 "	1680 in²	53.8 PSF	42.4 PSF	53.8 PSF	42.4 PSF	35.8 PSF	28.3 PSF	35.8 PSF	28.3 PSF	100.40 LB-FT	104.6 LB	441.4 LB	384.2 LB
24 "			42.1 PSF	33.2 PSF	42.1 PSF	33.2 PSF	28.1 PSF	22.1 PSF	28.1 PSF	22.1 PSF	100.40 LB-FT	81.9 LB	385.0 LB	356.5 LB
30 "			34.7 PSF	27.4 PSF	34.7 PSF	27.4 PSF	23.1 PSF	18.2 PSF	23.1 PSF	18.2 PSF	100.40 LB-FT	67.5 LB	350.0 LB	339.6 LB
36 "			29.6 PSF	23.3 PSF	29.6 PSF	23.3 PSF					100.40 LB-FT	57.6 LB	326.0 LB	305.7 LB
18 "	48 "	2304 in²	39.2 PSF	30.9 PSF	39.2 PSF	30.9 PSF	26.1 PSF	20.6 PSF	26.1 PSF	20.6 PSF	100.40 LB-FT	104.6 LB	467.6 LB	410.4 LB
24 "			30.7 PSF	24.2 PSF	30.7 PSF	24.2 PSF	20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF	100.40 LB-FT	81.9 LB	405.9 LB	377.0 LB
30 "			25.3 PSF	20.0 PSF	25.3 PSF	20.0 PSF					100.40 LB-FT	67.5 LB	366.9 LB	334.0 LB
36 "			21.6 PSF	17.0 PSF	21.6 PSF	17.0 PSF					100.40 LB-FT	57.6 LB	340.4 LB	320.1 LB

36" STAND DEPTH: MAX FACE AREA (552in² - 2304in²), FRAME QUANTITY (2-3 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO								MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	552 in ²	153.2 PSF	120.9 PSF	153.2 PSF	120.9 PSF	102.1 PSF	80.6 PSF	102.1 PSF	80.6 PSF	100.40 LB-FT	97.9 LB	249.3 LB	200.6 LB
24 "			120.5 PSF	95.1 PSF	120.5 PSF	95.1 PSF	80.3 PSF	63.4 PSF	80.3 PSF	63.4 PSF	100.40 LB-FT	77.0 LB	220.2 LB	197.9 LB
30 "			99.9 PSF	78.8 PSF	99.9 PSF	78.8 PSF	66.6 PSF	52.5 PSF	66.6 PSF	52.5 PSF	100.40 LB-FT	63.8 LB	202.4 LB	196.8 LB
36 "			85.5 PSF	67.5 PSF	85.5 PSF	67.5 PSF	57.0 PSF	45.0 PSF	57.0 PSF	45.0 PSF	100.40 LB-FT	54.6 LB	190.4 LB	196.4 LB
18 "	30 "	930 in ²	90.9 PSF	71.8 PSF	90.9 PSF	71.8 PSF	60.6 PSF	47.8 PSF	60.6 PSF	47.8 PSF	100.40 LB-FT	97.9 LB	265.6 LB	216.9 LB
24 "			71.5 PSF	56.5 PSF	71.5 PSF	56.5 PSF	47.7 PSF	37.6 PSF	47.7 PSF	37.6 PSF	100.40 LB-FT	77.0 LB	233.0 LB	210.7 LB
30 "			59.3 PSF	46.8 PSF	59.3 PSF	46.8 PSF	39.5 PSF	31.2 PSF	39.5 PSF	31.2 PSF	100.40 LB-FT	63.8 LB	213.1 LB	207.4 LB
36 "			50.7 PSF	40.0 PSF	50.7 PSF	40.0 PSF	33.8 PSF	26.7 PSF	33.8 PSF	26.7 PSF	100.40 LB-FT	54.6 LB	199.5 LB	205.5 LB
18 "	36 "	1260 in ²	67.1 PSF	53.0 PSF	67.1 PSF	53.0 PSF	44.7 PSF	35.3 PSF	44.7 PSF	35.3 PSF	100.40 LB-FT	97.9 LB	281.9 LB	233.2 LB
24 "			52.8 PSF	41.7 PSF	52.8 PSF	41.7 PSF	35.2 PSF	27.8 PSF	35.2 PSF	27.8 PSF	100.40 LB-FT	77.0 LB	245.9 LB	223.6 LB
30 "			43.7 PSF	34.5 PSF	43.7 PSF	34.5 PSF	29.1 PSF	23.0 PSF	29.1 PSF	23.0 PSF	100.40 LB-FT	63.8 LB	223.7 LB	218.1 LB
36 "			37.4 PSF	29.5 PSF	37.4 PSF	29.5 PSF	24.9 PSF	19.7 PSF	24.9 PSF	19.7 PSF	100.40 LB-FT	54.6 LB	208.6 LB	214.6 LB
18 "	42 "	1680 in ²	50.3 PSF	39.7 PSF	50.3 PSF	39.7 PSF	33.5 PSF	26.5 PSF	33.5 PSF	26.5 PSF	100.40 LB-FT	97.9 LB	298.2 LB	249.5 LB
24 "			39.6 PSF	31.2 PSF	39.6 PSF	31.2 PSF	26.4 PSF	20.8 PSF	26.4 PSF	20.8 PSF	100.40 LB-FT	77.0 LB	258.7 LB	236.4 LB
30 "			32.8 PSF	25.9 PSF	32.8 PSF	25.9 PSF	21.8 PSF	17.2 PSF	21.8 PSF	17.2 PSF	100.40 LB-FT	63.8 LB	234.4 LB	228.7 LB
36 "			28.1 PSF	22.1 PSF	28.1 PSF	22.1 PSF	24.4 PSF	19.3 PSF	24.4 PSF	19.3 PSF	100.40 LB-FT	54.6 LB	217.7 LB	201.2 LB
18 "	48 "	2304 in ²	36.7 PSF	28.9 PSF	36.7 PSF	28.9 PSF	24.4 PSF	19.3 PSF	24.4 PSF	19.3 PSF	100.40 LB-FT	97.9 LB	314.5 LB	265.8 LB
24 "			28.8 PSF	22.8 PSF	28.8 PSF	22.8 PSF	24.4 PSF	19.3 PSF	24.4 PSF	19.3 PSF	100.40 LB-FT	77.0 LB	271.5 LB	226.7 LB
30 "			23.9 PSF	18.8 PSF	23.9 PSF	18.8 PSF	24.4 PSF	19.3 PSF	24.4 PSF	19.3 PSF	100.40 LB-FT	63.8 LB	245.0 LB	216.9 LB
36 "			20.4 PSF	16.1 PSF	20.4 PSF	16.1 PSF	24.4 PSF	19.3 PSF	24.4 PSF	19.3 PSF	100.40 LB-FT	54.6 LB	226.9 LB	210.3 LB

"HD" STAND DESIGN SCHEDULE

FRANK BENNARD, PE
PE# 0046549 CA# 9885



FL# 16921.1

ENGINEERING EXPRESS
CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM

24" STAND DEPTH: MAX FACE AREA (2760in² - 11520in²), FRAME QUANTITY (5-8 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 8 FRAMES				MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2760 in²	200.0 PSF	157.8 PSF	171.4 PSF	135.3 PSF	176.3 PSF	139.2 PSF	150.0 PSF	118.4 PSF	151.1 PSF	119.3 PSF	128.7 PSF	101.6 PSF	125.9 PSF	99.4 PSF	107.4 PSF	84.7 PSF	247.00 LB-FT	241.4 LB	838.5 LB	684.6 LB
24 "			158.5 PSF	125.1 PSF	141.3 PSF	111.5 PSF	138.7 PSF	109.5 PSF	123.7 PSF	97.6 PSF	118.9 PSF	93.8 PSF	106.1 PSF	83.8 PSF	99.1 PSF	78.2 PSF	88.5 PSF	69.9 PSF	247.00 LB-FT	189.9 LB	753.3 LB	662.4 LB
30 "			130.6 PSF	103.1 PSF	130.6 PSF	103.1 PSF	114.3 PSF	90.2 PSF	114.3 PSF	90.2 PSF	98.0 PSF	77.3 PSF	98.0 PSF	77.3 PSF	81.6 PSF	64.4 PSF	81.6 PSF	64.4 PSF	245.70 LB-FT	156.5 LB	696.5 LB	647.8 LB
36 "			104.2 PSF	82.3 PSF	104.2 PSF	82.3 PSF	91.2 PSF	72.0 PSF	91.2 PSF	72.0 PSF	78.1 PSF	61.7 PSF	78.1 PSF	61.7 PSF	65.1 PSF	51.4 PSF	65.1 PSF	51.4 PSF	229.00 LB-FT	124.8 LB	615.3 LB	606.6 LB
18 "	30 "	4650 in²	119.6 PSF	94.4 PSF	100.1 PSF	79.1 PSF	104.6 PSF	82.6 PSF	87.7 PSF	69.2 PSF	89.7 PSF	70.8 PSF	75.2 PSF	59.4 PSF	59.0 PSF	62.7 PSF	49.5 PSF	49.5 PSF	247.00 LB-FT	241.4 LB	900.9 LB	745.0 LB
24 "			94.1 PSF	74.3 PSF	82.8 PSF	65.3 PSF	82.3 PSF	65.0 PSF	72.5 PSF	57.2 PSF	70.5 PSF	55.7 PSF	62.2 PSF	49.1 PSF	58.8 PSF	46.4 PSF	51.9 PSF	40.9 PSF	247.00 LB-FT	189.9 LB	800.7 LB	709.9 LB
30 "			77.5 PSF	61.2 PSF	77.5 PSF	61.2 PSF	67.8 PSF	53.5 PSF	67.8 PSF	53.5 PSF	58.1 PSF	45.9 PSF	58.1 PSF	45.9 PSF	48.4 PSF	38.2 PSF	48.4 PSF	38.2 PSF	245.70 LB-FT	156.5 LB	735.7 LB	687.0 LB
36 "			61.8 PSF	48.8 PSF	61.8 PSF	48.8 PSF	54.1 PSF	42.7 PSF	54.1 PSF	42.7 PSF	46.4 PSF	36.6 PSF	46.4 PSF	36.6 PSF	38.6 PSF	30.5 PSF	38.6 PSF	30.5 PSF	229.00 LB-FT	124.8 LB	646.5 LB	637.8 LB
18 "	36 "	6300 in²	88.3 PSF	69.7 PSF	72.8 PSF	57.5 PSF	77.2 PSF	61.0 PSF	63.7 PSF	50.3 PSF	66.2 PSF	52.2 PSF	54.7 PSF	43.1 PSF	55.1 PSF	43.5 PSF	45.6 PSF	36.0 PSF	247.00 LB-FT	241.4 LB	961.3 LB	805.3 LB
24 "			69.4 PSF	54.8 PSF	60.3 PSF	47.6 PSF	60.7 PSF	47.9 PSF	52.8 PSF	41.7 PSF	52.1 PSF	41.1 PSF	45.3 PSF	35.8 PSF	43.4 PSF	34.2 PSF	37.8 PSF	29.8 PSF	247.00 LB-FT	189.9 LB	848.2 LB	757.3 LB
30 "			57.2 PSF	45.1 PSF	57.2 PSF	45.1 PSF	50.0 PSF	39.5 PSF	50.0 PSF	39.5 PSF	42.9 PSF	33.8 PSF	42.9 PSF	33.8 PSF	35.7 PSF	28.2 PSF	35.7 PSF	28.2 PSF	245.70 LB-FT	156.5 LB	774.8 LB	726.1 LB
36 "			45.6 PSF	36.0 PSF	45.6 PSF	36.0 PSF	39.9 PSF	31.5 PSF	39.9 PSF	31.5 PSF	34.2 PSF	27.0 PSF	34.2 PSF	27.0 PSF	28.5 PSF	22.5 PSF	28.5 PSF	22.5 PSF	229.00 LB-FT	124.8 LB	677.7 LB	669.0 LB
18 "	42 "	8400 in²	65.8 PSF	52.0 PSF	53.8 PSF	42.5 PSF	57.6 PSF	45.5 PSF	47.1 PSF	37.2 PSF	49.4 PSF	39.0 PSF	40.4 PSF	31.9 PSF	41.2 PSF	32.5 PSF	33.7 PSF	26.6 PSF	246.30 LB-FT	240.7 LB	1016.2 LB	863.4 LB
24 "			52.1 PSF	41.1 PSF	44.7 PSF	35.3 PSF	45.5 PSF	35.9 PSF	39.1 PSF	30.9 PSF	39.0 PSF	30.8 PSF	33.5 PSF	26.5 PSF	32.5 PSF	25.7 PSF	28.0 PSF	22.1 PSF	247.00 LB-FT	189.9 LB	895.7 LB	804.8 LB
30 "			42.9 PSF	33.8 PSF	42.9 PSF	33.8 PSF	37.5 PSF	29.6 PSF	37.5 PSF	29.6 PSF	32.2 PSF	25.4 PSF	32.2 PSF	25.4 PSF	26.8 PSF	21.1 PSF	26.8 PSF	21.1 PSF	245.70 LB-FT	156.5 LB	813.9 LB	765.2 LB
36 "			34.2 PSF	27.0 PSF	34.2 PSF	27.0 PSF	29.9 PSF	23.6 PSF	29.9 PSF	23.6 PSF	25.6 PSF	20.2 PSF	25.6 PSF	20.2 PSF	21.4 PSF	16.9 PSF	21.4 PSF	16.9 PSF	229.00 LB-FT	124.8 LB	708.9 LB	700.2 LB
18 "	48 "	11520 in²	45.8 PSF	36.1 PSF	38.6 PSF	30.5 PSF	41.4 PSF	32.6 PSF	33.8 PSF	26.7 PSF	35.5 PSF	28.0 PSF	29.0 PSF	22.9 PSF	29.6 PSF	23.3 PSF	24.2 PSF	19.1 PSF	242.50 LB-FT	237.0 LB	1058.1 LB	911.5 LB
24 "			37.9 PSF	29.9 PSF	32.2 PSF	25.4 PSF	33.2 PSF	26.2 PSF	28.2 PSF	22.2 PSF	28.4 PSF	22.4 PSF	24.2 PSF	19.1 PSF	23.7 PSF	18.7 PSF	20.1 PSF	15.9 PSF	247.00 LB-FT	189.9 LB	943.2 LB	852.3 LB
30 "			31.3 PSF	24.7 PSF	31.3 PSF	24.7 PSF	27.3 PSF	21.6 PSF	27.3 PSF	21.6 PSF	23.4 PSF	18.5 PSF	23.4 PSF	18.5 PSF					245.70 LB-FT	156.5 LB	853.1 LB	781.9 LB
36 "			24.9 PSF	19.7 PSF	24.9 PSF	19.7 PSF	21.8 PSF	17.2 PSF	21.8 PSF	17.2 PSF									229.00 LB-FT	124.8 LB	740.2 LB	692.9 LB

36" STAND DEPTH: MAX FACE AREA (2760in² - 11520in²), FRAME QUANTITY (5-8 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)	
			MAX FACE AREA : 8 FRAMES				MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES								
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3						
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT					
18 "	24 "	2760 in²	188.0 PSF	148.4 PSF	172.8 PSF	136.4 PSF	164.5 PSF	129.9 PSF	151.3 PSF	119.4 PSF	141.0 PSF	111.3 PSF	129.7 PSF	102.4 PSF	117.5 PSF	92.7 PSF	108.2 PSF	85.4 PSF	247.00 LB-FT	225.2 LB	576.8 LB	441.3 LB	
24 "			148.1 PSF	116.9 PSF	142.1 PSF	112.1 PSF	129.6 PSF	102.3 PSF	124.4 PSF	98.2 PSF	111.1 PSF	87.7 PSF	106.7 PSF	84.2 PSF	92.6 PSF	73.1 PSF	89.0 PSF	70.2 PSF	247.00 LB-FT	177.4 LB	510.6 LB	435.4 LB	
30 "			123.1 PSF	97.1 PSF	123.1 PSF	97.1 PSF	107.7 PSF	85.0 PSF	107.7 PSF	85.0 PSF	92.3 PSF	72.8 PSF	92.3 PSF	72.8 PSF	76.9 PSF	60.7 PSF	76.9 PSF	60.7 PSF	247.00 LB-FT	147.4 LB	471.0 LB	433.8 LB	
36 "			105.7 PSF	83.4 PSF	105.7 PSF	83.4 PSF	92.5 PSF	73.0 PSF	92.5 PSF	73.0 PSF	79.2 PSF	62.5 PSF	79.2 PSF	62.5 PSF	66.0 PSF	52.1 PSF	66.0 PSF	52.1 PSF	247.00 LB-FT	126.6 LB	444.7 LB	433.8 LB	
18 "	30 "	4650 in²	111.6 PSF	88.1 PSF	101.5 PSF	80.1 PSF	97.6 PSF	77.1 PSF	88.8 PSF	70.1 PSF	83.7 PSF	66.0 PSF	76.2 PSF	60.2 PSF	69.7 PSF	55.0 PSF	63.6 PSF	50.2 PSF	247.00 LB-FT	225.2 LB	614.3 LB	478.8 LB	
24 "			87.9 PSF	69.4 PSF	83.6 PSF	66.0 PSF	76.9 PSF	60.7 PSF	73.2 PSF	57.8 PSF	65.9 PSF	52.0 PSF	62.8 PSF	49.5 PSF	54.9 PSF	43.3 PSF	52.4 PSF	41.3 PSF	247.00 LB-FT	177.4 LB	540.2 LB	465.0 LB	
30 "			73.0 PSF	57.6 PSF	73.0 PSF	57.6 PSF	63.9 PSF	50.4 PSF	63.9 PSF	50.4 PSF	54.8 PSF	43.2 PSF	54.8 PSF	43.2 PSF	45.6 PSF	36.0 PSF	45.6 PSF	36.0 PSF	247.00 LB-FT	147.4 LB	495.6 LB	458.4 LB	
36 "			62.7 PSF	49.5 PSF	62.7 PSF	49.5 PSF	54.9 PSF	43.3 PSF	54.9 PSF	43.3 PSF	47.0 PSF	37.1 PSF	47.0 PSF	37.1 PSF	39.2 PSF	30.9 PSF	39.2 PSF	30.9 PSF	247.00 LB-FT	126.6 LB	465.8 LB	454.9 LB	
18 "	36 "	6300 in²	82.3 PSF	65.0 PSF	74.1 PSF	58.5 PSF	72.0 PSF	56.9 PSF	64.9 PSF	51.2 PSF	61.7 PSF	43.9 PSF	55.7 PSF	43.9 PSF	51.4 PSF	40.6 PSF	46.4 PSF	36.6 PSF	247.00 LB-FT	225.2 LB	651.9 LB	516.4 LB	
24 "			64.9 PSF	51.2 PSF	61.2 PSF	48.3 PSF	56.7 PSF	44.8 PSF	53.5 PSF	42.3 PSF	48.6 PSF	38.4 PSF	45.9 PSF	36.2 PSF	40.5 PSF	32.0 PSF	38.3 PSF	30.2 PSF	247.00 LB-FT	177.4 LB	569.8 LB	494.6 LB	
30 "			53.9 PSF	42.5 PSF	53.9 PSF	42.5 PSF	47.1 PSF	37.2 PSF	47.1 PSF	37.2 PSF	40.4 PSF	31.9 PSF	40.4 PSF	31.9 PSF	33.7 PSF	26.6 PSF	33.7 PSF	26.6 PSF	247.00 LB-FT	147.4 LB	520.2 LB	482.9 LB	
36 "			46.3 PSF	36.5 PSF	46.3 PSF	36.5 PSF	40.5 PSF	31.9 PSF	40.5 PSF	31.9 PSF	34.7 PSF	27.4 PSF	34.7 PSF	27.4 PSF	28.9 PSF	22.8 PSF	28.9 PSF	22.8 PSF	247.00 LB-FT	126.6 LB	486.9 LB	476.0 LB	
18 "	42 "	8400 in²	61.7 PSF	48.7 PSF	55.0 PSF	43.4 PSF	54.0 PSF	42.6 PSF	48.2 PSF	38.0 PSF	46.3 PSF	36.5 PSF	41.3 PSF	32.6 PSF	38.6 PSF	30.4 PSF	34.5 PSF	27.2 PSF	247.00 LB-FT	225.2 LB	689.4 LB	553.9 LB	
24 "			48.6 PSF	38.4 PSF	45.5 PSF	35.9 PSF	42.5 PSF	33.6 PSF	39.8 PSF	31.4 PSF	36.5 PSF	28.8 PSF	34.1 PSF	26.9 PSF	30.4 PSF	24.0 PSF	28.5 PSF	22.5 PSF	247.00 LB-FT	177.4 LB	599.3 LB	524.2 LB	
30 "			40.4 PSF	31.9 PSF	40.4 PSF	31.9 PSF	35.3 PSF	27.9 PSF	35.3 PSF	27.9 PSF	30.3 PSF	23.9 PSF	30.3 PSF	23.9 PSF	25.2 PSF	19.9 PSF	25.2 PSF	19.9 PSF	247.00 LB-FT	147.4 LB	544.7 LB	507.5 LB	
36 "			34.7 PSF	27.4 PSF	34.7 PSF	27.4 PSF	30.3 PSF	23.9 PSF	30.3 PSF	23.9 PSF	26.0 PSF	20.5 PSF	26.0 PSF	20.5 PSF	21.7 PSF	17.1 PSF	21.7 PSF	17.1 PSF	247.00 LB-FT	126.6 LB	508.0 LB	497.1 LB	
18 "	48 "	11520 in²	45.0 PSF	35.5 PSF	39.7 PSF	31.3 PSF	39.4 PSF	31.1 PSF	34.8 PSF	27.4 PSF	33.7 PSF	26.6 PSF	29.8 PSF	23.5 PSF	28.1 PSF	22.2 PSF	24.9 PSF	19.6 PSF	247.00 LB-FT	225.2 LB	727.0 LB	591.5 LB	
24 "			35.4 PSF	28.0 PSF	32.9 PSF	25.9 PSF	31.0 PSF	24.5 PSF	28.8 PSF	22.7 PSF	26.6 PSF	21.0 PSF	24.7 PSF	19.5 PSF	22.1 PSF	17.5 PSF	20.6 PSF	16.2 PSF	247.00 LB-FT	177.4 LB	628.9 LB	553.8 LB	
30 "			29.4 PSF	23.2 PSF	29.4 PSF	23.2 PSF	25.8 PSF	20.3 PSF	25.8 PSF	20.3 PSF	22.1 PSF	17.4 PSF	22.1 PSF	17.4 PSF						247.00 LB-FT	147.4 LB	569.3 LB	509.6 LB
36 "			25.3 PSF	19.9 PSF	25.3 PSF	19.9 PSF	22.1 PSF	17.4 PSF	22.1 PSF	17.4 PSF										247.00 LB-FT	126.6 LB	529.1 LB	479.6 LB

"HD" STAND DESIGN SCHEDULE CONTINUED

FRANK BENNARDO, PE
PE# 0046549 CA# 9885



36" STAND DEPTH: MAX FACE AREA (2208in² - 9216in²), FRAME QUANTITY (4-7 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2208 in ²	200.0 PSF	157.8 PSF	188.9 PSF	149.1 PSF	176.3 PSF	139.1 PSF	162.0 PSF	127.9 PSF	146.9 PSF	115.9 PSF	135.1 PSF	106.7 PSF	117.5 PSF	92.7 PSF	108.2 PSF	85.4 PSF	247.00 LB-FT	225.2 LB	575.8 LB	441.3 LB
24 "			162.0 PSF	127.9 PSF	155.3 PSF	122.6 PSF	138.9 PSF	109.6 PSF	133.2 PSF	105.2 PSF	115.7 PSF	91.3 PSF	111.1 PSF	87.7 PSF	92.6 PSF	73.1 PSF	89.0 PSF	70.2 PSF	247.00 LB-FT	177.4 LB	511.8 LB	435.4 LB
30 "			134.6 PSF	106.3 PSF	134.6 PSF	106.3 PSF	115.4 PSF	91.1 PSF	115.4 PSF	91.1 PSF	96.1 PSF	75.9 PSF	96.1 PSF	75.9 PSF	76.9 PSF	60.7 PSF	76.9 PSF	60.7 PSF	247.00 LB-FT	147.4 LB	472.2 LB	433.8 LB
36 "			115.6 PSF	91.2 PSF	115.6 PSF	91.2 PSF	99.1 PSF	78.2 PSF	99.1 PSF	78.2 PSF	82.5 PSF	65.2 PSF	82.5 PSF	65.2 PSF	66.0 PSF	52.1 PSF	66.0 PSF	52.1 PSF	247.00 LB-FT	126.6 LB	445.9 LB	433.8 LB
18 "	30 "	3720 in ²	122.0 PSF	96.3 PSF	111.0 PSF	87.6 PSF	104.6 PSF	82.6 PSF	95.2 PSF	75.1 PSF	87.2 PSF	68.8 PSF	79.4 PSF	62.6 PSF	69.7 PSF	55.0 PSF	63.6 PSF	50.2 PSF	247.00 LB-FT	225.2 LB	615.5 LB	478.8 LB
24 "			96.1 PSF	75.9 PSF	91.4 PSF	72.1 PSF	82.4 PSF	65.0 PSF	78.4 PSF	61.9 PSF	68.7 PSF	54.2 PSF	65.4 PSF	51.6 PSF	54.9 PSF	43.3 PSF	52.4 PSF	41.3 PSF	247.00 LB-FT	177.4 LB	541.4 LB	465.0 LB
30 "			79.9 PSF	63.0 PSF	79.9 PSF	63.0 PSF	68.5 PSF	54.0 PSF	68.5 PSF	54.0 PSF	57.0 PSF	45.0 PSF	57.0 PSF	45.0 PSF	45.6 PSF	36.0 PSF	45.6 PSF	36.0 PSF	247.00 LB-FT	147.4 LB	496.8 LB	458.4 LB
36 "			68.6 PSF	54.1 PSF	68.6 PSF	54.1 PSF	58.8 PSF	46.4 PSF	58.8 PSF	46.4 PSF	49.0 PSF	38.7 PSF	49.0 PSF	38.7 PSF	39.2 PSF	30.9 PSF	39.2 PSF	30.9 PSF	247.00 LB-FT	126.6 LB	467.0 LB	454.9 LB
18 "	36 "	5040 in ²	90.1 PSF	71.1 PSF	81.1 PSF	64.0 PSF	77.2 PSF	60.9 PSF	69.5 PSF	54.9 PSF	64.3 PSF	50.8 PSF	58.0 PSF	45.8 PSF	51.4 PSF	40.6 PSF	46.4 PSF	36.6 PSF	247.00 LB-FT	225.2 LB	653.1 LB	516.4 LB
24 "			70.9 PSF	56.0 PSF	66.9 PSF	52.8 PSF	60.8 PSF	48.0 PSF	57.4 PSF	45.3 PSF	50.7 PSF	40.0 PSF	47.8 PSF	37.8 PSF	40.5 PSF	32.0 PSF	38.3 PSF	30.2 PSF	247.00 LB-FT	177.4 LB	571.0 LB	494.6 LB
30 "			58.9 PSF	46.5 PSF	58.9 PSF	46.5 PSF	50.5 PSF	39.9 PSF	50.5 PSF	39.9 PSF	42.1 PSF	33.2 PSF	42.1 PSF	33.2 PSF	33.7 PSF	26.6 PSF	33.7 PSF	26.6 PSF	247.00 LB-FT	147.4 LB	521.4 LB	482.9 LB
36 "			50.6 PSF	39.9 PSF	50.6 PSF	39.9 PSF	43.4 PSF	34.2 PSF	43.4 PSF	34.2 PSF	36.1 PSF	28.5 PSF	36.1 PSF	28.5 PSF	28.9 PSF	22.8 PSF	28.9 PSF	22.8 PSF	247.00 LB-FT	126.6 LB	488.1 LB	476.0 LB
18 "	42 "	6720 in ²	67.5 PSF	53.3 PSF	60.2 PSF	47.5 PSF	57.9 PSF	45.7 PSF	51.6 PSF	40.7 PSF	48.2 PSF	38.1 PSF	43.0 PSF	34.0 PSF	38.6 PSF	30.4 PSF	34.5 PSF	27.2 PSF	247.00 LB-FT	225.2 LB	690.6 LB	553.9 LB
24 "			53.2 PSF	42.0 PSF	49.7 PSF	39.3 PSF	45.6 PSF	36.0 PSF	42.6 PSF	33.7 PSF	38.0 PSF	30.0 PSF	35.6 PSF	28.1 PSF	30.4 PSF	24.0 PSF	28.5 PSF	22.5 PSF	247.00 LB-FT	177.4 LB	600.5 LB	524.2 LB
30 "			44.2 PSF	34.9 PSF	44.2 PSF	34.9 PSF	37.9 PSF	29.9 PSF	37.9 PSF	29.9 PSF	31.6 PSF	24.9 PSF	31.6 PSF	24.9 PSF	25.2 PSF	19.9 PSF	25.2 PSF	19.9 PSF	247.00 LB-FT	147.4 LB	545.9 LB	507.5 LB
36 "			37.9 PSF	29.9 PSF	37.9 PSF	29.9 PSF	32.5 PSF	25.7 PSF	32.5 PSF	25.7 PSF	27.1 PSF	21.4 PSF	27.1 PSF	21.4 PSF	21.7 PSF	17.1 PSF	21.7 PSF	17.1 PSF	247.00 LB-FT	126.6 LB	509.2 LB	497.1 LB
18 "	48 "	9216 in ²	49.2 PSF	38.9 PSF	43.4 PSF	34.3 PSF	42.2 PSF	33.3 PSF	37.2 PSF	29.4 PSF	35.2 PSF	27.7 PSF	31.1 PSF	24.5 PSF	28.1 PSF	22.2 PSF	24.9 PSF	19.6 PSF	247.00 LB-FT	225.2 LB	728.2 LB	591.5 LB
24 "			38.8 PSF	30.6 PSF	36.0 PSF	28.4 PSF	33.2 PSF	26.2 PSF	30.8 PSF	24.3 PSF	27.7 PSF	21.8 PSF	25.7 PSF	20.3 PSF	22.1 PSF	17.5 PSF	20.6 PSF	16.2 PSF	247.00 LB-FT	177.4 LB	630.1 LB	553.8 LB
30 "			32.2 PSF	25.4 PSF	32.2 PSF	25.4 PSF	27.6 PSF	21.8 PSF	27.6 PSF	21.8 PSF	23.0 PSF	18.1 PSF	23.0 PSF	18.1 PSF	22.1 PSF	17.5 PSF	20.6 PSF	16.2 PSF	247.00 LB-FT	147.4 LB	570.5 LB	505.1 LB
36 "			27.7 PSF	21.8 PSF	27.7 PSF	21.8 PSF	23.7 PSF	18.7 PSF	23.7 PSF	18.7 PSF	23.0 PSF	18.1 PSF	23.0 PSF	18.1 PSF	22.1 PSF	17.5 PSF	20.6 PSF	16.2 PSF	247.00 LB-FT	126.6 LB	530.3 LB	473.2 LB

24" STAND DEPTH: MAX FACE AREA (1656in² - 6912in²), FRAME QUANTITY (3-6 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	1656 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	178.5 PSF	140.9 PSF	167.9 PSF	132.6 PSF	142.9 PSF	112.8 PSF	125.9 PSF	99.4 PSF	107.4 PSF	84.7 PSF	247.00 LB-FT	241.4 LB	837.7 LB	684.6 LB
24 "			198.2 PSF	156.4 PSF	176.5 PSF	139.3 PSF	165.1 PSF	130.4 PSF	147.1 PSF	116.2 PSF	132.1 PSF	104.3 PSF	117.8 PSF	93.0 PSF	99.1 PSF	78.2 PSF	88.5 PSF	69.9 PSF	247.00 LB-FT	189.9 LB	756.1 LB	662.4 LB
30 "			163.3 PSF	128.9 PSF	163.3 PSF	128.9 PSF	136.1 PSF	107.4 PSF	136.1 PSF	107.4 PSF	108.9 PSF	85.9 PSF	108.9 PSF	85.9 PSF	81.6 PSF	64.4 PSF	81.6 PSF	64.4 PSF	245.70 LB-FT	156.5 LB	699.3 LB	647.8 LB
36 "			130.3 PSF	102.8 PSF	130.3 PSF	102.8 PSF	108.5 PSF	85.7 PSF	108.5 PSF	85.7 PSF	86.8 PSF	68.5 PSF	86.8 PSF	68.5 PSF	65.1 PSF	51.4 PSF	65.1 PSF	51.4 PSF	229.00 LB-FT	124.8 LB	618.1 LB	606.6 LB
18 "	30 "	2790 in²	142.9 PSF	112.8 PSF	125.1 PSF	98.7 PSF	124.6 PSF	98.3 PSF	104.3 PSF	82.3 PSF	99.7 PSF	78.7 PSF	83.5 PSF	65.9 PSF	74.7 PSF	59.0 PSF	62.7 PSF	49.5 PSF	247.00 LB-FT	241.4 LB	901.5 LB	745.0 LB
24 "			117.6 PSF	92.8 PSF	103.4 PSF	81.6 PSF	98.0 PSF	77.4 PSF	86.2 PSF	68.1 PSF	78.4 PSF	61.9 PSF	69.0 PSF	54.5 PSF	58.8 PSF	46.4 PSF	51.9 PSF	40.9 PSF	247.00 LB-FT	189.9 LB	803.6 LB	709.9 LB
30 "			96.9 PSF	76.5 PSF	96.9 PSF	76.5 PSF	80.7 PSF	63.7 PSF	80.7 PSF	63.7 PSF	64.6 PSF	51.0 PSF	64.6 PSF	51.0 PSF	48.4 PSF	38.2 PSF	48.4 PSF	38.2 PSF	245.70 LB-FT	156.5 LB	738.5 LB	687.0 LB
36 "			77.3 PSF	61.0 PSF	77.3 PSF	61.0 PSF	64.4 PSF	50.8 PSF	64.4 PSF	50.8 PSF	51.5 PSF	40.7 PSF	51.5 PSF	40.7 PSF	38.6 PSF	30.5 PSF	38.6 PSF	30.5 PSF	229.00 LB-FT	124.8 LB	649.3 LB	637.8 LB
18 "	36 "	3780 in²	97.1 PSF	87.1 PSF	90.9 PSF	71.8 PSF	91.9 PSF	72.6 PSF	75.8 PSF	59.9 PSF	73.5 PSF	58.0 PSF	60.7 PSF	47.9 PSF	55.1 PSF	43.5 PSF	45.6 PSF	36.0 PSF	247.00 LB-FT	241.4 LB	964.1 LB	805.3 LB
24 "			86.8 PSF	68.5 PSF	75.4 PSF	59.5 PSF	72.3 PSF	57.1 PSF	62.8 PSF	49.6 PSF	57.8 PSF	45.7 PSF	50.3 PSF	39.7 PSF	43.4 PSF	34.2 PSF	37.8 PSF	29.8 PSF	247.00 LB-FT	189.9 LB	851.1 LB	757.3 LB
30 "			71.5 PSF	56.4 PSF	71.5 PSF	56.4 PSF	59.6 PSF	47.0 PSF	59.6 PSF	47.0 PSF	47.7 PSF	37.6 PSF	47.7 PSF	37.6 PSF	35.7 PSF	28.2 PSF	35.7 PSF	28.2 PSF	245.70 LB-FT	156.5 LB	777.6 LB	726.1 LB
36 "			57.0 PSF	45.0 PSF	57.0 PSF	45.0 PSF	47.5 PSF	37.5 PSF	47.5 PSF	37.5 PSF	38.0 PSF	30.0 PSF	38.0 PSF	30.0 PSF	28.9 PSF	22.5 PSF	28.9 PSF	22.5 PSF	229.00 LB-FT	124.8 LB	680.5 LB	669.0 LB
18 "	42 "	5040 in²	67.5 PSF	64.9 PSF	67.2 PSF	53.0 PSF	67.5 PSF	54.1 PSF	56.0 PSF	44.2 PSF	54.9 PSF	43.3 PSF	44.9 PSF	35.4 PSF	41.2 PSF	32.5 PSF	33.7 PSF	26.6 PSF	246.30 LB-FT	240.7 LB	1018.2 LB	863.4 LB
24 "			65.1 PSF	51.4 PSF	55.8 PSF	44.1 PSF	54.2 PSF	42.8 PSF	46.5 PSF	36.7 PSF	43.4 PSF	37.3 PSF	39.4 PSF	32.5 PSF	32.5 PSF	25.7 PSF	28.0 PSF	22.1 PSF	247.00 LB-FT	189.9 LB	898.5 LB	804.8 LB
30 "			53.6 PSF	42.3 PSF	53.6 PSF	42.3 PSF	44.7 PSF	35.3 PSF	44.7 PSF	35.3 PSF	35.7 PSF	28.2 PSF	35.7 PSF	28.2 PSF	26.8 PSF	21.1 PSF	26.8 PSF	21.1 PSF	245.70 LB-FT	156.5 LB	816.7 LB	765.2 LB
36 "			42.8 PSF	33.8 PSF	42.8 PSF	33.8 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	28.5 PSF	22.5 PSF	28.5 PSF	22.5 PSF	21.4 PSF	16.9 PSF	21.4 PSF	16.9 PSF	229.00 LB-FT	124.8 LB	711.7 LB	700.2 LB
18 "	48 "	6912 in²	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	40.2 PSF	31.8 PSF	39.4 PSF	31.1 PSF	32.2 PSF	25.4 PSF	29.6 PSF	23.3 PSF	24.2 PSF	19.1 PSF	242.50 LB-FT	237.0 LB	1057.5 LB	911.5 LB
24 "			45.8 PSF	36.1 PSF	40.2 PSF	31.7 PSF	39.5 PSF	31.2 PSF	33.5 PSF	26.4 PSF	31.6 PSF	24.9 PSF	26.8 PSF	21.2 PSF	23.7 PSF	18.7 PSF	20.1 PSF	15.9 PSF	247.00 LB-FT	189.9 LB	943.8 LB	852.3 LB
30 "			39.1 PSF	30.8 PSF	39.1 PSF	30.8 PSF	32.6 PSF	25.7 PSF	32.6 PSF	25.7 PSF	26.0 PSF	20.5 PSF	26.0 PSF	20.5 PSF	20.5 PSF	15.4 PSF	15.4 PSF	15.4 PSF	245.70 LB-FT	156.5 LB	855.9 LB	770.6 LB
36 "			31.2 PSF	24.6 PSF	31.2 PSF	24.6 PSF	26.0 PSF	20.5 PSF	26.0 PSF	20.5 PSF	20.8 PSF	16.4 PSF	20.8 PSF	16.4 PSF	16.4 PSF	12.4 PSF	12.4 PSF	12.4 PSF	229.00 LB-FT	124.8 LB	743.0 LB	697.7 LB

"HD" STAND DESIGN SCHEDULE CONTINUED

24" STAND DEPTH: MAX FACE AREA (1104in² - 4608in²), FRAME QUANTITY (2-5 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)	
			MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES								
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3						
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT					
18 "	24 "	1104 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	188.9 PSF	149.1 PSF	160.7 PSF	126.9 PSF	125.9 PSF	99.4 PSF	107.4 PSF	84.7 PSF	247.00 LB-FT	241.4 LB	839.6 LB	684.6 LB	
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	198.2 PSF	156.4 PSF	176.5 PSF	139.3 PSF	148.6 PSF	117.3 PSF	132.5 PSF	104.6 PSF	99.1 PSF	78.2 PSF	88.5 PSF	69.9 PSF	247.00 LB-FT	189.9 LB	756.1 LB	662.4 LB	
30 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	163.3 PSF	128.9 PSF	163.3 PSF	128.9 PSF	122.3 PSF	96.7 PSF	122.5 PSF	96.7 PSF	81.6 PSF	64.4 PSF	81.6 PSF	64.4 PSF	245.70 LB-FT	156.5 LB	699.3 LB	647.8 LB	
36 "	30 "	1860 in²	162.8 PSF	128.6 PSF	162.8 PSF	128.6 PSF	130.3 PSF	102.8 PSF	130.3 PSF	102.8 PSF	97.7 PSF	77.1 PSF	97.7 PSF	77.1 PSF	65.1 PSF	51.4 PSF	65.1 PSF	51.4 PSF	229.00 LB-FT	124.8 LB	620.3 LB	606.6 LB	
18 "			142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	125.1 PSF	98.7 PSF	122.1 PSF	88.5 PSF	93.9 PSF	74.1 PSF	74.7 PSF	59.0 PSF	62.7 PSF	49.5 PSF	247.00 LB-FT	241.4 LB	900.0 LB	745.0 LB	
24 "			142.9 PSF	112.8 PSF	129.2 PSF	102.0 PSF	117.6 PSF	92.8 PSF	103.4 PSF	81.6 PSF	88.2 PSF	69.6 PSF	77.6 PSF	61.3 PSF	58.8 PSF	46.4 PSF	51.9 PSF	40.9 PSF	247.00 LB-FT	189.9 LB	803.6 LB	709.9 LB	
30 "	36 "	2520 in²	121.1 PSF	95.6 PSF	121.1 PSF	95.6 PSF	96.9 PSF	76.5 PSF	96.9 PSF	76.5 PSF	72.7 PSF	57.4 PSF	72.7 PSF	57.4 PSF	48.4 PSF	38.2 PSF	48.4 PSF	38.2 PSF	245.70 LB-FT	156.5 LB	740.7 LB	687.0 LB	
18 "			96.6 PSF	76.3 PSF	96.6 PSF	76.3 PSF	77.3 PSF	61.0 PSF	77.3 PSF	61.0 PSF	58.0 PSF	45.7 PSF	58.0 PSF	45.7 PSF	38.6 PSF	30.5 PSF	38.6 PSF	30.5 PSF	229.00 LB-FT	124.8 LB	651.5 LB	637.8 LB	
24 "			97.1 PSF	108.9 PSF	97.1 PSF	89.7 PSF	97.1 PSF	87.1 PSF	90.9 PSF	71.8 PSF	82.7 PSF	65.3 PSF	68.3 PSF	55.1 PSF	43.5 PSF	45.6 PSF	45.6 PSF	36.0 PSF	247.00 LB-FT	241.4 LB	966.3 LB	805.3 LB	
30 "	42 "	3360 in²	97.1 PSF	85.6 PSF	94.2 PSF	74.3 PSF	86.8 PSF	68.5 PSF	75.4 PSF	59.5 PSF	65.1 PSF	51.4 PSF	56.6 PSF	44.7 PSF	43.4 PSF	34.2 PSF	37.8 PSF	29.8 PSF	247.00 LB-FT	189.9 LB	853.3 LB	757.3 LB	
18 "			89.4 PSF	70.6 PSF	89.4 PSF	70.6 PSF	71.5 PSF	56.4 PSF	71.5 PSF	56.4 PSF	53.6 PSF	42.3 PSF	53.6 PSF	42.3 PSF	35.7 PSF	28.2 PSF	35.7 PSF	28.2 PSF	245.70 LB-FT	156.5 LB	779.9 LB	726.1 LB	
24 "			71.3 PSF	56.3 PSF	71.3 PSF	56.3 PSF	57.0 PSF	45.0 PSF	57.0 PSF	45.0 PSF	42.8 PSF	33.8 PSF	42.8 PSF	33.8 PSF	28.5 PSF	22.5 PSF	28.5 PSF	22.5 PSF	229.00 LB-FT	124.8 LB	682.8 LB	669.0 LB	
36 "	48 "	4608 in²	67.5 PSF	81.1 PSF	67.5 PSF	66.3 PSF	67.5 PSF	64.9 PSF	67.2 PSF	53.0 PSF	61.7 PSF	48.7 PSF	50.4 PSF	39.8 PSF	41.2 PSF	32.5 PSF	33.7 PSF	26.6 PSF	246.30 LB-FT	240.7 LB	1019.9 LB	863.4 LB	
18 "			67.5 PSF	64.2 PSF	67.5 PSF	55.0 PSF	65.1 PSF	51.4 PSF	55.8 PSF	44.1 PSF	48.8 PSF	38.5 PSF	41.9 PSF	33.1 PSF	32.5 PSF	25.7 PSF	28.0 PSF	22.1 PSF	247.00 LB-FT	189.9 LB	900.8 LB	804.8 LB	
24 "			67.0 PSF	52.9 PSF	67.0 PSF	52.9 PSF	53.6 PSF	42.3 PSF	53.6 PSF	42.3 PSF	40.2 PSF	31.7 PSF	40.2 PSF	31.7 PSF	26.8 PSF	21.1 PSF	26.8 PSF	21.1 PSF	245.70 LB-FT	156.5 LB	819.0 LB	765.2 LB	
30 "			53.5 PSF	42.2 PSF	53.5 PSF	42.2 PSF	42.8 PSF	33.8 PSF	42.8 PSF	33.8 PSF	32.1 PSF	25.3 PSF	32.1 PSF	25.3 PSF	21.4 PSF	16.9 PSF	21.4 PSF	16.9 PSF	229.00 LB-FT	124.8 LB	714.0 LB	700.2 LB	
18 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	44.3 PSF	35.0 PSF	36.2 PSF	28.6 PSF	29.6 PSF	23.3 PSF	23.3 PSF	24.2 PSF	19.1 PSF	242.50 LB-FT	237.0 LB	1058.8 LB	911.5 LB
24 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	40.2 PSF	31.7 PSF	35.6 PSF	28.1 PSF	30.2 PSF	23.8 PSF	23.7 PSF	18.7 PSF	20.1 PSF	15.9 PSF	247.00 LB-FT	189.9 LB	942.3 LB	852.3 LB	
30 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	39.1 PSF	30.8 PSF	39.1 PSF	30.8 PSF	29.3 PSF	23.1 PSF	29.3 PSF	23.1 PSF					245.70 LB-FT	156.5 LB	855.9 LB	759.4 LB	
36 "			39.0 PSF	30.8 PSF	39.0 PSF	30.8 PSF	31.2 PSF	24.6 PSF	31.2 PSF	24.6 PSF	23.4 PSF	18.4 PSF	23.4 PSF	18.4 PSF					229.00 LB-FT	124.8 LB	745.2 LB	686.5 LB	

36" STAND DEPTH: MAX FACE AREA (1104in² - 4608in²), FRAME QUANTITY (2-5 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	1104 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	176.3 PSF	139.1 PSF	162.0 PSF	127.9 PSF	117.5 PSF	92.7 PSF	108.2 PSF	85.4 PSF	247.00 LB-FT	225.2 LB	575.8 LB	441.3 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	185.2 PSF	146.2 PSF	177.4 PSF	140.1 PSF	138.9 PSF	109.6 PSF	133.2 PSF	105.2 PSF	92.6 PSF	73.1 PSF	89.0 PSF	70.2 PSF	247.00 LB-FT	177.4 LB	513.4 LB	435.4 LB
30 "			192.3 PSF	151.8 PSF	192.3 PSF	151.8 PSF	153.8 PSF	121.4 PSF	153.8 PSF	121.4 PSF	115.4 PSF	91.1 PSF	115.4 PSF	91.1 PSF	76.9 PSF	60.7 PSF	76.9 PSF	60.7 PSF	247.00 LB-FT	147.4 LB	476.1 LB	433.8 LB
36 "	30 "	1860 in²	165.1 PSF	130.4 PSF	165.1 PSF	130.4 PSF	132.1 PSF	104.3 PSF	132.1 PSF	104.3 PSF	99.1 PSF	78.2 PSF	99.1 PSF	78.2 PSF	66.0 PSF	52.1 PSF	66.0 PSF	52.1 PSF	247.00 LB-FT	126.6 LB	449.8 LB	433.8 LB
18 "			156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	139.5 PSF	110.1 PSF	126.8 PSF	100.1 PSF	104.6 PSF	82.6 PSF	95.2 PSF	75.1 PSF	69.7 PSF	55.0 PSF	63.6 PSF	50.2 PSF	247.00 LB-FT	225.2 LB	617.1 LB	478.8 LB
24 "			137.4 PSF	108.4 PSF	130.4 PSF	103.0 PSF	109.9 PSF	86.7 PSF	104.4 PSF	82.4 PSF	82.4 PSF	65.0 PSF	78.4 PSF	61.9 PSF	54.9 PSF	43.3 PSF	52.4 PSF	41.3 PSF	247.00 LB-FT	177.4 LB	545.2 LB	465.0 LB
30 "	36 "	2520 in²	114.1 PSF	90.1 PSF	114.1 PSF	90.1 PSF	91.3 PSF	72.1 PSF	91.3 PSF	72.1 PSF	68.5 PSF	54.0 PSF	68.5 PSF	54.0 PSF	45.6 PSF	36.0 PSF	45.6 PSF	36.0 PSF	247.00 LB-FT	147.4 LB	500.6 LB	458.4 LB
18 "			98.0 PSF	77.4 PSF	98.0 PSF	77.4 PSF	78.4 PSF	61.9 PSF	78.4 PSF	61.9 PSF	58.8 PSF	46.4 PSF	58.8 PSF	46.4 PSF	39.2 PSF	30.9 PSF	39.2 PSF	30.9 PSF	247.00 LB-FT	126.6 LB	470.9 LB	454.9 LB
24 "			115.4 PSF	101.6 PSF	115.4 PSF	91.3 PSF	102.9 PSF	81.3 PSF	92.6 PSF	73.1 PSF	77.2 PSF	60.9 PSF	69.5 PSF	54.9 PSF	51.4 PSF	40.6 PSF	46.4 PSF	36.6 PSF	247.00 LB-FT	225.2 LB	656.9 LB	516.4 LB
30 "	42 "	3360 in²	101.4 PSF	80.6 PSF	95.5 PSF	75.4 PSF	81.1 PSF	64.0 PSF	60.3 PSF	60.8 PSF	48.0 PSF	57.4 PSF	45.3 PSF	40.5 PSF	32.0 PSF	30.2 PSF	38.3 PSF	30.2 PSF	247.00 LB-FT	177.4 LB	574.8 LB	494.6 LB
18 "			84.2 PSF	66.5 PSF	84.2 PSF	66.5 PSF	67.4 PSF	53.2 PSF	67.4 PSF	53.2 PSF	50.5 PSF	39.9 PSF	50.5 PSF	39.9 PSF	33.7 PSF	26.6 PSF	33.7 PSF	26.6 PSF	247.00 LB-FT	147.4 LB	525.2 LB	482.9 LB
24 "			72.3 PSF	57.1 PSF	72.3 PSF	57.1 PSF	57.8 PSF	45.7 PSF	57.8 PSF	45.7 PSF	43.4 PSF	34.2 PSF	43.4 PSF	34.2 PSF	28.9 PSF	22.8 PSF	28.9 PSF	22.8 PSF	247.00 LB-FT	126.6 LB	492.0 LB	476.0 LB
36 "	48 "	4608 in²	81.4 PSF	76.2 PSF	81.4 PSF	67.8 PSF	77.2 PSF	60.9 PSF	68.7 PSF	54.3 PSF	57.9 PSF	45.7 PSF	51.6 PSF	40.7 PSF	38.6 PSF	30.4 PSF	34.5 PSF	27.2 PSF	247.00 LB-FT	225.2 LB	694.5 LB	553.9 LB
18 "			76.0 PSF	60.0 PSF	71.0 PSF	56.0 PSF	60.8 PSF	48.0 PSF	56.8 PSF	44.8 PSF	45.6 PSF	36.0 PSF	42.6 PSF	33.7 PSF	30.4 PSF	24.0 PSF	28.5 PSF	22.5 PSF	247.00 LB-FT	177.4 LB	604.4 LB	524.2 LB
24 "			63.2 PSF	49.8 PSF	63.2 PSF	49.8 PSF	50.5 PSF	39.9 PSF	50.5 PSF	39.9 PSF	37.9 PSF	29.9 PSF	37.9 PSF	29.9 PSF	25.2 PSF	19.9 PSF	25.2 PSF	19.9 PSF	247.00 LB-FT	147.4 LB	549.8 LB	507.5 LB
30 "			54.2 PSF	42.8 PSF	54.2 PSF	42.8 PSF	43.4 PSF	34.2 PSF	43.4 PSF	34.2 PSF	32.5 PSF	25.7 PSF	32.5 PSF	25.7 PSF	21.7 PSF	17.1 PSF	21.7 PSF	17.1 PSF	247.00 LB-FT	126.6 LB	513.1 LB	497.1 LB
18 "			56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	49.6 PSF	39.2 PSF	42.2 PSF	33.3 PSF	37.2 PSF	29.4 PSF	28.1 PSF	22.2 PSF	24.9 PSF	19.6 PSF	247.00 LB-FT	225.2 LB	726.9 LB	591.5 LB
24 "			55.4 PSF	43.7 PSF	51.3 PSF	40.5 PSF	44.3 PSF	35.0 PSF	41.1 PSF	32.4 PSF	33.2 PSF	26.2 PSF	30.8 PSF	24.3 PSF	22.1 PSF	17.3 PSF	20.6 PSF	16.2 PSF	247.00 LB-FT	177.4 LB	634.0 LB	553.8 LB
30 "			46.0 PSF	36.3 PSF	46.0 PSF	36.3 PSF	36.8 PSF	29.1 PSF	36.8 PSF	29.1 PSF	27.6 PSF	21.8 PSF	27.6 PSF	21.8 PSF					247.00 LB-FT	147.4 LB	574.4 LB	487.1 LB
36 "			39.5 PSF	31.2 PSF	39.5 PSF	31.2 PSF	31.6 PSF	24.9 PSF	31.6 PSF	24.9 PSF	23.7 PSF	18.7 PSF	23.7 PSF	18.7 PSF					247.00 LB-FT	126.6 LB	534.2 LB	473.2 LB

"HD" STAND DESIGN SCHEDULE CONTINUED

36" STAND DEPTH: MAX FACE AREA (552in² - 2304in²), FRAME QUANTITY (2-3 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO								MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	552 in ²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	210.20 LB-FT	191.6 LB	491.4 LB	328.0 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	185.2 PSF	146.2 PSF	177.4 PSF	140.1 PSF	247.00 LB-FT	177.4 LB	513.4 LB	367.9 LB
30 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	153.8 PSF	121.4 PSF	153.8 PSF	121.4 PSF	247.00 LB-FT	147.4 LB	473.8 LB	366.3 LB
36 "			198.2 PSF	156.4 PSF	198.2 PSF	156.4 PSF	132.1 PSF	104.3 PSF	132.1 PSF	104.3 PSF	247.00 LB-FT	126.6 LB	451.3 LB	366.3 LB
18 "	30 "	930 in ²	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	139.5 PSF	110.1 PSF	126.8 PSF	100.1 PSF	247.00 LB-FT	225.2 LB	617.1 LB	411.3 LB
24 "			156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	109.9 PSF	86.7 PSF	104.4 PSF	82.4 PSF	247.00 LB-FT	177.4 LB	543.0 LB	397.5 LB
30 "			137.0 PSF	108.1 PSF	137.0 PSF	108.1 PSF	91.3 PSF	72.1 PSF	91.3 PSF	72.1 PSF	247.00 LB-FT	147.4 LB	502.1 LB	390.9 LB
36 "			117.6 PSF	92.8 PSF	117.6 PSF	92.8 PSF	78.4 PSF	61.9 PSF	78.4 PSF	61.9 PSF	247.00 LB-FT	126.6 LB	472.4 LB	387.4 LB
18 "	36 "	1260 in ²	115.4 PSF	121.9 PSF	115.4 PSF	109.5 PSF	102.9 PSF	81.3 PSF	92.6 PSF	73.1 PSF	247.00 LB-FT	225.2 LB	658.4 LB	448.9 LB
24 "			115.4 PSF	96.0 PSF	114.5 PSF	90.4 PSF	81.1 PSF	64.0 PSF	76.4 PSF	60.3 PSF	247.00 LB-FT	177.4 LB	576.3 LB	427.1 LB
30 "			101.1 PSF	79.8 PSF	101.1 PSF	79.8 PSF	67.4 PSF	53.2 PSF	67.4 PSF	53.2 PSF	247.00 LB-FT	147.4 LB	526.7 LB	415.4 LB
36 "			86.8 PSF	68.5 PSF	86.8 PSF	68.5 PSF	57.8 PSF	45.7 PSF	57.8 PSF	45.7 PSF	247.00 LB-FT	126.6 LB	493.5 LB	408.5 LB
18 "	42 "	1680 in ²	81.4 PSF	91.4 PSF	81.4 PSF	81.3 PSF	77.2 PSF	60.9 PSF	68.7 PSF	54.3 PSF	247.00 LB-FT	225.2 LB	696.0 LB	486.4 LB
24 "			81.4 PSF	72.0 PSF	81.4 PSF	67.2 PSF	60.8 PSF	48.0 PSF	56.8 PSF	44.8 PSF	247.00 LB-FT	177.4 LB	605.9 LB	456.7 LB
30 "			75.8 PSF	59.8 PSF	75.8 PSF	59.8 PSF	50.5 PSF	39.9 PSF	50.5 PSF	39.9 PSF	247.00 LB-FT	147.4 LB	551.3 LB	440.0 LB
36 "			65.1 PSF	51.4 PSF	65.1 PSF	51.4 PSF	43.4 PSF	34.2 PSF	43.4 PSF	34.2 PSF	247.00 LB-FT	126.6 LB	514.6 LB	429.6 LB
18 "	48 "	2304 in ²	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	49.6 PSF	39.2 PSF	246.10 LB-FT	224.4 LB	726.9 LB	522.2 LB
24 "			56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	44.3 PSF	35.0 PSF	41.1 PSF	32.4 PSF	247.00 LB-FT	177.4 LB	631.7 LB	486.3 LB
30 "			55.3 PSF	43.6 PSF	55.3 PSF	43.6 PSF	36.8 PSF	29.1 PSF	36.8 PSF	29.1 PSF	247.00 LB-FT	147.4 LB	575.9 LB	464.6 LB
36 "			47.4 PSF	37.4 PSF	47.4 PSF	37.4 PSF	31.6 PSF	24.9 PSF	31.6 PSF	24.9 PSF	247.00 LB-FT	126.6 LB	535.7 LB	450.7 LB

DESIGN SCHEDULE NOTES:

1. MAXIMUM CALCULATED FACE AREA SHALL BE EQUAL TO OR LESS THAN THE MAXIMUM ALLOWABLE FACE AREA FOR EACH CONFIGURATION.
2. REFERENCE ANCHOR SCHEDULE FOR ANCHOR TYPES LISTED HEREIN.

"XHD" STAND DESIGN SCHEDULE

24" STAND DEPTH: MAX FACE AREA (2760in² - 11520in²), FRAME QUANTITY (5-8 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 8 FRAMES				MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
		MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT					
18 "	24 "	2760 in ²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	181.6 PSF	143.4 PSF	167.8 PSF	132.5 PSF	311.90 LB-FT	348.1 LB	1209.7 LB	1032.5 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	197.5 PSF	155.9 PSF	197.4 PSF	155.9 PSF	169.3 PSF	133.6 PSF	169.3 PSF	133.6 PSF	141.0 PSF	111.3 PSF	141.0 PSF	111.3 PSF	311.90 LB-FT	270.4 LB	1076.3 LB	990.8 LB
30 "			184.9 PSF	145.9 PSF	184.9 PSF	145.9 PSF	161.7 PSF	127.7 PSF	161.7 PSF	127.7 PSF	138.6 PSF	109.4 PSF	138.6 PSF	109.4 PSF	115.5 PSF	91.2 PSF	115.5 PSF	91.2 PSF	311.90 LB-FT	221.4 LB	991.4 LB	965.7 LB
36 "			156.7 PSF	123.7 PSF	156.7 PSF	123.7 PSF	137.1 PSF	108.2 PSF	137.1 PSF	108.2 PSF	117.5 PSF	92.7 PSF	117.5 PSF	92.7 PSF	97.9 PSF	77.3 PSF	97.9 PSF	77.3 PSF	311.90 LB-FT	187.7 LB	931.9 LB	948.8 LB
18 "	30 "	4650 in ²	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	135.9 PSF	107.3 PSF	129.3 PSF	102.1 PSF	116.6 PSF	92.0 PSF	107.8 PSF	85.1 PSF	97.3 PSF	76.8 PSF	311.90 LB-FT	348.1 LB	1300.5 LB	1119.5 LB
24 "			133.9 PSF	105.7 PSF	131.2 PSF	103.5 PSF	117.2 PSF	92.5 PSF	114.8 PSF	90.7 PSF	100.4 PSF	79.3 PSF	98.5 PSF	77.8 PSF	83.7 PSF	66.1 PSF	82.2 PSF	64.9 PSF	311.90 LB-FT	270.4 LB	1145.9 LB	1058.4 LB
30 "			109.7 PSF	86.6 PSF	109.7 PSF	86.6 PSF	96.0 PSF	75.8 PSF	96.0 PSF	75.8 PSF	82.3 PSF	64.9 PSF	82.3 PSF	64.9 PSF	68.5 PSF	54.1 PSF	68.5 PSF	54.1 PSF	311.90 LB-FT	221.4 LB	1046.8 LB	1021.0 LB
36 "			93.0 PSF	73.4 PSF	93.0 PSF	73.4 PSF	81.3 PSF	64.2 PSF	81.3 PSF	64.2 PSF	69.7 PSF	55.0 PSF	69.7 PSF	55.0 PSF	58.1 PSF	45.8 PSF	58.1 PSF	45.8 PSF	311.90 LB-FT	187.7 LB	978.8 LB	995.8 LB
18 "	36 "	6300 in ²	97.1 PSF	100.5 PSF	97.1 PSF	88.4 PSF	97.1 PSF	87.9 PSF	97.1 PSF	77.4 PSF	95.4 PSF	75.3 PSF	84.1 PSF	66.4 PSF	79.5 PSF	62.8 PSF	70.1 PSF	55.4 PSF	311.90 LB-FT	348.1 LB	1392.2 LB	1206.5 LB
24 "			97.1 PSF	78.0 PSF	94.9 PSF	74.9 PSF	86.5 PSF	68.3 PSF	83.1 PSF	65.6 PSF	74.1 PSF	58.5 PSF	71.3 PSF	56.3 PSF	61.8 PSF	48.8 PSF	59.5 PSF	54.1 PSF	311.90 LB-FT	270.4 LB	1213.5 LB	1126.0 LB
30 "			81.0 PSF	63.9 PSF	81.0 PSF	63.9 PSF	70.8 PSF	55.9 PSF	70.8 PSF	55.9 PSF	60.7 PSF	47.9 PSF	60.7 PSF	47.9 PSF	50.6 PSF	39.9 PSF	50.6 PSF	39.9 PSF	311.90 LB-FT	221.4 LB	1102.1 LB	1076.4 LB
36 "			68.6 PSF	54.1 PSF	68.6 PSF	54.1 PSF	60.0 PSF	47.4 PSF	60.0 PSF	47.4 PSF	51.4 PSF	40.6 PSF	51.4 PSF	40.6 PSF	42.9 PSF	33.8 PSF	42.9 PSF	33.8 PSF	311.90 LB-FT	187.7 LB	1025.8 LB	1042.7 LB
18 "	42 "	8400 in ²	67.5 PSF	75.3 PSF	67.5 PSF	64.8 PSF	67.5 PSF	65.9 PSF	67.5 PSF	56.7 PSF	67.5 PSF	56.5 PSF	61.6 PSF	48.6 PSF	59.6 PSF	47.1 PSF	51.4 PSF	40.6 PSF	311.90 LB-FT	348.1 LB	1479.3 LB	1293.6 LB
24 "			67.5 PSF	58.5 PSF	67.5 PSF	55.1 PSF	64.9 PSF	51.2 PSF	61.1 PSF	48.2 PSF	55.6 PSF	43.9 PSF	52.4 PSF	41.4 PSF	46.3 PSF	36.6 PSF	43.7 PSF	34.5 PSF	311.90 LB-FT	270.4 LB	1281.2 LB	1193.6 LB
30 "			60.7 PSF	47.9 PSF	60.7 PSF	47.9 PSF	53.1 PSF	41.9 PSF	53.1 PSF	41.9 PSF	45.5 PSF	35.9 PSF	45.5 PSF	35.9 PSF	37.9 PSF	29.9 PSF	37.9 PSF	29.9 PSF	311.90 LB-FT	221.4 LB	1157.5 LB	1131.8 LB
36 "			51.4 PSF	40.6 PSF	51.4 PSF	40.6 PSF	45.0 PSF	35.5 PSF	45.0 PSF	35.5 PSF	38.6 PSF	30.4 PSF	38.6 PSF	30.4 PSF	32.1 PSF	25.4 PSF	32.1 PSF	25.4 PSF	311.90 LB-FT	187.7 LB	1072.7 LB	1089.6 LB
18 "	48 "	11520 in ²	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	43.9 PSF	34.7 PSF	43.5 PSF	34.3 PSF	36.6 PSF	28.9 PSF	311.90 LB-FT	348.1 LB	1557.9 LB	1380.6 LB
24 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	43.7 PSF	34.5 PSF	40.5 PSF	32.0 PSF	37.5 PSF	29.6 PSF	33.8 PSF	26.6 PSF	31.3 PSF	24.7 PSF	311.90 LB-FT	270.4 LB	1344.1 LB	1261.2 LB
30 "			44.2 PSF	34.9 PSF	43.6 PSF	34.4 PSF	38.7 PSF	30.6 PSF	38.2 PSF	30.1 PSF	33.2 PSF	26.2 PSF	32.7 PSF	25.8 PSF	27.6 PSF	21.8 PSF	27.3 PSF	21.5 PSF	311.90 LB-FT	221.4 LB	1212.9 LB	1187.1 LB
36 "			37.5 PSF	29.6 PSF	37.5 PSF	29.6 PSF	32.8 PSF	25.9 PSF	32.8 PSF	25.9 PSF	28.1 PSF	22.2 PSF	28.1 PSF	22.2 PSF	23.4 PSF	18.5 PSF	23.4 PSF	18.5 PSF	311.90 LB-FT	187.7 LB	1119.6 LB	1136.6 LB

36" STAND DEPTH: MAX FACE AREA (2760in² - 11520in²), FRAME QUANTITY (5-8 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 8 FRAMES				MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2760 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	171.3 PSF	135.3 PSF	171.3 PSF	135.3 PSF	311.90 LB-FT	328.5 LB	839.1 LB	686.6 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	187.7 PSF	148.2 PSF	187.7 PSF	148.2 PSF	160.9 PSF	127.0 PSF	160.9 PSF	127.0 PSF	134.0 PSF	105.8 PSF	134.0 PSF	105.8 PSF	311.90 LB-FT	256.9 LB	743.6 LB	675.0 LB
30 "			176.7 PSF	139.5 PSF	176.7 PSF	139.5 PSF	154.6 PSF	122.0 PSF	154.6 PSF	122.0 PSF	132.5 PSF	104.6 PSF	132.5 PSF	104.6 PSF	110.4 PSF	87.2 PSF	110.4 PSF	87.2 PSF	311.90 LB-FT	211.7 LB	682.4 LB	669.0 LB
36 "			150.5 PSF	118.8 PSF	150.5 PSF	118.8 PSF	131.6 PSF	103.9 PSF	131.6 PSF	103.9 PSF	112.8 PSF	89.1 PSF	112.8 PSF	89.1 PSF	94.0 PSF	74.2 PSF	94.0 PSF	74.2 PSF	311.90 LB-FT	180.2 LB	639.1 LB	665.4 LB
18 "	30 "	4650 in²	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	142.4 PSF	112.4 PSF	142.4 PSF	112.4 PSF	122.0 PSF	96.3 PSF	122.0 PSF	96.3 PSF	101.7 PSF	80.3 PSF	101.7 PSF	80.3 PSF	311.90 LB-FT	328.5 LB	900.3 LB	741.4 LB
24 "			127.3 PSF	100.5 PSF	127.3 PSF	100.5 PSF	111.4 PSF	87.9 PSF	111.4 PSF	87.9 PSF	95.5 PSF	75.3 PSF	95.5 PSF	75.3 PSF	62.8 PSF	79.5 PSF	62.8 PSF	79.5 PSF	311.90 LB-FT	256.9 LB	788.4 LB	717.9 LB
30 "			104.9 PSF	82.8 PSF	104.9 PSF	82.8 PSF	91.7 PSF	72.4 PSF	91.7 PSF	72.4 PSF	78.6 PSF	62.1 PSF	78.6 PSF	62.1 PSF	65.5 PSF	51.7 PSF	65.5 PSF	51.7 PSF	311.90 LB-FT	211.7 LB	717.6 LB	704.3 LB
36 "			89.3 PSF	70.5 PSF	89.3 PSF	70.5 PSF	78.1 PSF	61.7 PSF	78.1 PSF	61.7 PSF	66.9 PSF	52.8 PSF	66.9 PSF	52.8 PSF	55.8 PSF	44.0 PSF	55.8 PSF	44.0 PSF	311.90 LB-FT	180.2 LB	669.1 LB	695.4 LB
18 "	36 "	6300 in²	115.4 PSF	94.8 PSF	115.4 PSF	94.8 PSF	105.1 PSF	82.9 PSF	105.1 PSF	82.9 PSF	90.1 PSF	71.1 PSF	90.1 PSF	71.1 PSF	75.0 PSF	59.2 PSF	75.0 PSF	59.2 PSF	311.90 LB-FT	328.5 LB	957.0 LB	796.1 LB
24 "			93.9 PSF	74.2 PSF	93.9 PSF	74.2 PSF	82.2 PSF	64.9 PSF	82.2 PSF	64.9 PSF	70.4 PSF	55.6 PSF	70.4 PSF	55.6 PSF	58.7 PSF	46.3 PSF	58.7 PSF	46.3 PSF	311.90 LB-FT	256.9 LB	831.3 LB	760.7 LB
30 "			77.4 PSF	61.1 PSF	77.4 PSF	61.1 PSF	67.7 PSF	53.4 PSF	67.7 PSF	53.4 PSF	58.0 PSF	45.8 PSF	58.0 PSF	45.8 PSF	48.3 PSF	38.2 PSF	48.3 PSF	38.2 PSF	311.90 LB-FT	211.7 LB	752.9 LB	739.5 LB
36 "			65.9 PSF	52.0 PSF	65.9 PSF	52.0 PSF	57.6 PSF	45.5 PSF	57.6 PSF	45.5 PSF	49.4 PSF	39.0 PSF	49.4 PSF	39.0 PSF	41.2 PSF	32.5 PSF	41.2 PSF	32.5 PSF	311.90 LB-FT	180.2 LB	699.2 LB	725.5 LB
18 "	42 "	8400 in²	81.4 PSF	71.1 PSF	81.4 PSF	71.1 PSF	78.8 PSF	62.2 PSF	78.8 PSF	62.2 PSF	67.5 PSF	55.5 PSF	67.5 PSF	55.5 PSF	56.3 PSF	44.4 PSF	56.3 PSF	44.4 PSF	311.90 LB-FT	328.5 LB	1011.8 LB	850.9 LB
24 "			70.4 PSF	55.6 PSF	70.4 PSF	55.6 PSF	61.6 PSF	48.6 PSF	61.6 PSF	48.6 PSF	52.8 PSF	41.7 PSF	52.8 PSF	41.7 PSF	44.0 PSF	34.7 PSF	44.0 PSF	34.7 PSF	311.90 LB-FT	256.9 LB	874.1 LB	803.5 LB
30 "			58.0 PSF	45.8 PSF	58.0 PSF	45.8 PSF	50.8 PSF	40.1 PSF	50.8 PSF	40.1 PSF	43.5 PSF	34.3 PSF	43.5 PSF	34.3 PSF	36.2 PSF	28.6 PSF	36.2 PSF	28.6 PSF	311.90 LB-FT	211.7 LB	788.2 LB	774.8 LB
36 "			49.4 PSF	39.0 PSF	49.4 PSF	39.0 PSF	43.2 PSF	34.1 PSF	43.2 PSF	34.1 PSF	37.0 PSF	29.2 PSF	37.0 PSF	29.2 PSF	30.9 PSF	24.4 PSF	30.9 PSF	24.4 PSF	311.90 LB-FT	180.2 LB	729.2 LB	755.5 LB
18 "	48 "	11520 in²	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	55.9 PSF	44.1 PSF	49.2 PSF	38.9 PSF	47.9 PSF	37.8 PSF	41.0 PSF	32.4 PSF	40.0 PSF	31.5 PSF	311.90 LB-FT	328.5 LB	1061.8 LB	905.6 LB
24 "			51.3 PSF	40.5 PSF	51.3 PSF	40.5 PSF	44.9 PSF	35.5 PSF	44.9 PSF	35.5 PSF	38.5 PSF	30.4 PSF	38.5 PSF	30.4 PSF	32.1 PSF	25.3 PSF	32.1 PSF	25.3 PSF	311.90 LB-FT	256.9 LB	916.9 LB	846.4 LB
30 "			42.3 PSF	33.4 PSF	42.3 PSF	33.4 PSF	37.0 PSF	29.2 PSF	37.0 PSF	29.2 PSF	31.7 PSF	25.0 PSF	31.7 PSF	25.0 PSF	26.4 PSF	20.8 PSF	26.4 PSF	20.8 PSF	311.90 LB-FT	211.7 LB	823.5 LB	810.1 LB
36 "			36.0 PSF	28.4 PSF	36.0 PSF	28.4 PSF	31.5 PSF	24.9 PSF	31.5 PSF	24.9 PSF	27.0 PSF	21.3 PSF	27.0 PSF	21.3 PSF	22.5 PSF	17.7 PSF	22.5 PSF	17.7 PSF	311.90 LB-FT	180.2 LB	759.3 LB	785.6 LB

"XHD" STAND DESIGN SCHEDULE CONTINUED

24" STAND DEPTH: MAX FACE AREA (2208in² - 9216in²), FRAME QUANTITY (4-7 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2208 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	181.6 PSF	143.4 PSF	167.8 PSF	132.5 PSF	311.90 LB-FT	348.1 LB	1209.7 LB	1032.5 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	176.3 PSF	139.2 PSF	176.3 PSF	139.2 PSF	141.0 PSF	111.3 PSF	141.0 PSF	111.3 PSF	311.90 LB-FT	270.4 LB	1074.4 LB	990.8 LB
30 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	173.3 PSF	136.8 PSF	173.3 PSF	136.8 PSF	144.4 PSF	114.0 PSF	144.4 PSF	114.0 PSF	115.5 PSF	91.2 PSF	115.5 PSF	91.2 PSF	311.90 LB-FT	221.4 LB	990.4 LB	965.7 LB
36 "			171.3 PSF	135.3 PSF	171.3 PSF	135.3 PSF	146.9 PSF	115.9 PSF	146.9 PSF	115.9 PSF	122.4 PSF	96.6 PSF	122.4 PSF	96.6 PSF	97.9 PSF	77.3 PSF	97.9 PSF	77.3 PSF	311.90 LB-FT	187.7 LB	933.1 LB	948.8 LB
18 "	30 "	3720 in²	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	134.7 PSF	106.3 PSF	121.4 PSF	95.9 PSF	107.8 PSF	85.1 PSF	97.3 PSF	76.8 PSF	311.90 LB-FT	348.1 LB	1301.3 LB	1119.5 LB
24 "			142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	125.6 PSF	99.1 PSF	123.0 PSF	97.1 PSF	104.6 PSF	82.6 PSF	102.6 PSF	81.0 PSF	83.7 PSF	66.1 PSF	82.2 PSF	64.9 PSF	311.90 LB-FT	270.4 LB	1145.0 LB	1058.4 LB
30 "			120.0 PSF	94.7 PSF	120.0 PSF	94.7 PSF	102.8 PSF	81.2 PSF	102.8 PSF	81.2 PSF	85.7 PSF	67.6 PSF	85.7 PSF	67.6 PSF	68.5 PSF	54.1 PSF	68.5 PSF	54.1 PSF	311.90 LB-FT	221.4 LB	1048.0 LB	1021.0 LB
36 "			101.7 PSF	80.3 PSF	101.7 PSF	80.3 PSF	87.1 PSF	68.8 PSF	87.1 PSF	68.8 PSF	72.6 PSF	57.3 PSF	72.6 PSF	57.3 PSF	58.1 PSF	45.8 PSF	58.1 PSF	45.8 PSF	311.90 LB-FT	187.7 LB	980.0 LB	995.8 LB
18 "	36 "	5040 in²	97.1 PSF	109.9 PSF	97.1 PSF	96.6 PSF	97.1 PSF	94.2 PSF	97.1 PSF	82.9 PSF	97.1 PSF	78.5 PSF	87.6 PSF	69.1 PSF	79.5 PSF	62.8 PSF	70.1 PSF	55.4 PSF	311.90 LB-FT	348.1 LB	1393.4 LB	1206.5 LB
24 "			97.1 PSF	85.4 PSF	97.1 PSF	81.9 PSF	92.7 PSF	73.2 PSF	89.0 PSF	70.3 PSF	77.2 PSF	61.0 PSF	74.2 PSF	58.6 PSF	61.8 PSF	48.8 PSF	59.5 PSF	46.9 PSF	311.90 LB-FT	270.4 LB	1214.7 LB	1126.0 LB
30 "			88.5 PSF	69.9 PSF	88.5 PSF	69.9 PSF	75.9 PSF	59.9 PSF	75.9 PSF	59.9 PSF	63.2 PSF	49.9 PSF	63.2 PSF	49.9 PSF	50.6 PSF	39.9 PSF	50.6 PSF	39.9 PSF	311.90 LB-FT	221.4 LB	1103.3 LB	1076.4 LB
36 "			75.0 PSF	59.2 PSF	75.0 PSF	59.2 PSF	64.3 PSF	50.8 PSF	64.3 PSF	50.8 PSF	53.6 PSF	42.3 PSF	53.6 PSF	42.3 PSF	42.9 PSF	33.8 PSF	42.9 PSF	33.8 PSF	311.90 LB-FT	187.7 LB	1027.0 LB	1042.7 LB
18 "	42 "	6720 in²	67.5 PSF	82.4 PSF	67.5 PSF	70.8 PSF	67.5 PSF	70.6 PSF	67.5 PSF	60.7 PSF	67.5 PSF	58.8 PSF	64.2 PSF	50.7 PSF	59.6 PSF	47.1 PSF	51.4 PSF	40.6 PSF	311.90 LB-FT	348.1 LB	1480.5 LB	1293.6 LB
24 "			67.5 PSF	64.0 PSF	67.5 PSF	60.3 PSF	67.5 PSF	54.9 PSF	65.5 PSF	51.7 PSF	57.9 PSF	45.7 PSF	54.6 PSF	43.1 PSF	46.3 PSF	36.6 PSF	43.7 PSF	34.5 PSF	311.90 LB-FT	270.4 LB	1282.4 LB	1193.6 LB
30 "			66.4 PSF	52.4 PSF	66.4 PSF	52.4 PSF	56.9 PSF	44.9 PSF	56.9 PSF	44.9 PSF	47.4 PSF	37.4 PSF	47.4 PSF	37.4 PSF	37.9 PSF	29.9 PSF	37.9 PSF	29.9 PSF	311.90 LB-FT	221.4 LB	1158.7 LB	1131.8 LB
36 "			56.3 PSF	44.4 PSF	56.3 PSF	44.4 PSF	48.2 PSF	38.1 PSF	48.2 PSF	38.1 PSF	40.2 PSF	31.7 PSF	40.2 PSF	31.7 PSF	32.1 PSF	25.4 PSF	32.1 PSF	25.4 PSF	311.90 LB-FT	187.7 LB	1073.9 LB	1089.6 LB
18 "	48 "	9216 in²	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	43.5 PSF	34.3 PSF	36.6 PSF	28.9 PSF	311.90 LB-FT	348.1 LB	1557.9 LB	1380.6 LB
24 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	42.2 PSF	33.3 PSF	39.1 PSF	30.8 PSF	33.8 PSF	26.6 PSF	31.3 PSF	24.7 PSF	311.90 LB-FT	270.4 LB	1344.8 LB	1261.2 LB
30 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	41.5 PSF	32.7 PSF	40.9 PSF	32.3 PSF	34.6 PSF	27.3 PSF	34.1 PSF	26.9 PSF	27.6 PSF	21.8 PSF	27.3 PSF	21.5 PSF	311.90 LB-FT	221.4 LB	1211.9 LB	1187.1 LB
36 "			41.0 PSF	32.4 PSF	41.0 PSF	32.4 PSF	35.1 PSF	27.7 PSF	35.1 PSF	27.7 PSF	29.3 PSF	23.1 PSF	29.3 PSF	23.1 PSF	23.4 PSF	18.5 PSF	23.4 PSF	18.5 PSF	311.90 LB-FT	187.7 LB	1120.8 LB	1136.6 LB

36" STAND DEPTH: MAX FACE AREA (2208in² - 9216in²), FRAME QUANTITY (4-7 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2208 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	171.3 PSF	135.3 PSF	171.3 PSF	135.3 PSF	311.90 LB-FT	328.5 LB	839.1 LB	686.6 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	167.6 PSF	132.3 PSF	167.6 PSF	132.3 PSF	134.0 PSF	105.8 PSF	134.0 PSF	105.8 PSF	311.90 LB-FT	256.9 LB	741.7 LB	675.0 LB
30 "			193.3 PSF	152.6 PSF	193.3 PSF	152.6 PSF	165.6 PSF	130.8 PSF	165.6 PSF	130.8 PSF	138.0 PSF	109.0 PSF	138.0 PSF	109.0 PSF	110.4 PSF	87.2 PSF	110.4 PSF	87.2 PSF	311.90 LB-FT	211.7 LB	683.6 LB	669.0 LB
36 "			164.6 PSF	129.9 PSF	164.6 PSF	129.9 PSF	141.0 PSF	111.3 PSF	141.0 PSF	111.3 PSF	117.5 PSF	92.8 PSF	117.5 PSF	92.8 PSF	94.0 PSF	74.2 PSF	94.0 PSF	74.2 PSF	311.90 LB-FT	180.2 LB	640.3 LB	665.4 LB
18 "	30 "	3720 in²	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	152.5 PSF	120.4 PSF	152.5 PSF	120.4 PSF	127.1 PSF	100.3 PSF	127.1 PSF	100.3 PSF	101.7 PSF	80.3 PSF	101.7 PSF	80.3 PSF	311.90 LB-FT	328.5 LB	901.3 LB	741.4 LB
24 "			139.2 PSF	109.9 PSF	139.2 PSF	109.9 PSF	119.3 PSF	94.2 PSF	119.3 PSF	94.2 PSF	99.4 PSF	78.5 PSF	99.4 PSF	78.5 PSF	79.5 PSF	62.8 PSF	79.5 PSF	62.8 PSF	311.90 LB-FT	256.9 LB	789.7 LB	717.9 LB
30 "			114.7 PSF	90.5 PSF	114.7 PSF	90.5 PSF	98.3 PSF	77.6 PSF	98.3 PSF	77.6 PSF	81.9 PSF	64.7 PSF	81.9 PSF	64.7 PSF	65.5 PSF	51.7 PSF	65.5 PSF	51.7 PSF	311.90 LB-FT	211.7 LB	718.8 LB	704.3 LB
36 "			97.7 PSF	77.1 PSF	97.7 PSF	77.1 PSF	83.7 PSF	66.1 PSF	83.7 PSF	66.1 PSF	69.7 PSF	55.0 PSF	69.7 PSF	55.0 PSF	55.8 PSF	44.0 PSF	55.8 PSF	44.0 PSF	311.90 LB-FT	180.2 LB	670.3 LB	695.4 LB
18 "	36 "	5040 in²	115.4 PSF	103.7 PSF	115.4 PSF	103.7 PSF	112.6 PSF	88.9 PSF	112.6 PSF	88.9 PSF	93.8 PSF	74.1 PSF	93.8 PSF	74.1 PSF	75.0 PSF	59.2 PSF	75.0 PSF	59.2 PSF	311.90 LB-FT	328.5 LB	958.2 LB	796.1 LB
24 "			102.7 PSF	81.1 PSF	102.7 PSF	81.1 PSF	88.1 PSF	69.5 PSF	88.1 PSF	69.5 PSF	73.4 PSF	57.9 PSF	73.4 PSF	57.9 PSF	58.7 PSF	46.3 PSF	58.7 PSF	46.3 PSF	311.90 LB-FT	256.9 LB	832.5 LB	760.7 LB
30 "			84.6 PSF	66.8 PSF	84.6 PSF	66.8 PSF	72.5 PSF	57.3 PSF	72.5 PSF	57.3 PSF	60.4 PSF	47.7 PSF	60.4 PSF	47.7 PSF	48.3 PSF	38.2 PSF	48.3 PSF	38.2 PSF	311.90 LB-FT	211.7 LB	754.1 LB	739.5 LB
36 "			72.1 PSF	56.9 PSF	72.1 PSF	56.9 PSF	61.8 PSF	48.8 PSF	61.8 PSF	48.8 PSF	51.5 PSF	40.6 PSF	51.5 PSF	40.6 PSF	41.2 PSF	32.5 PSF	41.2 PSF	32.5 PSF	311.90 LB-FT	180.2 LB	700.4 LB	725.5 LB
18 "	42 "	6720 in²	81.4 PSF	77.8 PSF	81.4 PSF	76.8 PSF	81.4 PSF	66.6 PSF	81.4 PSF	65.9 PSF	70.3 PSF	55.5 PSF	69.6 PSF	54.9 PSF	56.3 PSF	44.4 PSF	55.7 PSF	44.0 PSF	311.90 LB-FT	328.5 LB	1013.0 LB	850.9 LB
24 "			77.0 PSF	60.8 PSF	77.0 PSF	60.8 PSF	66.0 PSF	52.1 PSF	66.0 PSF	52.1 PSF	55.0 PSF	43.4 PSF	55.0 PSF	43.4 PSF	44.0 PSF	34.7 PSF	44.0 PSF	34.7 PSF	311.90 LB-FT	256.9 LB	875.3 LB	803.5 LB
30 "			63.5 PSF	50.1 PSF	63.5 PSF	50.1 PSF	54.4 PSF	42.9 PSF	54.4 PSF	42.9 PSF	45.3 PSF	35.8 PSF	45.3 PSF	35.8 PSF	36.2 PSF	28.6 PSF	36.2 PSF	28.6 PSF	311.90 LB-FT	211.7 LB	789.4 LB	774.8 LB
36 "			54.0 PSF	42.7 PSF	54.0 PSF	42.7 PSF	46.3 PSF	36.6 PSF	46.3 PSF	36.6 PSF	38.6 PSF	30.5 PSF	38.6 PSF	30.5 PSF	30.9 PSF	24.4 PSF	30.9 PSF	24.4 PSF	311.90 LB-FT	180.2 LB	730.4 LB	755.5 LB
18 "	48 "	9216 in²	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	51.3 PSF	40.5 PSF	49.9 PSF	39.4 PSF	41.0 PSF	32.4 PSF	40.0 PSF	31.5 PSF	311.90 LB-FT	328.5 LB	1062.6 LB	905.6 LB
24 "			56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	48.1 PSF	38.0 PSF	48.1 PSF	38.0 PSF	40.1 PSF	31.7 PSF	40.1 PSF	31.7 PSF	32.1 PSF	25.3 PSF	32.1 PSF	25.3 PSF	311.90 LB-FT	256.9 LB	916.2 LB	846.4 LB
30 "			46.3 PSF	36.5 PSF	46.3 PSF	36.5 PSF	39.6 PSF	31.3 PSF	39.6 PSF	31.3 PSF	33.0 PSF	26.1 PSF	33.0 PSF	26.1 PSF	26.4 PSF	20.8 PSF	26.4 PSF	20.8 PSF	311.90 LB-FT	211.7 LB	824.7 LB	810.1 LB
36 "			39.4 PSF	31.1 PSF	39.4 PSF	31.1 PSF	33.8 PSF	26.6 PSF	33.8 PSF	26.6 PSF	28.1 PSF	22.2 PSF	28.1 PSF	22.2 PSF	22.5 PSF	17.7 PSF	22.5 PSF	17.7 PSF	311.90 LB-FT	180.2 LB	760.5 LB	785.6 LB

"XHD" STAND DESIGN SCHEDULE CONTINUED

36" STAND DEPTH: MAX FACE AREA (1656in² - 6912in²), FRAME QUANTITY (3-6 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	1656 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	171.3 PSF	135.3 PSF	171.3 PSF	135.3 PSF	311.90 LB-FT	328.5 LB	839.1 LB	686.6 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	178.7 PSF	141.1 PSF	178.7 PSF	141.1 PSF	134.0 PSF	105.8 PSF	134.0 PSF	105.8 PSF	311.90 LB-FT	256.9 LB	742.8 LB	675.0 LB
30 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	184.1 PSF	145.3 PSF	184.1 PSF	145.3 PSF	147.2 PSF	116.2 PSF	147.2 PSF	116.2 PSF	110.4 PSF	87.2 PSF	110.4 PSF	87.2 PSF	311.90 LB-FT	211.7 LB	682.9 LB	669.0 LB
36 "			188.1 PSF	148.5 PSF	188.1 PSF	148.5 PSF	156.7 PSF	123.7 PSF	156.7 PSF	123.7 PSF	125.4 PSF	99.0 PSF	125.4 PSF	99.0 PSF	94.0 PSF	74.2 PSF	94.0 PSF	74.2 PSF	311.90 LB-FT	180.2 LB	641.9 LB	665.4 LB
18 "	30 "	2790 in²	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	135.6 PSF	107.0 PSF	135.6 PSF	107.0 PSF	101.7 PSF	80.3 PSF	101.7 PSF	80.3 PSF	311.90 LB-FT	328.5 LB	899.4 LB	741.4 LB
24 "			156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	132.6 PSF	104.7 PSF	132.6 PSF	104.7 PSF	106.1 PSF	83.7 PSF	106.1 PSF	83.7 PSF	79.5 PSF	62.8 PSF	79.5 PSF	62.8 PSF	311.90 LB-FT	256.9 LB	789.0 LB	717.9 LB
30 "			131.1 PSF	103.5 PSF	131.1 PSF	103.5 PSF	109.2 PSF	86.2 PSF	109.2 PSF	86.2 PSF	87.4 PSF	69.0 PSF	87.4 PSF	69.0 PSF	65.5 PSF	51.7 PSF	65.5 PSF	51.7 PSF	311.90 LB-FT	211.7 LB	720.5 LB	704.3 LB
36 "			111.6 PSF	88.1 PSF	111.6 PSF	88.1 PSF	93.0 PSF	73.4 PSF	93.0 PSF	73.4 PSF	74.4 PSF	58.7 PSF	74.4 PSF	58.7 PSF	55.8 PSF	44.0 PSF	55.8 PSF	44.0 PSF	311.90 LB-FT	180.2 LB	671.9 LB	695.4 LB
18 "	36 "	3780 in²	115.4 PSF	118.5 PSF	115.4 PSF	118.5 PSF	115.4 PSF	98.8 PSF	115.4 PSF	98.8 PSF	100.1 PSF	79.0 PSF	100.1 PSF	79.0 PSF	75.0 PSF	59.2 PSF	75.0 PSF	59.2 PSF	311.90 LB-FT	328.5 LB	959.8 LB	796.1 LB
24 "			115.4 PSF	92.7 PSF	115.4 PSF	92.7 PSF	97.9 PSF	77.2 PSF	97.9 PSF	77.2 PSF	78.3 PSF	61.8 PSF	78.3 PSF	61.8 PSF	58.7 PSF	46.3 PSF	58.7 PSF	46.3 PSF	311.90 LB-FT	256.9 LB	834.1 LB	760.7 LB
30 "			96.7 PSF	76.4 PSF	96.7 PSF	76.4 PSF	80.6 PSF	63.6 PSF	80.6 PSF	63.6 PSF	64.5 PSF	50.9 PSF	64.5 PSF	50.9 PSF	48.3 PSF	38.2 PSF	48.3 PSF	38.2 PSF	311.90 LB-FT	211.7 LB	755.7 LB	739.5 LB
36 "			82.4 PSF	65.0 PSF	82.4 PSF	65.0 PSF	68.6 PSF	54.2 PSF	68.6 PSF	54.2 PSF	54.9 PSF	43.3 PSF	54.9 PSF	43.3 PSF	41.2 PSF	32.5 PSF	41.2 PSF	32.5 PSF	311.90 LB-FT	180.2 LB	702.0 LB	725.5 LB
18 "	42 "	5040 in²	81.4 PSF	88.9 PSF	81.4 PSF	87.7 PSF	81.4 PSF	74.1 PSF	81.4 PSF	73.1 PSF	75.0 PSF	59.2 PSF	74.2 PSF	58.6 PSF	56.3 PSF	44.4 PSF	55.7 PSF	44.0 PSF	311.90 LB-FT	328.5 LB	1014.6 LB	850.9 LB
24 "			81.4 PSF	69.5 PSF	81.4 PSF	69.5 PSF	73.4 PSF	57.9 PSF	73.4 PSF	57.9 PSF	58.7 PSF	46.3 PSF	58.7 PSF	46.3 PSF	44.0 PSF	34.7 PSF	44.0 PSF	34.7 PSF	311.90 LB-FT	256.9 LB	876.9 LB	803.5 LB
30 "			72.5 PSF	57.3 PSF	72.5 PSF	57.3 PSF	60.4 PSF	47.7 PSF	60.4 PSF	47.7 PSF	48.3 PSF	38.2 PSF	48.3 PSF	38.2 PSF	36.2 PSF	28.6 PSF	36.2 PSF	28.6 PSF	311.90 LB-FT	211.7 LB	791.0 LB	774.8 LB
36 "			61.8 PSF	48.8 PSF	61.8 PSF	48.8 PSF	51.5 PSF	40.6 PSF	51.5 PSF	40.6 PSF	41.2 PSF	32.5 PSF	41.2 PSF	32.5 PSF	30.9 PSF	24.4 PSF	30.9 PSF	24.4 PSF	311.90 LB-FT	180.2 LB	732.0 LB	755.5 LB
18 "	48 "	6912 in²	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	54.7 PSF	43.2 PSF	53.2 PSF	42.0 PSF	41.0 PSF	32.4 PSF	40.0 PSF	31.5 PSF	311.90 LB-FT	328.5 LB	1063.7 LB	905.6 LB
24 "			56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	53.5 PSF	42.2 PSF	53.5 PSF	42.2 PSF	42.8 PSF	33.8 PSF	42.8 PSF	33.8 PSF	32.1 PSF	25.3 PSF	32.1 PSF	25.3 PSF	311.90 LB-FT	256.9 LB	917.5 LB	846.4 LB
30 "			52.9 PSF	41.7 PSF	52.9 PSF	41.7 PSF	44.1 PSF	34.8 PSF	44.1 PSF	34.8 PSF	35.2 PSF	27.8 PSF	35.2 PSF	27.8 PSF	26.4 PSF	20.8 PSF	26.4 PSF	20.8 PSF	311.90 LB-FT	211.7 LB	826.3 LB	810.1 LB
36 "			45.0 PSF	35.5 PSF	45.0 PSF	35.5 PSF	37.5 PSF	29.6 PSF	37.5 PSF	29.6 PSF	30.0 PSF	23.7 PSF	30.0 PSF	23.7 PSF	22.5 PSF	17.7 PSF	22.5 PSF	17.7 PSF	311.90 LB-FT	180.2 LB	762.1 LB	785.6 LB

24" STAND DEPTH: MAX FACE AREA (1104in² - 4608in²), FRAME QUANTITY (2-5 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	1104 in ²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	181.6 PSF	143.4 PSF	167.8 PSF	132.5 PSF	311.90 LB-FT	348.1 LB	1209.7 LB	1032.5 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	141.0 PSF	111.3 PSF	141.0 PSF	111.3 PSF	311.90 LB-FT	270.4 LB	1069.9 LB	990.8 LB
30 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	173.3 PSF	136.8 PSF	173.3 PSF	136.8 PSF	115.5 PSF	91.2 PSF	115.5 PSF	91.2 PSF	311.90 LB-FT	221.4 LB	990.4 LB	965.7 LB
36 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	195.8 PSF	154.6 PSF	195.8 PSF	154.6 PSF	146.9 PSF	115.9 PSF	146.9 PSF	115.9 PSF	97.9 PSF	77.3 PSF	97.9 PSF	77.3 PSF	311.90 LB-FT	187.7 LB	934.7 LB	948.8 LB
18 "	30 "	1860 in ²	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	107.8 PSF	85.1 PSF	97.3 PSF	76.8 PSF	311.90 LB-FT	348.1 LB	1296.8 LB	1119.5 LB
24 "			142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	125.6 PSF	99.1 PSF	123.0 PSF	97.1 PSF	83.7 PSF	66.1 PSF	82.2 PSF	64.9 PSF	311.90 LB-FT	270.4 LB	1145.0 LB	1058.4 LB
30 "			142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	137.1 PSF	108.3 PSF	137.1 PSF	108.3 PSF	102.8 PSF	81.2 PSF	102.8 PSF	81.2 PSF	68.5 PSF	54.1 PSF	68.5 PSF	54.1 PSF	311.90 LB-FT	221.4 LB	1049.6 LB	1021.0 LB
36 "			142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	116.2 PSF	91.7 PSF	116.2 PSF	91.7 PSF	87.1 PSF	68.8 PSF	87.1 PSF	68.8 PSF	58.1 PSF	45.8 PSF	58.1 PSF	45.8 PSF	311.90 LB-FT	187.7 LB	981.6 LB	995.8 LB
18 "	36 "	2520 in ²	97.1 PSF	157.0 PSF	97.1 PSF	137.9 PSF	97.1 PSF	125.6 PSF	97.1 PSF	110.4 PSF	97.1 PSF	94.2 PSF	82.9 PSF	79.5 PSF	62.8 PSF	55.4 PSF	39.7 PSF	55.4 PSF	311.90 LB-FT	348.1 LB	1397.3 LB	1206.5 LB
24 "			97.1 PSF	122.0 PSF	97.1 PSF	116.9 PSF	97.1 PSF	97.6 PSF	97.1 PSF	93.6 PSF	92.7 PSF	73.2 PSF	89.0 PSF	70.3 PSF	61.8 PSF	48.8 PSF	59.5 PSF	46.9 PSF	311.90 LB-FT	270.4 LB	1218.6 LB	1126.0 LB
30 "			97.1 PSF	99.9 PSF	97.1 PSF	99.9 PSF	97.1 PSF	79.9 PSF	97.1 PSF	79.9 PSF	75.9 PSF	59.9 PSF	75.9 PSF	59.9 PSF	50.6 PSF	39.9 PSF	50.6 PSF	39.9 PSF	311.90 LB-FT	221.4 LB	1107.2 LB	1076.4 LB
36 "			97.1 PSF	84.6 PSF	97.1 PSF	84.6 PSF	85.8 PSF	67.7 PSF	85.8 PSF	67.7 PSF	64.3 PSF	50.8 PSF	64.3 PSF	50.8 PSF	42.9 PSF	33.8 PSF	42.9 PSF	33.8 PSF	311.90 LB-FT	187.7 LB	1030.8 LB	1042.7 LB
18 "	42 "	3360 in ²	67.5 PSF	117.7 PSF	67.5 PSF	101.1 PSF	67.5 PSF	94.2 PSF	67.5 PSF	80.9 PSF	67.5 PSF	70.6 PSF	60.7 PSF	59.6 PSF	47.1 PSF	31.4 PSF	40.6 PSF	34.5 PSF	311.90 LB-FT	348.1 LB	1484.3 LB	1293.6 LB
24 "			67.5 PSF	91.5 PSF	67.5 PSF	86.0 PSF	67.5 PSF	73.2 PSF	67.5 PSF	68.8 PSF	67.5 PSF	54.9 PSF	65.5 PSF	51.7 PSF	46.3 PSF	36.6 PSF	43.7 PSF	34.5 PSF	311.90 LB-FT	270.4 LB	1286.2 LB	1193.6 LB
30 "			67.5 PSF	74.9 PSF	67.5 PSF	74.9 PSF	67.5 PSF	59.9 PSF	67.5 PSF	59.9 PSF	56.9 PSF	44.9 PSF	56.9 PSF	44.9 PSF	37.9 PSF	29.9 PSF	37.9 PSF	29.9 PSF	311.90 LB-FT	221.4 LB	1162.6 LB	1131.8 LB
36 "			67.5 PSF	63.5 PSF	67.5 PSF	63.5 PSF	64.3 PSF	50.8 PSF	64.3 PSF	50.8 PSF	48.2 PSF	38.1 PSF	48.2 PSF	38.1 PSF	32.1 PSF	25.4 PSF	32.1 PSF	25.4 PSF	311.90 LB-FT	187.7 LB	1077.8 LB	1089.6 LB
18 "	48 "	4608 in ²	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	43.5 PSF	34.3 PSF	36.6 PSF	28.9 PSF	311.90 LB-FT	348.1 LB	1557.9 LB	1380.6 LB
24 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	33.8 PSF	26.6 PSF	33.8 PSF	21.7 PSF	311.90 LB-FT	270.4 LB	1340.3 LB	1261.2 LB
30 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	41.5 PSF	32.7 PSF	40.9 PSF	32.3 PSF	27.6 PSF	21.8 PSF	23.3 PSF	21.5 PSF	311.90 LB-FT	221.4 LB	1211.9 LB	1187.1 LB
36 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	35.1 PSF	27.7 PSF	35.1 PSF	27.7 PSF	23.4 PSF	18.5 PSF	23.4 PSF	18.5 PSF	311.90 LB-FT	187.7 LB	1118.7 LB	1136.6 LB

"XHD" STAND DESIGN SCHEDULE CONTINUED

24" STAND DEPTH: MAX FACE AREA (552in² - 2304in²), FRAME QUANTITY (2-3 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO								MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	552 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	171.70 LB-FT	191.6 LB	667.1 LB	556.2 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	221.00 LB-FT	191.6 LB	762.9 LB	652.1 LB
30 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	269.90 LB-FT	191.6 LB	858.8 LB	747.9 LB
36 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	195.8 PSF	154.6 PSF	195.8 PSF	154.6 PSF	311.90 LB-FT	187.7 LB	934.7 LB	828.8 LB
18 "	30 "	930 in²	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	206.80 LB-FT	230.8 LB	863.5 LB	703.2 LB
24 "			142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	266.20 LB-FT	230.8 LB	979.0 LB	818.6 LB
30 "			142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	137.1 PSF	108.3 PSF	137.1 PSF	108.3 PSF	311.90 LB-FT	221.4 LB	1049.6 LB	901.0 LB
36 "			142.9 PSF	112.8 PSF	142.9 PSF	112.8 PSF	116.2 PSF	91.7 PSF	116.2 PSF	91.7 PSF	311.90 LB-FT	187.7 LB	981.6 LB	875.8 LB
18 "	36 "	1260 in²	97.1 PSF	157.8 PSF	97.1 PSF	157.8 PSF	97.1 PSF	128.6 PSF	97.1 PSF	110.4 PSF	311.90 LB-FT	348.1 LB	1395.1 LB	1086.5 LB
24 "			97.1 PSF	146.4 PSF	97.1 PSF	140.3 PSF	97.1 PSF	97.6 PSF	97.1 PSF	93.6 PSF	311.90 LB-FT	270.4 LB	1220.1 LB	1006.0 LB
30 "			97.1 PSF	119.9 PSF	97.1 PSF	119.9 PSF	97.1 PSF	79.9 PSF	97.1 PSF	79.9 PSF	311.90 LB-FT	221.4 LB	1108.7 LB	956.4 LB
36 "			97.1 PSF	101.6 PSF	97.1 PSF	101.6 PSF	85.8 PSF	67.7 PSF	85.8 PSF	67.7 PSF	311.90 LB-FT	187.7 LB	1032.3 LB	922.7 LB
18 "	42 "	1680 in²	67.5 PSF	141.3 PSF	67.5 PSF	121.3 PSF	67.5 PSF	94.2 PSF	67.5 PSF	80.9 PSF	311.90 LB-FT	348.1 LB	1485.8 LB	1173.6 LB
24 "			67.5 PSF	109.8 PSF	67.5 PSF	103.2 PSF	67.5 PSF	73.2 PSF	67.5 PSF	68.8 PSF	311.90 LB-FT	270.4 LB	1287.7 LB	1073.6 LB
30 "			67.5 PSF	89.9 PSF	67.5 PSF	89.9 PSF	67.5 PSF	59.9 PSF	67.5 PSF	59.9 PSF	311.90 LB-FT	221.4 LB	1164.1 LB	1011.8 LB
36 "			67.5 PSF	76.2 PSF	67.5 PSF	76.2 PSF	64.3 PSF	50.8 PSF	64.3 PSF	50.8 PSF	311.90 LB-FT	187.7 LB	1079.3 LB	969.6 LB
18 "	48 "	2304 in²	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	164.30 LB-FT	183.4 LB	821.3 LB	720.9 LB
24 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	211.50 LB-FT	183.4 LB	913.0 LB	812.6 LB
30 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	258.20 LB-FT	183.4 LB	1004.7 LB	904.3 LB
36 "			45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	45.8 PSF	36.1 PSF	304.70 LB-FT	183.4 LB	1096.4 LB	996.0 LB

DESIGN SCHEDULE NOTES:

1. MAXIMUM CALCULATED FACE AREA SHALL BE EQUAL TO OR LESS THAN THE MAXIMUM ALLOWABLE FACE AREA FOR EACH CONFIGURATION.
2. REFERENCE ANCHOR SCHEDULE FOR ANCHOR TYPES LISTED HEREIN.

36" STAND DEPTH: MAX FACE AREA (552in² - 2304in²), FRAME QUANTITY (2-3 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO								MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	552 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	181.90 LB-FT	191.6 LB	491.4 LB	380.5 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	232.60 LB-FT	191.6 LB	555.3 LB	444.4 LB
30 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	282.30 LB-FT	191.6 LB	619.2 LB	508.3 LB
36 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	188.1 PSF	148.5 PSF	188.1 PSF	148.5 PSF	311.90 LB-FT	180.2 LB	641.9 LB	545.4 LB
18 "	30 "	930 in²	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	239.90 LB-FT	252.6 LB	693.5 LB	505.6 LB
24 "			156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	306.60 LB-FT	252.6 LB	777.7 LB	589.8 LB
30 "			156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	131.1 PSF	103.5 PSF	131.1 PSF	103.5 PSF	311.90 LB-FT	211.7 LB	720.5 LB	584.3 LB
36 "			156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	111.6 PSF	88.1 PSF	111.6 PSF	88.1 PSF	311.90 LB-FT	180.2 LB	671.9 LB	575.4 LB
18 "	36 "	1260 in²	115.4 PSF	157.8 PSF	115.4 PSF	157.8 PSF	115.4 PSF	118.5 PSF	115.4 PSF	118.5 PSF	311.90 LB-FT	328.5 LB	959.8 LB	676.1 LB
24 "			115.4 PSF	139.1 PSF	115.4 PSF	139.1 PSF	115.4 PSF	92.7 PSF	115.4 PSF	92.7 PSF	311.90 LB-FT	256.9 LB	837.8 LB	640.7 LB
30 "			115.4 PSF	114.6 PSF	115.4 PSF	114.6 PSF	96.7 PSF	76.4 PSF	96.7 PSF	76.4 PSF	311.90 LB-FT	211.7 LB	759.5 LB	619.5 LB
36 "			115.4 PSF	97.6 PSF	115.4 PSF	97.6 PSF	82.4 PSF	65.0 PSF	82.4 PSF	65.0 PSF	311.90 LB-FT	180.2 LB	705.7 LB	605.5 LB
18 "	42 "	1680 in²	81.4 PSF	133.3 PSF	81.4 PSF	131.5 PSF	81.4 PSF	88.9 PSF	81.4 PSF	87.7 PSF	311.90 LB-FT	328.5 LB	1018.3 LB	730.9 LB
24 "			81.4 PSF	104.3 PSF	81.4 PSF	104.3 PSF	81.4 PSF	69.5 PSF	81.4 PSF	69.5 PSF	311.90 LB-FT	256.9 LB	880.7 LB	683.5 LB
30 "			81.4 PSF	85.9 PSF	81.4 PSF	85.9 PSF	72.5 PSF	57.3 PSF	72.5 PSF	57.3 PSF	311.90 LB-FT	211.7 LB	794.8 LB	654.8 LB
36 "			81.4 PSF	73.2 PSF	81.4 PSF	73.2 PSF	61.8 PSF	48.8 PSF	61.8 PSF	48.8 PSF	311.90 LB-FT	180.2 LB	735.8 LB	635.5 LB
18 "	48 "	2304 in²	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	213.00 LB-FT	224.4 LB	726.9 LB	574.7 LB
24 "			56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	272.30 LB-FT	224.4 LB	801.7 LB	649.5 LB
30 "			56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	52.9 PSF	41.7 PSF	52.9 PSF	41.7 PSF	311.90 LB-FT	211.7 LB	826.3 LB	690.1 LB
36 "			56.1 PSF	44.2 PSF	56.1 PSF	44.2 PSF	45.0 PSF	35.5 PSF	45.0 PSF	35.5 PSF	311.90 LB-FT	180.2 LB	762.1 LB	665.6 LB

"FIXED HD" STAND DESIGN SCHEDULE

48" STAND DEPTH: MAX FACE AREA (2760in² - 11520in²), FRAME QUANTITY (5-8 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 8 FRAMES				MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2760 in ²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	193.7 PSF	152.9 PSF	193.7 PSF	152.9 PSF	166.0 PSF	131.0 PSF	166.0 PSF	131.0 PSF	138.3 PSF	109.2 PSF	138.3 PSF	109.2 PSF	247.00 LB-FT	265.2 LB	558.0 LB	374.0 LB
24 "			172.8 PSF	136.4 PSF	172.8 PSF	136.4 PSF	151.2 PSF	119.4 PSF	151.2 PSF	119.4 PSF	129.6 PSF	102.3 PSF	129.6 PSF	102.3 PSF	108.0 PSF	85.2 PSF	108.0 PSF	85.2 PSF	247.00 LB-FT	207.0 LB	485.8 LB	373.3 LB
30 "			142.1 PSF	112.2 PSF	142.1 PSF	112.2 PSF	124.3 PSF	98.1 PSF	124.3 PSF	98.1 PSF	106.6 PSF	84.1 PSF	106.6 PSF	84.1 PSF	88.8 PSF	70.1 PSF	88.8 PSF	70.1 PSF	247.00 LB-FT	207.0 LB	485.8 LB	373.3 LB
36 "			120.8 PSF	95.4 PSF	120.8 PSF	95.4 PSF	105.7 PSF	83.4 PSF	105.7 PSF	83.4 PSF	90.6 PSF	71.5 PSF	90.6 PSF	71.5 PSF	75.5 PSF	59.6 PSF	75.5 PSF	59.6 PSF	247.00 LB-FT	144.7 LB	407.9 LB	374.0 LB
18 "	30 "	4650 in ²	131.4 PSF	103.7 PSF	131.4 PSF	103.7 PSF	114.9 PSF	90.7 PSF	114.9 PSF	90.7 PSF	98.5 PSF	77.8 PSF	98.5 PSF	77.8 PSF	82.1 PSF	64.8 PSF	82.1 PSF	64.8 PSF	247.00 LB-FT	265.2 LB	593.1 LB	407.2 LB
24 "			102.5 PSF	80.9 PSF	102.5 PSF	80.9 PSF	89.7 PSF	70.8 PSF	89.7 PSF	70.8 PSF	76.9 PSF	60.7 PSF	76.9 PSF	60.7 PSF	64.1 PSF	50.6 PSF	64.1 PSF	50.6 PSF	247.00 LB-FT	207.0 LB	511.7 LB	399.2 LB
30 "			84.3 PSF	66.6 PSF	84.3 PSF	66.6 PSF	73.8 PSF	58.2 PSF	73.8 PSF	58.2 PSF	63.2 PSF	49.9 PSF	63.2 PSF	49.9 PSF	52.7 PSF	41.6 PSF	52.7 PSF	41.6 PSF	247.00 LB-FT	207.0 LB	511.7 LB	399.2 LB
36 "			71.7 PSF	56.6 PSF	71.7 PSF	56.6 PSF	62.7 PSF	49.5 PSF	62.7 PSF	49.5 PSF	53.8 PSF	42.4 PSF	53.8 PSF	42.4 PSF	44.8 PSF	35.3 PSF	44.8 PSF	35.3 PSF	247.00 LB-FT	144.7 LB	426.0 LB	392.1 LB
18 "	36 "	6300 in ²	96.9 PSF	76.5 PSF	96.9 PSF	76.5 PSF	84.8 PSF	67.0 PSF	84.8 PSF	67.0 PSF	72.7 PSF	57.4 PSF	72.7 PSF	57.4 PSF	60.6 PSF	47.8 PSF	60.6 PSF	47.8 PSF	247.00 LB-FT	265.2 LB	626.3 LB	440.3 LB
24 "			75.7 PSF	59.7 PSF	75.7 PSF	59.7 PSF	66.2 PSF	52.3 PSF	66.2 PSF	52.3 PSF	56.7 PSF	44.8 PSF	56.7 PSF	44.8 PSF	47.3 PSF	37.3 PSF	47.3 PSF	37.3 PSF	247.00 LB-FT	207.0 LB	537.6 LB	425.1 LB
30 "			62.2 PSF	49.1 PSF	62.2 PSF	49.1 PSF	54.4 PSF	43.0 PSF	54.4 PSF	43.0 PSF	46.7 PSF	36.8 PSF	46.7 PSF	36.8 PSF	38.9 PSF	30.7 PSF	38.9 PSF	30.7 PSF	247.00 LB-FT	207.0 LB	537.6 LB	425.1 LB
36 "			52.9 PSF	41.8 PSF	52.9 PSF	41.8 PSF	46.3 PSF	36.5 PSF	46.3 PSF	36.5 PSF	39.7 PSF	31.3 PSF	39.7 PSF	31.3 PSF	33.0 PSF	26.1 PSF	33.0 PSF	26.1 PSF	247.00 LB-FT	144.7 LB	444.1 LB	410.2 LB
18 "	42 "	8400 in ²	72.7 PSF	57.4 PSF	72.7 PSF	57.4 PSF	63.6 PSF	50.2 PSF	63.6 PSF	50.2 PSF	54.5 PSF	43.0 PSF	54.5 PSF	43.0 PSF	45.4 PSF	35.8 PSF	45.4 PSF	35.8 PSF	247.00 LB-FT	265.2 LB	659.4 LB	473.5 LB
24 "			56.7 PSF	44.8 PSF	56.7 PSF	44.8 PSF	49.6 PSF	39.2 PSF	49.6 PSF	39.2 PSF	42.5 PSF	33.6 PSF	42.5 PSF	33.6 PSF	35.4 PSF	28.0 PSF	35.4 PSF	28.0 PSF	247.00 LB-FT	207.0 LB	563.5 LB	451.0 LB
30 "			46.7 PSF	36.8 PSF	46.7 PSF	36.8 PSF	40.8 PSF	32.2 PSF	40.8 PSF	32.2 PSF	35.0 PSF	27.6 PSF	35.0 PSF	27.6 PSF	29.1 PSF	23.0 PSF	29.1 PSF	23.0 PSF	247.00 LB-FT	207.0 LB	563.5 LB	451.0 LB
36 "			39.7 PSF	31.3 PSF	39.7 PSF	31.3 PSF	34.7 PSF	27.4 PSF	34.7 PSF	27.4 PSF	29.7 PSF	23.5 PSF	29.7 PSF	23.5 PSF	23.5 PSF	24.8 PSF	19.5 PSF	24.8 PSF	19.5 PSF	247.00 LB-FT	144.7 LB	462.2 LB
18 "	48 "	11520 in ³	53.0 PSF	41.8 PSF	53.0 PSF	41.8 PSF	46.4 PSF	36.6 PSF	46.4 PSF	36.6 PSF	39.7 PSF	31.4 PSF	39.7 PSF	31.4 PSF	33.1 PSF	26.1 PSF	33.1 PSF	26.1 PSF	247.00 LB-FT	265.2 LB	692.6 LB	506.6 LB
24 "			41.4 PSF	32.6 PSF	41.4 PSF	32.6 PSF	36.2 PSF	28.6 PSF	36.2 PSF	28.6 PSF	31.0 PSF	24.5 PSF	31.0 PSF	24.5 PSF	25.8 PSF	20.4 PSF	25.8 PSF	20.4 PSF	247.00 LB-FT	207.0 LB	589.4 LB	476.9 LB
30 "			34.0 PSF	26.8 PSF	34.0 PSF	26.8 PSF	29.7 PSF	23.5 PSF	29.7 PSF	23.5 PSF	25.5 PSF	20.1 PSF	25.5 PSF	20.1 PSF	21.2 PSF	16.8 PSF	21.2 PSF	16.8 PSF	247.00 LB-FT	207.0 LB	589.4 LB	476.9 LB
36 "			28.9 PSF	22.8 PSF	28.9 PSF	22.8 PSF	25.3 PSF	20.0 PSF	25.3 PSF	20.0 PSF	21.7 PSF	17.1 PSF	21.7 PSF	17.1 PSF	17.1 PSF	17.1 PSF	17.1 PSF	17.1 PSF	17.1 PSF	247.00 LB-FT	144.7 LB	480.2 LB

"FIXED HD" STAND DESIGN SCHEDULE CONTINUED

FRANK BENNARDO, PE
PE# 0046549 CA# 9885



48" STAND DEPTH: MAX FACE AREA (2208in² - 9216in²), FRAME QUANTITY (4-7 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 7 FRAMES				MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	2208 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	172.9 PSF	136.5 PSF	172.9 PSF	136.5 PSF	138.3 PSF	109.2 PSF	138.3 PSF	109.2 PSF	247.00 LB-FT	265.2 LB	556.0 LB	374.0 LB
24 "			189.0 PSF	149.2 PSF	189.0 PSF	149.2 PSF	162.0 PSF	127.9 PSF	162.0 PSF	127.9 PSF	135.0 PSF	106.6 PSF	135.0 PSF	106.6 PSF	108.0 PSF	85.2 PSF	108.0 PSF	85.2 PSF	247.00 LB-FT	207.0 LB	487.0 LB	373.3 LB
30 "			155.4 PSF	122.7 PSF	155.4 PSF	122.7 PSF	133.2 PSF	105.2 PSF	133.2 PSF	105.2 PSF	111.0 PSF	87.6 PSF	111.0 PSF	87.6 PSF	88.8 PSF	70.1 PSF	88.8 PSF	70.1 PSF	247.00 LB-FT	170.2 LB	440.8 LB	373.6 LB
36 "	30 "	3720 in²	132.1 PSF	104.3 PSF	132.1 PSF	104.3 PSF	113.3 PSF	89.4 PSF	113.3 PSF	89.4 PSF	94.4 PSF	74.5 PSF	94.4 PSF	74.5 PSF	75.5 PSF	59.6 PSF	75.5 PSF	59.6 PSF	247.00 LB-FT	144.7 LB	409.1 LB	374.0 LB
18 "			143.7 PSF	113.4 PSF	143.7 PSF	113.4 PSF	123.2 PSF	97.2 PSF	123.2 PSF	97.2 PSF	102.6 PSF	81.0 PSF	102.6 PSF	81.0 PSF	82.1 PSF	64.8 PSF	82.1 PSF	64.8 PSF	247.00 LB-FT	265.2 LB	594.3 LB	407.2 LB
24 "			112.2 PSF	88.5 PSF	112.2 PSF	88.5 PSF	96.1 PSF	75.9 PSF	96.1 PSF	75.9 PSF	80.1 PSF	63.2 PSF	80.1 PSF	63.2 PSF	64.1 PSF	50.6 PSF	64.1 PSF	50.6 PSF	247.00 LB-FT	207.0 LB	512.9 LB	399.2 LB
30 "	36 "	5040 in²	92.2 PSF	72.8 PSF	92.2 PSF	72.8 PSF	79.0 PSF	62.4 PSF	79.0 PSF	62.4 PSF	65.9 PSF	52.0 PSF	65.9 PSF	52.0 PSF	52.7 PSF	41.6 PSF	52.7 PSF	41.6 PSF	247.00 LB-FT	170.2 LB	462.1 LB	394.9 LB
36 "			78.4 PSF	61.9 PSF	78.4 PSF	61.9 PSF	67.2 PSF	53.0 PSF	67.2 PSF	53.0 PSF	56.0 PSF	44.2 PSF	56.0 PSF	44.2 PSF	44.8 PSF	35.3 PSF	44.8 PSF	35.3 PSF	247.00 LB-FT	144.7 LB	427.2 LB	392.1 LB
18 "			106.0 PSF	83.7 PSF	106.0 PSF	83.7 PSF	90.9 PSF	71.7 PSF	90.9 PSF	71.7 PSF	75.7 PSF	59.8 PSF	75.7 PSF	59.8 PSF	60.6 PSF	47.8 PSF	60.6 PSF	47.8 PSF	247.00 LB-FT	265.2 LB	627.5 LB	440.3 LB
24 "	42 "	6720 in²	82.8 PSF	65.3 PSF	82.8 PSF	65.3 PSF	70.9 PSF	56.0 PSF	70.9 PSF	56.0 PSF	59.1 PSF	46.7 PSF	59.1 PSF	46.7 PSF	47.3 PSF	37.3 PSF	47.3 PSF	37.3 PSF	247.00 LB-FT	207.0 LB	538.8 LB	425.1 LB
30 "			68.1 PSF	53.7 PSF	68.1 PSF	53.7 PSF	58.3 PSF	46.0 PSF	58.3 PSF	46.0 PSF	48.6 PSF	38.4 PSF	48.6 PSF	38.4 PSF	38.9 PSF	30.7 PSF	38.9 PSF	30.7 PSF	247.00 LB-FT	170.2 LB	483.4 LB	416.1 LB
36 "			57.9 PSF	45.7 PSF	57.9 PSF	45.7 PSF	49.6 PSF	39.1 PSF	49.6 PSF	39.1 PSF	41.3 PSF	32.6 PSF	41.3 PSF	32.6 PSF	33.0 PSF	26.1 PSF	33.0 PSF	26.1 PSF	247.00 LB-FT	144.7 LB	445.3 LB	410.2 LB
18 "	48 "	9216 in²	79.5 PSF	62.8 PSF	79.5 PSF	62.8 PSF	68.2 PSF	53.8 PSF	68.2 PSF	53.8 PSF	56.8 PSF	44.8 PSF	56.8 PSF	44.8 PSF	45.4 PSF	35.8 PSF	45.4 PSF	35.8 PSF	247.00 LB-FT	265.2 LB	660.6 LB	473.5 LB
24 "			62.1 PSF	49.0 PSF	62.1 PSF	49.0 PSF	53.2 PSF	42.0 PSF	53.2 PSF	42.0 PSF	44.3 PSF	35.0 PSF	44.3 PSF	35.0 PSF	35.4 PSF	28.0 PSF	35.4 PSF	28.0 PSF	247.00 LB-FT	207.0 LB	564.7 LB	451.0 LB
30 "			51.0 PSF	40.3 PSF	51.0 PSF	40.3 PSF	43.7 PSF	34.5 PSF	43.7 PSF	34.5 PSF	36.4 PSF	28.8 PSF	36.4 PSF	28.8 PSF	29.1 PSF	23.0 PSF	29.1 PSF	23.0 PSF	247.00 LB-FT	170.2 LB	504.7 LB	437.4 LB
36 "	48 "	9216 in²	43.4 PSF	34.2 PSF	43.4 PSF	34.2 PSF	37.2 PSF	29.3 PSF	37.2 PSF	29.3 PSF	31.0 PSF	24.4 PSF	31.0 PSF	24.4 PSF	24.8 PSF	19.5 PSF	24.8 PSF	19.5 PSF	247.00 LB-FT	144.7 LB	463.4 LB	428.3 LB
18 "			58.0 PSF	45.8 PSF	58.0 PSF	45.8 PSF	49.7 PSF	39.2 PSF	49.7 PSF	39.2 PSF	41.4 PSF	32.7 PSF	41.4 PSF	32.7 PSF	33.1 PSF	26.1 PSF	33.1 PSF	26.1 PSF	247.00 LB-FT	265.2 LB	693.8 LB	506.6 LB
24 "			45.2 PSF	35.7 PSF	45.2 PSF	35.7 PSF	38.8 PSF	30.6 PSF	38.8 PSF	30.6 PSF	32.3 PSF	25.5 PSF	32.3 PSF	25.5 PSF	25.8 PSF	20.4 PSF	25.8 PSF	20.4 PSF	247.00 LB-FT	207.0 LB	590.6 LB	476.9 LB
30 "	48 "	9216 in²	37.2 PSF	29.4 PSF	37.2 PSF	29.4 PSF	31.9 PSF	25.2 PSF	31.9 PSF	25.2 PSF	26.6 PSF	21.0 PSF	26.6 PSF	21.0 PSF	21.2 PSF	16.8 PSF	21.2 PSF	16.8 PSF	247.00 LB-FT	170.2 LB	525.9 LB	458.7 LB
36 "			31.6 PSF	25.0 PSF	31.6 PSF	25.0 PSF	27.1 PSF	21.4 PSF	27.1 PSF	21.4 PSF	22.6 PSF	17.8 PSF	22.6 PSF	17.8 PSF					247.00 LB-FT	144.7 LB	481.5 LB	419.4 LB

48" STAND DEPTH: MAX FACE AREA (1656in² - 6912in²), FRAME QUANTITY (3-6 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO																MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 6 FRAMES				MAX FACE AREA : 5 FRAMES				MAX FACE AREA : 4 FRAMES				MAX FACE AREA : 3 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	1656 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	184.5 PSF	145.6 PSF	184.5 PSF	145.6 PSF	138.3 PSF	109.2 PSF	138.3 PSF	109.2 PSF	247.00 LB-FT	265.2 LB	557.2 LB	374.0 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	180.0 PSF	142.1 PSF	180.0 PSF	142.1 PSF	144.0 PSF	113.7 PSF	144.0 PSF	113.7 PSF	108.0 PSF	85.2 PSF	108.0 PSF	85.2 PSF	247.00 LB-FT	207.0 LB	486.4 LB	373.3 LB
30 "			177.6 PSF	140.2 PSF	177.6 PSF	140.2 PSF	148.0 PSF	116.8 PSF	148.0 PSF	116.8 PSF	118.4 PSF	93.5 PSF	118.4 PSF	93.5 PSF	88.8 PSF	70.1 PSF	88.8 PSF	70.1 PSF	247.00 LB-FT	170.2 LB	442.4 LB	373.6 LB
36 "			151.0 PSF	119.2 PSF	151.0 PSF	119.2 PSF	125.8 PSF	99.3 PSF	125.8 PSF	99.3 PSF	100.7 PSF	79.5 PSF	100.7 PSF	79.5 PSF	75.5 PSF	59.6 PSF	75.5 PSF	59.6 PSF	247.00 LB-FT	144.7 LB	410.7 LB	374.0 LB
18 "	30 "	2790 in²	156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	136.8 PSF	108.0 PSF	136.8 PSF	108.0 PSF	109.5 PSF	86.4 PSF	109.5 PSF	86.4 PSF	82.1 PSF	64.8 PSF	82.1 PSF	64.8 PSF	247.00 LB-FT	265.2 LB	593.7 LB	407.2 LB
24 "			128.2 PSF	101.2 PSF	128.2 PSF	101.2 PSF	106.8 PSF	84.3 PSF	106.8 PSF	84.3 PSF	85.4 PSF	67.4 PSF	85.4 PSF	67.4 PSF	64.1 PSF	50.6 PSF	64.1 PSF	50.6 PSF	247.00 LB-FT	207.0 LB	514.5 LB	399.2 LB
30 "			105.4 PSF	83.2 PSF	105.4 PSF	83.2 PSF	87.8 PSF	69.3 PSF	87.8 PSF	69.3 PSF	70.3 PSF	55.5 PSF	70.3 PSF	55.5 PSF	52.7 PSF	41.6 PSF	52.7 PSF	41.6 PSF	247.00 LB-FT	170.2 LB	463.7 LB	394.9 LB
36 "			89.6 PSF	70.7 PSF	89.6 PSF	70.7 PSF	74.7 PSF	58.9 PSF	74.7 PSF	58.9 PSF	59.7 PSF	47.1 PSF	59.7 PSF	47.1 PSF	44.8 PSF	35.3 PSF	44.8 PSF	35.3 PSF	247.00 LB-FT	144.7 LB	428.8 LB	392.1 LB
18 "	36 "	3780 in²	115.4 PSF	95.7 PSF	115.4 PSF	95.7 PSF	101.0 PSF	79.7 PSF	101.0 PSF	79.7 PSF	80.8 PSF	63.8 PSF	80.8 PSF	63.8 PSF	60.6 PSF	47.8 PSF	60.6 PSF	47.8 PSF	247.00 LB-FT	265.2 LB	629.1 LB	440.3 LB
24 "			94.6 PSF	74.7 PSF	94.6 PSF	74.7 PSF	78.8 PSF	62.2 PSF	78.8 PSF	62.2 PSF	63.1 PSF	49.8 PSF	63.1 PSF	49.8 PSF	47.3 PSF	37.3 PSF	47.3 PSF	37.3 PSF	247.00 LB-FT	207.0 LB	540.4 LB	425.1 LB
30 "			77.8 PSF	61.4 PSF	77.8 PSF	61.4 PSF	64.8 PSF	51.2 PSF	64.8 PSF	51.2 PSF	51.8 PSF	40.9 PSF	51.8 PSF	40.9 PSF	38.9 PSF	30.7 PSF	38.9 PSF	30.7 PSF	247.00 LB-FT	170.2 LB	485.0 LB	416.1 LB
36 "			66.1 PSF	52.2 PSF	66.1 PSF	52.2 PSF	55.1 PSF	43.5 PSF	55.1 PSF	43.5 PSF	44.1 PSF	34.8 PSF	44.1 PSF	34.8 PSF	33.0 PSF	26.1 PSF	33.0 PSF	26.1 PSF	247.00 LB-FT	144.7 LB	446.9 LB	410.2 LB
18 "	42 "	5040 in²	86.6 PSF	71.7 PSF	86.6 PSF	71.7 PSF	75.7 PSF	59.8 PSF	75.7 PSF	59.8 PSF	60.6 PSF	47.8 PSF	60.6 PSF	47.8 PSF	45.4 PSF	35.8 PSF	45.4 PSF	35.8 PSF	247.00 LB-FT	265.2 LB	662.2 LB	473.5 LB
24 "			70.9 PSF	56.0 PSF	70.9 PSF	56.0 PSF	59.1 PSF	46.7 PSF	59.1 PSF	46.7 PSF	47.3 PSF	37.3 PSF	47.3 PSF	37.3 PSF	35.4 PSF	28.0 PSF	35.4 PSF	28.0 PSF	247.00 LB-FT	207.0 LB	566.3 LB	451.0 LB
30 "			58.3 PSF	46.0 PSF	58.3 PSF	46.0 PSF	48.6 PSF	38.4 PSF	48.6 PSF	38.4 PSF	38.9 PSF	30.7 PSF	38.9 PSF	30.7 PSF	29.1 PSF	23.0 PSF	29.1 PSF	23.0 PSF	247.00 LB-FT	170.2 LB	506.3 LB	437.4 LB
36 "			49.6 PSF	39.1 PSF	49.6 PSF	39.1 PSF	41.3 PSF	32.6 PSF	41.3 PSF	32.6 PSF	33.0 PSF	26.1 PSF	33.0 PSF	26.1 PSF	24.8 PSF	19.5 PSF	24.8 PSF	19.5 PSF	247.00 LB-FT	144.7 LB	465.0 LB	428.3 LB
18 "	48 "	6912 in²	63.1 PSF	49.8 PSF	63.1 PSF	49.8 PSF	55.2 PSF	43.6 PSF	55.2 PSF	43.6 PSF	44.2 PSF	34.8 PSF	44.2 PSF	34.8 PSF	33.1 PSF	26.1 PSF	33.1 PSF	26.1 PSF	247.00 LB-FT	265.2 LB	693.1 LB	506.6 LB
24 "			51.7 PSF	40.8 PSF	51.7 PSF	40.8 PSF	43.1 PSF	34.0 PSF	43.1 PSF	34.0 PSF	34.5 PSF	27.2 PSF	34.5 PSF	27.2 PSF	25.8 PSF	20.4 PSF	25.8 PSF	20.4 PSF	247.00 LB-FT	207.0 LB	592.2 LB	476.9 LB
30 "			42.5 PSF	33.6 PSF	42.5 PSF	33.6 PSF	35.4 PSF	28.0 PSF	35.4 PSF	28.0 PSF	28.3 PSF	22.4 PSF	28.3 PSF	22.4 PSF	21.2 PSF	16.8 PSF	21.2 PSF	16.8 PSF	247.00 LB-FT	170.2 LB	527.5 LB	458.7 LB
36 "			36.1 PSF	28.5 PSF	36.1 PSF	28.5 PSF	30.1 PSF	23.8 PSF	30.1 PSF	23.8 PSF	24.1 PSF	19.0 PSF	24.1 PSF	19.0 PSF						247.00 LB-FT	144.7 LB	483.1 LB

"FIXED HD" STAND DESIGN SCHEDULE CONTINUED

48" STAND DEPTH: MAX FACE AREA (552in² - 2304in²), FRAME QUANTITY (2-3 FRAMES)

STAND CLEAR HEIGHT	MAX MEAN UNIT HEIGHT	MAX FACE AREA	UNIT TO FRAME RATIO								MAX. BASE MOMENT (M)	MAX. BASE SHEAR (V)	MAX. BASE UPLIFT (T)	MAX. BASE GRAVITY (C)
			MAX FACE AREA : 3 FRAMES				MAX FACE AREA : 2 FRAMES							
			ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHOR TYPE: 2 OR 3					
			MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT				
18 "	24 "	552 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	178.50 LB-FT	191.6 LB	403.6 LB	240.2 LB
24 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	228.70 LB-FT	191.6 LB	451.5 LB	288.1 LB
30 "			200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	177.6 PSF	140.2 PSF	177.6 PSF	140.2 PSF	247.00 LB-FT	170.2 LB	442.4 LB	306.1 LB
18 "	30 "	690 in²	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	200.0 PSF	157.8 PSF	223.20 LB-FT	239.5 LB	537.2 LB	313.3 LB
24 "			156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	128.2 PSF	101.2 PSF	128.2 PSF	101.2 PSF	247.00 LB-FT	207.0 LB	514.5 LB	331.7 LB
30 "			156.4 PSF	123.5 PSF	156.4 PSF	123.5 PSF	105.4 PSF	83.2 PSF	105.4 PSF	83.2 PSF	247.00 LB-FT	170.2 LB	463.7 LB	327.4 LB
36 "	36 "	1116 in²	134.5 PSF	106.1 PSF	134.5 PSF	106.1 PSF	89.6 PSF	70.7 PSF	89.6 PSF	70.7 PSF	247.00 LB-FT	144.7 LB	432.5 LB	324.6 LB
18 "			130.4 PSF	106.1 PSF	130.4 PSF	106.1 PSF	108.0 PSF	108.0 PSF	130.4 PSF	108.0 PSF	247.00 LB-FT	265.2 LB	629.1 LB	372.8 LB
24 "			115.4 PSF	112.0 PSF	115.4 PSF	112.0 PSF	94.6 PSF	74.7 PSF	94.6 PSF	74.7 PSF	247.00 LB-FT	207.0 LB	544.2 LB	357.6 LB
30 "	42 "	1470 in²	115.4 PSF	92.1 PSF	115.4 PSF	92.1 PSF	77.8 PSF	61.4 PSF	77.8 PSF	61.4 PSF	247.00 LB-FT	170.2 LB	488.7 LB	348.6 LB
36 "			99.2 PSF	78.3 PSF	99.2 PSF	78.3 PSF	66.1 PSF	52.2 PSF	66.1 PSF	52.2 PSF	247.00 LB-FT	144.7 LB	450.6 LB	342.7 LB
18 "			98.9 PSF	123.0 PSF	98.9 PSF	123.0 PSF	98.9 PSF	82.0 PSF	98.9 PSF	82.0 PSF	247.00 LB-FT	265.2 LB	666.0 LB	406.0 LB
24 "	48 "	1920 in²	86.6 PSF	84.0 PSF	86.6 PSF	84.0 PSF	70.9 PSF	56.0 PSF	70.9 PSF	56.0 PSF	247.00 LB-FT	207.0 LB	570.0 LB	383.5 LB
30 "			86.6 PSF	69.1 PSF	86.6 PSF	69.1 PSF	58.3 PSF	46.0 PSF	58.3 PSF	46.0 PSF	247.00 LB-FT	170.2 LB	510.0 LB	369.9 LB
36 "			74.4 PSF	58.7 PSF	74.4 PSF	58.7 PSF	49.6 PSF	39.1 PSF	49.6 PSF	39.1 PSF	247.00 LB-FT	144.7 LB	468.7 LB	360.8 LB
18 "	48 "	1920 in²	75.7 PSF	59.8 PSF	75.7 PSF	59.8 PSF	75.7 PSF	59.8 PSF	75.7 PSF	59.8 PSF	235.30 LB-FT	252.6 LB	661.9 LB	421.5 LB
24 "			63.1 PSF	49.8 PSF	63.1 PSF	49.8 PSF	51.7 PSF	40.8 PSF	51.7 PSF	40.8 PSF	247.00 LB-FT	207.0 LB	592.2 LB	409.4 LB
30 "			63.1 PSF	49.8 PSF	63.1 PSF	49.8 PSF	42.5 PSF	33.6 PSF	42.5 PSF	33.6 PSF	247.00 LB-FT	170.2 LB	527.5 LB	391.2 LB
36 "			54.2 PSF	42.8 PSF	54.2 PSF	42.8 PSF	36.1 PSF	28.5 PSF	36.1 PSF	28.5 PSF	247.00 LB-FT	144.7 LB	486.8 LB	378.9 LB

DESIGN SCHEDULE NOTES:

1. MAXIMUM CALCULATED FACE AREA SHALL BE EQUAL TO OR LESS THAN THE MAXIMUM ALLOWABLE FACE AREA FOR EACH CONFIGURATION. REFERENCE ANCHOR SCHEDULE FOR ANCHOR TYPES LISTED HEREIN.


"HD CUSTOM CROSS-BRACE" STAND DESIGN SCHEDULE

24" STAND DEPTH:




MAX UNIT DIMENSIONS (W x D x H)	STAND CLEAR HEIGHT	UNIT TO FRAME RATIO								LOAD TRANSFER INFORMATION FOR USE WITH HOST STRUCTURE VERIFICATION ONLY			
		(1) UNIT: (3) FRAMES				(2) UNITS: (4) FRAMES				(3) UNITS: (5) FRAMES			
		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3	
		MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT
48" WIDTH 48" DEPTH 66" HEIGHT	18"	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF
	24"	35.6 PSF	28.1 PSF	33.0 PSF	26.0 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF
	30"	35.6 PSF	28.1 PSF	33.0 PSF	26.0 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF
	36"	35.6 PSF	28.1 PSF	31.3 PSF	24.7 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF	35.6 PSF	28.1 PSF

36" STAND DEPTH:

MAX UNIT DIMENSIONS (W x D x H)	STAND CLEAR HEIGHT	UNIT TO FRAME RATIO								LOAD TRANSFER INFORMATION FOR USE WITH HOST STRUCTURE VERIFICATION ONLY			
		(1) UNIT: (3) FRAMES				(2) UNITS: (4) FRAMES				(3) UNITS: (5) FRAMES			
		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3		ANCHOR TYPE: 1 OR 4		ANCHORS TYPE: 2 OR 3	
		MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT	MAX ALLOWABLE LATERAL LOAD	MAX ALLOWABLE UPLIFT
48" WIDTH 48" DEPTH 66" HEIGHT	18"	50.2 PSF	39.6 PSF	41.9 PSF	33.0 PSF	50.2 PSF	39.6 PSF	50.2 PSF	39.6 PSF	50.2 PSF	39.6 PSF	50.2 PSF	39.6 PSF
	24"	44.0 PSF	34.7 PSF	35.6 PSF	28.1 PSF	50.2 PSF	39.6 PSF	42.7 PSF	33.7 PSF	50.2 PSF	39.6 PSF	42.7 PSF	33.7 PSF
	30"	39.0 PSF	30.8 PSF	35.6 PSF	28.1 PSF	46.9 PSF	37.0 PSF	42.7 PSF	33.7 PSF	46.9 PSF	37.0 PSF	42.7 PSF	33.7 PSF
	36"	33.5 PSF	26.5 PSF	33.5 PSF	26.5 PSF	40.2 PSF	31.8 PSF	40.2 PSF	31.8 PSF	40.2 PSF	31.8 PSF	40.2 PSF	31.8 PSF



HD CUSTOM CROSS-BRACE ASSEMBLY ALLOWABLE CONFIGURATIONS:



FL# 16921.1

ENGINEERING EXPRESS
CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM

PRECISION ALUMINUM PRODUCTS, INC.

1339 SW 1ST WAY
DEERFIELD BEACH, FL 33441
PH: (954) 480-6919

ALUMINUM A/C STANDS HVHZ & NON-HVHZ APPLICATIONS
FLORIDA BUILDING CODE SEVENTH EDITION (2020)
PRODUCT APPROVAL FL# 16921.1


REMARKS	DATE	CHKD	DATE
INIT ISSUE	07-08-09	FLB	
REV 2010 FBC	08-11-12	TSB	
REV FBC 5TH (2014)	06-15-15	CSL	
REV FBC 6TH (2017)	09-02-17	LAO	
REV FBC 7TH (2020)	12-15-20	CSL	

ALTERNATIONS, ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALID DATE OUT CERTIFICATION.


20-32768

SCALE:


FRAME ASSEMBLY & UNIT TIE-DOWN DETAILS:




1
16 **FRAME ASSEMBLY DETAIL**




3
16 **BASE PLATE DETAIL**




5
16 **ALTERNATE BASE PLATE ATTACHMENT AT WOOD/STEEL TRUSS MEMBERS**



2
16 **A/C UNIT TIE-DOWN DETAIL**



4
16 **BASEPLATE REACTIONS**



SECTION A-A (SIDE-VIEW)

ANCHOR SCHEDULE

FOR USE WITH DETAIL 3 ON THIS SHEET ONLY

ANCHOR TYPE	HOST STRUCTURE	ANCHOR DESCRIPTION
1	STEEL	(4) 3/8" SAE GRADE 2 GALVANIZED BOLTS W/ NUT & 3/4" MIN. WASHER, TO STRUCTURAL A36 STEEL MEMBERS (3/16" MIN HOST THICKNESS)
2	CONCRETE	(4) 1/4" POWERS WEDGE-BOLT CONCRETE ANCHORS OR EQUIVALENT WITH 5/8" MIN. WASHER, 2-1/2" EMBEDMENT & 3" MIN EDGE DISTANCE, SPACING PER THE FOLLOWING = (BASE PLATE WIDTH - 1.75").
3	WOOD	SEE DETAIL 5/16: USE DETAIL 3/16 FOR GROUND MOUNT ONLY WHEN APPROVED BY EOR/BUILDING OFFICIAL (SEE NOTES BELOW). (4)-3/8" LAG SCREWS w/WASHER, 2-1/2" THREAD PENETRATION, 2" EDGE DISTANCE.
4	STEEL	(4) 5/16" SAE GRADE 5 SHEET METAL SCREWS WITH 5/8" MIN. WASHER TO STRUCTURAL A36 STEEL MEMBERS (3/16" MIN HOST THICKNESS)


ANCHOR NOTES:

- ANCHORS SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURERS' RECOMMENDATIONS.
- ENSURE MINIMUM EDGE DISTANCE AS NOTED IN ANCHOR SCHEDULE FOR EACH ANCHOR.
- ALL CONCRETE SUBSTRATE SHALL HAVE MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI. CONCRETE SUBSTRATE THICKNESS SHALL BE GREATER THAN OR EQUAL TO 1.5xANCHOR EMBEDMENT. INSTALL CONCRETE ANCHORS TO UN-CRACKED CONCRETE ONLY.
- MINIMUM EMBEDMENT SHALL BE AS NOTED IN ANCHOR SCHEDULE. MINIMUM EMBEDMENT AND EDGE DISTANCE EXCLUDES ROOFING FINISHES.
- WHERE EXISTING STRUCTURE IS WOOD TRUSSES, EXISTING CONDITIONS MAY VARY. FIELD VERIFY THAT FASTENERS ARE INTO ADEQUATE WOOD TRUSS MEMBERS, NOT INTO PLYWOOD.


THE CONNECTION OF THE AC STAND TO THE SUPPORTING HOST STRUCTURE IS ASSUMED TO BE A RIGID CONNECTION. THE INSTALLER SHALL ENSURE THAT ANY ROTATION OF THE SUPPORTING HOST STRUCTURE IS STRICTLY PREVENTED. IN ADDITION, THE INSTALLER SHALL ENSURE THE HOST STRUCTURE CAN ADEQUATELY SUPPORT THE REACTIONS PROVIDED IN THIS APPROVAL.

IF THE INSTALLER IS UNABLE TO VERIFY THESE REQUIREMENTS, THE BUILDING OFFICIAL SHALL REQUIRE A SITE SPECIFIC EVALUATION TO ENSURE STAND STABILITY.

DATE	CHKD	DATE	CHKD
07-08-09	FLB	07-08-09	FLB
05-11-12	TSB	05-11-12	TSB
06-15-15	CSL	06-15-15	CSL
09-02-17	LAO	09-02-17	LAO
12-15-20	CSL	12-15-20	CSL



SECTION A-A (SECTION-VIEW)



SECTION B-B (PLAN-VIEW)

1 17 ALTERNATE BASE PLATE ATTACHMENT AT WOOD TRUSS MEMBERS



FOR USE AS AN ALTERNATE ATTACHMENT METHOD FOR TO WOOD

NOTE: USE OF THIS DETAIL (1/17) IS RESTRICTED TO FOLLOWING:

- ONLY APPLICABLE FOR THE FOLLOWING STAND TYPES: STD, HD, FIXED-HD
- LIMITED TO 60% OF THE ALLOWABLE DESIGN PRESSURE LISTED IN THE DESIGN TABLES.

EXAMPLE: MAX ALLOWABLE LATERAL LOAD PER DESIGN SCHEDULES = 95 PSF
MAX ALLOWABLE UPLIFT LOAD PER DESIGN SCHEDULE = 70 PSF

MAX ALLOWABLE LATERAL LOAD PER DETAIL (1/17) = 95 PSF x (0.60) = 57 PSF
MAX ALLOWABLE UPLIFT LOAD PER DETAIL (1/17) = 70 PSF x (0.60) = 42 PSF



SECTION C-C (SIDE-VIEW)

2 17 SMALL UNIT ANGLE ATTACHMENT DETAIL

THE CONNECTION OF THE AC STAND TO THE SUPPORTING HOST STRUCTURE IS ASSUMED TO BE A RIGID CONNECTION. THE INSTALLER SHALL ENSURE THAT ANY ROTATION OF THE SUPPORTING HOST STRUCTURE IS STRICTLY PREVENTED. IN ADDITION, THE INSTALLER SHALL ENSURE THE HOST STRUCTURE CAN ADEQUATELY SUPPORT THE REACTIONS PROVIDED IN THIS APPROVAL.

IF THE INSTALLER IS UNABLE TO VERIFY THESE REQUIREMENTS, THE BUILDING OFFICIAL SHALL REQUIRE A SITE SPECIFIC EVALUATION TO ENSURE STAND STABILITY.

FRANK BENNARD, PE
PE# 0046549 CA# 9885



FL# 16921.1

ENGINEERING EXPRESS
CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM

PRECISION ALUMINUM PRODUCTS, INC.
1339 SW 1ST WAY
DEERFIELD BEACH, FL 33441
PH: (954)-480-6919
ALUMINUM A/C STANDS HVHZ & NON-HVHZ APPLICATIONS
FLORIDA BUILDING CODE SEVENTH EDITION (2020)
PRODUCT APPROVAL FL# 16921.1

REMARKS	DRWN	CHKD	DATE
INIT ISSUE	TSB	FLB	07-08-09
REV 2010 FBC	CSL	TSB	05-11-12
REV FBC 5TH (2014)	CSL	CSL	06-15-15
REV FBC 6TH (2017)	LAO	FLB	09-02-17
REV FBC 7TH (2020)	CSL	RWN	12-15-20

COPYRIGHT ENGINEERING EXPRESS®

20-32768

SCALE:

17

17