



THIN LEADING EDGE - TLE

PRODUCT DATA SHEET

NAME	LENGTH	OVERAL WIDTH	EXPOSED WIDTH	NAIL HOLE FROM END	THICKNESS	DRY WEIGHT
------	--------	--------------	---------------	--------------------	-----------	------------

TLE	17	13	12	1 1/2	0.67	10.25
-----	----	----	----	-------	------	-------

NOTES:

1. THE PRODUCT ILLUSTRATED SATISFIES THE REQUIREMENTS FOR THE 2014 FLORIDA BUILDING CODE INCLUDING HVHZ.
2. FOR NON-HVHZ, INSTALLATION SHALL COMPLY WITH THE MANUFACTURER'S CURRENT PUBLISHED INSTALLATION INSTRUCTIONS, BUT NOT LESS THAN THE REQUIREMENTS AS ESTABLISHED IN FBC SECTION 1507.3 AND THE FRSA/TRI 07320 FOR MECHANICALLY FASTENED INSTALLATIONS.
3. FOR NON-HVHZ, INSTALLATION SHALL COMPLY WITH THE MANUFACTURER'S CURRENT PUBLISHED INSTALLATION INSTRUCTIONS, BUT NOT LESS THAN THE REQUIREMENTS AS ESTABLISHED IN FBC SECTION 1607.7.3 AND THE MORTAR OR ADHESIVE MANUFACTURER'S PRODUCT APPROVAL FOR MORTAR AND ADHESIVE INSTALLATIONS.
4. FOR HVHZ INSTALLATIONS, A STATIC FIELD UPLIFT TEST SHALL BE PERFORMED IN ACCORDANCE WITH TAS 106 FOR MORTAR OR ADHESIVE SET TILE INSTALLATIONS.

FASTENER HOLES

