

SERIES 8200 ALUMINUM CURTAIN WALL SYSTEM

- CURTAIN WALL SYSTEM IS RATED FOR SMALL MISSILE IMPACT. IMPACT SHUTTERS ARE NOT REQUIRED FOR ELEVATIONS ABOVE 30'-0" FROM GRADE. IMPACT SHUTTERS ARE REQUIRED FOR ELEVATIONS BELOW 30'-0" FROM GRADE.
 - THIS SYSTEM MAY BE USED IN CONJUNCTION WITH MIAMI DADE COUNTY APPROVED ENTRANCE DOORS.
 - CODE REQUIREMENTS FOR SAFEGUARDS MUST BE OBSERVED.
-
- THIS PRODUCT HAS BEEN DESIGNED AND TESTED TO COMPLY WITH THE REQUIREMENTS OF THE FLORIDA BUILDING CODE 7TH EDITION (2020) / 8TH EDITION (2023) INCLUDING HIGH VELOCITY HURRICANE ZONE (HVHZ).
 - WOOD BUCKS BY OTHERS, MUST BE ANCHORED PROPERLY TO TRANSFER LOADS TO THE STRUCTURE.
 - ANCHORS SHALL BE AS LISTED, SPACED AS SHOWN ON DETAILS, ANCHORS EMBEDMENT TO BASE MATERIAL SHALL BE BEYOND WALL DRESSING OR STUCCO.
 - ANCHORING OR LOADING CONDITIONS NOT SHOWN IN THESE DETAILS ARE NOT PART OF THIS APPROVAL.
 - A LOAD DURATION INCREASE IS USED IN DESIGN OF ANCHORS INTO WOOD ONLY.
 - MATERIALS INCLUDING BUT NOT LIMITED TO STEEL/METAL SCREWS THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF THE FLORIDA BUILDING CODE 7TH EDITION (2020) / 8TH EDITION (2023) SECTION AS APPLICABLE.
 - ULTIMATE DESIGN LOAD OBTAINED FROM ASCE-7-22, MULTIPLY BY 0.6 SHALL BE LESS THAN OR EQUAL TO MAX. DESIGN LOAD IN THIS DOCUMENT. THE DESIGN LOADS SHOWN IN THE DOCUMENT ARE ALLOWABLE DESIGN LOADS.
 - MANUFACTURER'S LABEL SHALL BE LOCATED ON A READILY VISIBLE LOCATION IN ACCORDANCE WITH SECTION 1709.9.3 OF FLORIDA BUILDING CODE LABELING TO COMPLY WITH SECTION 1709.9.2.


INSTRUCTIONS:

USE CHARTS AS FOLLOWS.

- STEP 1: DETERMINE DESIGN WIND LOAD REQUIREMENTS BASED ON WIND VELOCITY, BLDG. HEIGHT, WIND ZONE USING APPLICABLE ASCE 7-22 STANDARD.
- STEP 2: SEE CHARTS ON SHEET G1 FOR DESIGN LOAD CAPACITY OF DESIRED GLASS SIZE BASED ON APPLICABLE WIND DURATION.
- STEP 3: CHECK MULLION AND JAMB CAPACITY FOR A GIVEN SPACING AND HEIGHT USING CHARTS ON SHEET M1 THROUGH J11. THE CAPACITY SHOULD EXCEED THE DESIGN LOAD.
- STEP 4: USING CHART ON SHEETS A1 THROUGH A4 SELECT ANCHOR OPTION WITH DESIGN RATING MORE THAN DESIGN LOAD SPECIFIED IN STEP 1 ABOVE.
- STEP 5: THE LOWEST VALUE RESULTING FROM STEPS 2, 3 AND 4 SHALL APPLY TO ENTIRE SYSTEM.

ABBREVIATIONS AND SYMBOLS

- D.L.O. - DAYLITE OPENING
F.H. - FRAME HEIGHT
F.W. - FRAME WIDTH
W - WITH
W/O - WITHOUT
O.C. - ON CENTER
CW - CURTAIN WALL



LIMITATIONS OF USE

- A- THIS PRODUCT EVALUATION DOCUMENT (P.E.D.) PREPARED BY THIS ENGINEER IS GENERIC AND DOES NOT PROVIDE INFORMATION FOR A SITE SPECIFIC PROJECT; i.e. WHERE THE SITE CONDITIONS DEVIATE FROM THE P.E.D.
- B- CONTRACTOR TO BE RESPONSIBLE FOR THE SELECTION, PURCHASE AND INSTALLATION OF THIS PRODUCT BASED ON THIS PRODUCT EVALUATION PROVIDED HE/SHE DOES NOT DEVIATE FROM THE CONDITIONS DETAILED ON THIS DOCUMENT.
- C- THIS PRODUCT EVALUATION DOCUMENT WILL BE CONSIDERED INVALID IF ALTERED BY ANY MEANS.
- D- SITE SPECIFIC PROJECTS SHALL BE PREPARED BY A FLORIDA REGISTERED ENGINEER OR ARCHITECT WHICH WILL BECOME THE ENGINEER OF RECORD (E.O.R.) FOR THE PROJECT AND WHO WILL BE RESPONSIBLE FOR THE PROPER USE OF THE P.E.D.
- E- THIS P.E.D. SHALL BEAR THE DATE AND ORIGINAL SEAL AND SIGNATURE OF THE PROFESSIONAL ENGINEER OF RECORD THAT PREPARED IT.



http://www.trulite.com

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



REV#	DATE/REMARKS
REV 2	FBC 2023 UPDATE


ENGINEER:



MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd. 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:





COVER

DRAWN: James	SHEET No: 1 OF 23
DATE: 08.03.23	
DWG: AD16-18	

GLASS LOAD CAPACITY - PSF			
DAYLIGHT OPENING SIZE		GLASS TYPES	
		DRY GLAZED	
D.L.O. H. (IN.)	D.L.O. W. (IN.)	A	B
60	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	150.0	150.0
	45.5	150.0	150.0
	48.5	150.0	150.0
	51.5	150.0	150.0
	54.5	150.0	150.0
	57.5	150.0	150.0
66	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	150.0	150.0
	45.5	150.0	150.0
	48.5	150.0	150.0
	51.5	150.0	150.0
	54.5	150.0	150.0
	57.5	150.0	150.0
72	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	150.0	150.0
	45.5	150.0	150.0
	48.5	150.0	150.0
	51.5	150.0	150.0
	54.5	150.0	150.0
	57.5	150.0	150.0
78	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	150.0	150.0
	45.5	150.0	150.0
	48.5	150.0	150.0
	51.5	150.0	150.0
	54.5	150.0	150.0
	57.5	149.0	149.0
84	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	150.0	150.0
	45.5	150.0	150.0
	48.5	150.0	150.0
	51.5	150.0	150.0
	54.5	145.0	145.0
	57.5	142.0	142.0
90	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	150.0	150.0
	45.5	150.0	150.0
	48.5	149.0	149.0

GLASS LOAD CAPACITY - PSF			
DAYLIGHT OPENING SIZE		GLASS TYPES	
		DRY GLAZED	
D.L.O. H. (IN.)	D.L.O. W. (IN.)	A	B
96	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	150.0	150.0
	45.5	149.0	149.0
	48.5	141.0	141.0
102	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	150.0	150.0
	45.5	141.0	141.0
108	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
	42.5	145.0	145.0
	45.5	141.0	141.0
114	33.5	150.0	150.0
	36.5	150.0	150.0
	39.5	150.0	150.0
121	33.5	150.0	150.0
	36.5	150.0	150.0

NOTE:
GLASS CAPACITIES ON THIS SHEET ARE
BASED ON ASTM E1300-09 (3 SEC. GUSTS)



http://www.trulite.com
403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:
Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



REV#	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:
MCY ENGINEERING, INC.
GLAZING CONSULTANT
12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:
YIPING WANG
FLORIDA REGISTRATION
No. 55983
C.A.N. 28677
August 03rd, 2023


FLORIDA APPROVAL:
FL #25679.2

SHEET TITLE:
G1


DRAWN: James	SHEET No:
DATE: 08.03.23	3 OF 23
DWG: AD16-18	

MULLION DESIGN LOAD CAPACITIES							
MULLION DIMENSIONS		MULLION (M1)		JAMB MULLION (J1)		JAMB MULLION (J3)	
		DESIGN LOAD		DESIGN LOAD		DESIGN LOAD	
HEIGHT (IN.)	WIDTH (W) (IN.)	(+) PSF	(-) PSF	(+) PSF	(-) PSF	(+) PSF	(-) PSF
78	36	150.0	150.0	150.0	150.0	150.0	150.0
	42	150.0	150.0	150.0	150.0	150.0	150.0
	48	150.0	150.0	150.0	150.0	150.0	150.0
	54	150.0	150.0	150.0	150.0	150.0	150.0
	60	150.0	150.0	150.0	150.0	150.0	150.0
	66	150.0	150.0	150.0	150.0	150.0	150.0
	72	65.0	65.0	65.0	65.0	65.0	65.0
84	36	150.0	150.0	150.0	150.0	150.0	150.0
	42	150.0	150.0	150.0	150.0	150.0	150.0
	48	150.0	150.0	150.0	150.0	150.0	150.0
	54	150.0	150.0	150.0	150.0	150.0	150.0
	60	143.5	143.5	150.0	150.0	143.5	150.0
	66	65.0	65.0	65.0	65.0	65.0	65.0
	72	65.0	65.0	65.0	65.0	65.0	65.0
90	36	150.0	150.0	150.0	150.0	150.0	150.0
	42	150.0	150.0	150.0	150.0	150.0	150.0
	48	150.0	150.0	150.0	150.0	150.0	150.0
	54	138.9	138.9	150.0	150.0	138.9	150.0
	60	65.0	65.0	65.0	65.0	65.0	65.0
	66	65.0	65.0	65.0	65.0	65.0	65.0
	72	65.0	65.0	65.0	65.0	65.0	65.0
96	36	150.0	150.0	150.0	150.0	150.0	150.0
	42	150.0	150.0	150.0	150.0	150.0	150.0
	48	137.3	137.3	150.0	150.0	137.3	150.0
	54	122.0	122.0	150.0	150.0	122.0	150.0
	60	65.0	65.0	65.0	65.0	65.0	65.0
	66	65.0	65.0	65.0	65.0	65.0	65.0
	72	65.0	65.0	65.0	65.0	65.0	65.0
102	36	150.0	150.0	150.0	150.0	150.0	150.0
	42	139.0	139.0	150.0	150.0	139.0	150.0
	48	121.6	121.6	150.0	150.0	149.0	150.0
	54	65.0	65.0	65.0	65.0	65.0	65.0
	60	65.0	65.0	65.0	65.0	65.0	65.0
	66	65.0	65.0	65.0	65.0	65.0	65.0
	72	65.0	65.0	65.0	65.0	65.0	65.0
108	36	144.6	144.6	144.6	150.0	150.0	150.0
	42	124.0	124.0	124.0	150.0	150.0	150.0
	48	108.5	108.5	108.5	150.0	133.0	133.0
	54	65.0	65.0	65.0	65.0	65.0	65.0
	60	65.0	65.0	65.0	65.0	65.0	65.0
	66	65.0	65.0	65.0	65.0	65.0	65.0
114	36	129.8	129.8	150.0	150.0	150.0	150.0
	42	111.3	111.3	150.0	150.0	137.0	137.0
	48	65.0	65.0	65.0	65.0	65.0	65.0
	54	65.0	65.0	65.0	65.0	65.0	65.0
	60	65.0	65.0	65.0	65.0	65.0	65.0
120	36	117.2	117.2	150.0	150.0	144.0	144.0
	42	100.4	100.4	150.0	150.0	123.0	123.0
	48	65.0	65.0	65.0	65.0	65.0	65.0
	54	65.0	65.0	65.0	65.0	65.0	65.0
	60	65.0	65.0	65.0	65.0	65.0	65.0
126	36	104.1	104.1	150.0	150.0	131.0	131.0
	42	65.0	65.0	65.0	65.0	65.0	65.0
	48	65.0	65.0	65.0	65.0	65.0	65.0
	54	65.0	65.0	65.0	65.0	65.0	65.0
	60	65.0	65.0	65.0	65.0	65.0	65.0
132	36	90.5	90.5	150.0	150.0	119.0	119.0
	42	65.0	65.0	65.0	65.0	65.0	65.0
	48	65.0	65.0	65.0	65.0	65.0	65.0
	54	65.0	65.0	65.0	65.0	65.0	65.0


MULLION DESIGN LOAD CAPACITIES							
MULLION DIMENSIONS		MULLION (M1)		JAMB MULLION (J1)		JAMB MULLION (J3)	
		DESIGN LOAD		DESIGN LOAD		DESIGN LOAD	
HEIGHT (IN.)	WIDTH (W) (IN.)	(+) PSF	(-) PSF	(+) PSF	(-) PSF	(+) PSF	(-) PSF
138	36	79.2	79.2	150.0	150.0	109.0	109.0
	42	65.0	65.0	65.0	65.0	65.0	65.0
	48	65.0	65.0	65.0	65.0	65.0	65.0
	54	65.0	65.0	65.0	65.0	65.0	65.0
144	36	69.7	69.7	139.5	139.5	100.0	100.0
	42	65.0	65.0	65.0	65.0	65.0	65.0
	48	65.0	65.0	65.0	65.0	65.0	65.0



WIDTH (W) = W1 (JAMB)




WIDTH (W) = $\frac{W1 + W2}{2}$



WIDTH (W) = $\frac{W1 + W2}{2}$

REFER TO SEPARATE
FLORIDA APPROVED
IMPACT DOOR



MULLION (M1) (J1)



JAMB MULLION (J3)

M1	lx IN^4	Sx IN^3
82501	12.1992	3.5275

J1	lx IN^4	Sx IN^3
82504	9.8902	2.7949

STEP 3: JAMB/MULLION LOAD CAPACITIES



<http://www.trulite.com>

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE


ENGINEER:



MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



FLORIDA APPROVAL:


FL #25679.2

SHEET TITLE:


M1

DRAWN: James	SHEET No:
DATE: 08.03.23	4 OF 23
DWG: AD16-18	


MULLION DESIGN LOAD CAPACITIES							
MULLION DIMENSIONS		MULLION (M2)		MULLION (M3)		JAMB MULLION (J2)(J4)	
		DESIGN LOAD		DESIGN LOAD		DESIGN LOAD	
HEIGHT (IN.)	WIDTH (W) (IN.)	(+) PSF	(-) PSF	(+) PSF	(-) PSF	(+) PSF	(-) PSF
120	42	135.0	135.0	150.0	150.0	150.0	150.0
	48	65.0	65.0	75.0	75.0	75.0	75.0
	54	65.0	65.0	75.0	75.0	75.0	75.0
	60	65.0	65.0	75.0	75.0	75.0	75.0
	66	55.0	55.0	75.0	75.0	75.0	75.0
	72	55.0	55.0	75.0	75.0	75.0	75.0
126	42	128.6	128.6	150.0	150.0	150.0	150.0
	48	65.0	65.0	75.0	75.0	75.0	75.0
	54	65.0	65.0	75.0	75.0	75.0	75.0
	60	65.0	65.0	75.0	75.0	75.0	75.0
	66	55.0	55.0	75.0	75.0	75.0	75.0
	72	55.0	55.0	75.0	75.0	75.0	75.0
132	42	65.0	65.0	75.0	75.0	75.0	75.0
	48	65.0	65.0	75.0	75.0	75.0	75.0
	54	65.0	65.0	75.0	75.0	75.0	75.0
	60	55.0	55.0	75.0	75.0	75.0	75.0
	66	55.0	55.0	75.0	75.0	75.0	75.0
	72	55.0	55.0	75.0	75.0	75.0	75.0
138	42	65.0	65.0	75.0	75.0	75.0	75.0
	48	65.0	65.0	75.0	75.0	75.0	75.0
	54	65.0	65.0	75.0	75.0	75.0	75.0
	60	55.0	55.0	75.0	75.0	75.0	75.0
144	42	65.0	65.0	75.0	75.0	75.0	75.0
	48	65.0	65.0	75.0	75.0	75.0	75.0
	54	55.0	55.0	75.0	75.0	75.0	75.0
	60	55.0	55.0	75.0	75.0	75.0	75.0
150	42	65.0	65.0	75.0	75.0	75.0	75.0
	48	65.0	65.0	75.0	75.0	75.0	75.0
	54	55.0	55.0	75.0	75.0	75.0	75.0
	60	55.0	55.0	75.0	75.0	75.0	75.0
156	42	65.0	65.0	75.0	75.0	75.0	75.0
	48	65.0	65.0	75.0	75.0	75.0	75.0
	54	55.0	55.0	75.0	75.0	75.0	75.0
162	42	65.0	65.0	75.0	75.0	75.0	75.0
	48	55.0	55.0	75.0	75.0	75.0	75.0
	54	55.0	55.0	75.0	75.0	75.0	75.0
168	42	65.0	65.0	75.0	75.0	75.0	75.0
	48	55.0	55.0	75.0	75.0	75.0	75.0
	54	55.0	55.0	75.0	75.0	75.0	75.0




WIDTH (W) = W1 (JAMB)




WIDTH (W) = $\frac{W1 + W2}{2}$




MULLION (M2)



MULLION (M3)



MULLION (J2)



JAMB MULLION (J4)

M2	Ix IN^4	Sx IN^3
82501	12.1992	3.5275
R3	7.4986	-
TOTAL	33.9451	-

M3	Ix IN^4	Sx IN^3
82501	12.1992	3.5275
R4	9.7486	-
TOTAL	40.4701	-

M2	Ix IN^4	Sx IN^3
82501	12.1992	3.5275
R1	4.6177	2.1370
TOTAL	16.8169	-

J2	Ix IN^4	Sx IN^3
82504	9.8902	2.7949
R1	4.6177	2.1370
TOTAL	23.4535	-


PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT


PRODUCT SERIES

REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER: 
MCY ENGINEERING, INC.
GLAZING CONSULTANT
12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP: 
August 03rd, 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

M2


DRAWN: James	SHEET No: 5 OF 23
DATE: 08.03.23	
DWG: AD16-18	

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
108	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
114	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
120	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
120	84	72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
126	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
132	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
138	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0

CHART CONTINUES ON NEXT SHEET



STEP 3: JAMB/MULLION LOAD CAPACITIES

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT

Resistor
PRODUCT SERIES

REV N	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:

MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd. 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

J1

DRAWN: James	SHEET No:
DATE: 08.03.23	6 OF 23
DWG: AD16-18	

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
144	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	54.0	54.0
150	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	53.0	53.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	54.0	54.0
			72	51.0	51.0
156	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	53.0	53.0

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
156	84	72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	53.0	53.0
			72	51.0	51.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	54.0	54.0
			72	51.0	51.0
162	84	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	52.0	52.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	53.0	53.0
			72	50.0	50.0
168	84	72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	54.0	54.0
			66	51.0	51.0
			72	50.0	50.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	53.0	53.0
			66	50.0	50.0
			72	50.0	50.0



GLASS & ALUMINUM SOLUTIONS™

http://www.trulite.com

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE


ENGINEER:



MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd, 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:


J2

DRAWN: James	SHEET No:
DATE: 08.03.23	7 OF 23
DWG: AD16-18	

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
120	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
126	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
132	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
132	96	72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
138	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
144	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	54.0	54.0

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
150	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	54.0	54.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	53.0	53.0



GLASS & ALUMINUM SOLUTIONS™
http://www.trulite.com
403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:
Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT
Resistor
PRODUCT SERIES

REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:
MCY ENGINEERING, INC.
GLAZING CONSULTANT
12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com


STAMP:
YIPING WANG, P.E.
FLORIDA REGISTRATION
No. 55983
C.A.N. 28677
August 03rd, 2023

FLORIDA APPROVAL:
FL #25679.2

SHEET TITLE:
J3
DRAWN: James
DATE: 08.03.23
DWG: AD16-18
SHEET No:
8 OF 23

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
156	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	54.0	54.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	52.0	52.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	53.0	53.0
162	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	53.0	53.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	54.0	54.0
			72	51.0	51.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	52.0	52.0
			72	52.0	52.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	53.0	53.0

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
168	96	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	54.0	54.0
			72	51.0	51.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	52.0	52.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	53.0	53.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	53.0	53.0



403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:

MCY ENGINEERING, INC.
GLAZING CONSULTANT
12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:

August 03rd. 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

J4

DRAWN: James	SHEET No: 9 OF 23
DATE: 08.03.23	
DWG: AD16-18	

DOOR JAMB MULLION CAPACITY					
WINDOW PANEL DIMENSION				DESIGN LOAD	
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF
144	120	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	54.0	54.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	54.0	54.0
			72	52.0	52.0
150	120	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	54.0	54.0
		72	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	52.0	52.0
		78	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	53.0	53.0
			72	50.0	50.0
156	120	60	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	55.0	55.0
		66	42	55.0	55.0
			48	55.0	55.0
			54	55.0	55.0
			60	55.0	55.0
			66	55.0	55.0
			72	53.0	53.0

DOOR JAMB MULLION CAPACITY							
WINDOW PANEL DIMENSION				DESIGN LOAD			
FRAME HEIGHT (IN.)	DOOR HEIGHT (IN.)	DOOR WIDTH (W1) (IN.)	SIDELITE WIDTH (W2) (IN.)	(+) PSF	(-) PSF		
156	120	72	42	55.0	55.0		
			48	55.0	55.0		
			54	55.0	55.0		
			60	55.0	55.0		
			66	53.0	53.0		
			72	51.0	51.0		
		78	42	55.0	55.0		
			48	55.0	55.0		
			54	55.0	55.0		
			60	53.0	53.0		
			66	51.0	51.0		
			72	55.0	55.0		
162	120	60	42	55.0	55.0		
			48	55.0	55.0		
			54	55.0	55.0		
			60	55.0	55.0		
			66	55.0	55.0		
			72	53.0	53.0		
		66	42	55.0	55.0		
			48	55.0	55.0		
			54	55.0	55.0		
			60	55.0	55.0		
			66	54.0	54.0		
			72	51.0	51.0		
		72	42	55.0	55.0		
			48	55.0	55.0		
			54	55.0	55.0		
			60	54.0	54.0		
			66	52.0	52.0		
			72	55.0	55.0		
		168	120	60	42	55.0	55.0
					48	55.0	55.0
					54	55.0	55.0
					60	55.0	55.0
					66	54.0	54.0
					72	52.0	52.0
66	42			55.0	55.0		
	48			55.0	55.0		
	54			55.0	55.0		
	60			55.0	55.0		
	66			52.0	52.0		
	72			50.0	50.0		
72	42	55.0	55.0				
	48	55.0	55.0				
	54	55.0	55.0				
	60	52.0	52.0				
	66	50.0	50.0				
	72	55.0	55.0				
78	42	55.0	55.0				
	48	55.0	55.0				
	54	53.0	53.0				
	60	50.0	50.0				

STEP 3: JAMB/MULLION LOAD CAPACITIES

http://www.trulite.com

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT

Resistor
PRODUCT SERIES

REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:

MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:

YIPING WANG
FLORIDA REGISTRATION
No. 55989
C.A.N. 28677

August 03rd. 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:	
J6	
DRAWN: James	SHEET No: 11 OF 23
DATE: 08.03.23	
DWG: AD16-18	

ANCHOR DESIGN LOAD CAPACITIES						
NOMINAL DIMENSIONS		ANCHOR TYPES				
		B2	B3	C2	C3	D4
MULLION WIDTH	FRAME HEIGHT	3/4" SHIM		1/4" SHIM		5/16" SHIM
(IN.)	(IN.)	DESIGN LOAD (PSF)				
36	78	150.0	150.0	150.0	150.0	150.0
42		137.5	150.0	150.0	150.0	150.0
48		120.3	150.0	140.9	150.0	150.0
54		106.9	147.7	125.3	147.7	147.7
60		96.2	132.9	112.7	132.9	132.9
66		87.5	120.8	102.5	120.8	120.8
72		80.2	110.8	93.9	110.8	110.8
36	84	149.0	150.0	150.0	150.0	150.0
42		127.7	150.0	149.6	150.0	150.0
48		111.7	150.0	130.9	150.0	150.0
54		99.3	137.1	116.3	137.1	137.1
60		89.4	123.4	104.7	123.4	123.4
66		81.2	112.2	95.2	112.2	112.2
72		74.5	102.9	87.2	102.9	102.9
36	90	139.0	150.0	150.0	150.0	150.0
42		119.2	150.0	139.6	150.0	150.0
48		104.3	144.0	122.1	144.0	144.0
54		92.7	128.0	108.6	128.0	128.0
60		83.4	115.2	97.7	115.2	115.2
66		75.8	104.7	88.8	104.7	104.7
72		69.5	96.0	81.4	96.0	96.0
36	96	130.3	150.0	150.0	150.0	150.0
42		111.7	150.0	130.9	150.0	150.0
48		97.8	135.0	114.5	135.0	135.0
54		86.9	120.0	101.8	120.0	120.0
60		78.2	108.0	91.6	108.0	108.0
66		71.1	98.2	83.3	98.2	98.2
72		65.2	90.0	76.3	90.0	90.0
42	102	105.1	145.2	123.2	145.2	145.2
48		92.0	127.1	107.8	127.1	127.1
54		81.8	112.9	95.8	112.9	112.9
60		73.6	101.6	86.2	101.6	101.6
66		66.9	92.4	78.4	92.4	92.4
72		61.3	84.7	71.8	84.7	84.7
36		108	115.9	150.0	135.7	150.0
42	99.3		137.1	116.3	137.1	137.1
48	86.9		120.0	101.8	120.0	120.0
54	77.2		106.7	90.5	106.7	106.7
60	69.5		96.0	81.4	96.0	96.0
66	63.2		87.3	74.4	87.3	87.3
72	57.9		80.0	67.9	80.0	80.0
36	114	109.8	150.0	128.6	150.0	150.0
42		94.1	129.9	110.2	129.9	129.9
48		82.3	113.7	96.4	113.7	113.7
54		73.2	101.1	85.7	101.1	101.1
60		65.9	90.9	77.1	90.9	90.9
66		59.9	82.7	70.1	82.7	82.7
72		54.9	75.8	64.3	75.8	75.8
36	120	104.3	144.0	122.1	144.0	144.0
42		89.4	123.4	104.7	123.4	123.4
48		78.2	108.0	91.6	108.0	108.0
54		69.5	96.0	81.4	96.0	96.0
60		62.6	86.4	73.3	86.4	86.4
66		56.9	78.5	66.6	78.5	78.5
72		52.1	72.0	61.1	72.0	72.0

ANCHOR DESIGN LOAD CAPACITIES						
NOMINAL DIMENSIONS		ANCHOR TYPES				
		B2	B3	C2	C3	D4
MULLION WIDTH	FRAME HEIGHT	3/4" SHIM		1/4" SHIM		5/16" SHIM
(IN.)	(IN.)	DESIGN LOAD (PSF)				
36	126	99.3	137.1	116.3	137.1	137.1
42		85.1	117.6	99.7	117.6	117.6
48		74.5	102.9	87.2	102.9	102.9
54		66.2	91.4	77.5	91.4	91.4
60		59.6	82.3	69.8	82.3	82.3
66		54.2	74.8	63.4	74.8	74.8
72		49.7	68.6	58.2	68.6	68.6
36	132	94.8	130.9	111.0	130.9	130.9
42		81.2	112.2	95.2	112.2	112.2
48		71.1	98.2	83.3	98.2	98.2
54		63.2	87.3	74.0	87.3	87.3
60		56.9	78.5	66.6	78.5	78.5
66		51.7	71.4	60.6	71.4	71.4
36		138	90.7	125.2	106.2	125.2
42	77.7		107.3	91.0	107.3	107.3
48	68.0		93.9	79.7	93.9	93.9
54	60.4		83.5	70.8	83.5	83.5
60	54.4		75.1	63.7	75.1	75.1
66	49.5		68.3	57.9	68.3	68.3
36	144		86.9	120.2	101.8	120.2
42		74.5	102.9	87.2	102.9	102.9
48		65.2	90.0	76.3	90.0	90.0
54		57.9	80.0	67.9	80.0	80.0
60		52.1	72.0	61.1	72.0	72.0
36	150	75.0	75.0	75.0	75.0	75.0
42		71.5	75.0	75.0	75.0	75.0
48		62.6	75.0	73.3	75.0	75.0
54		55.6	75.0	65.1	75.0	75.0
60		50.0	69.1	58.6	69.1	69.1
36	156	75.0	75.0	75.0	75.0	75.0
42		68.7	75.0	75.0	75.0	75.0
48		60.2	75.0	70.5	75.0	75.0
54		53.5	73.8	62.6	73.8	73.8
36	162	75.0	75.0	75.0	75.0	75.0
42		66.2	75.0	75.0	75.0	75.0
48		57.9	75.0	67.9	75.0	75.0
54		51.5	71.1	60.3	71.1	71.1
36	168	74.5	75.0	75.0	75.0	75.0
42		63.8	75.0	74.8	75.0	75.0
48		55.9	75.0	65.4	75.0	75.0
54		49.7	68.6	58.2	68.6	68.6


ANCHOR TYPES:

TYPE "B": 5/16" DIA. ULTRACON (Fu=177 KSI, Fy=155 KSI)
1 3/4" MIN. EMBED INTO fc'=3 KSI MIN. CONCRETE
2 1/2" MIN. EDGE DISTANCE, 4 1/2" MIN. O.C.


TYPE "C": 1/4" DIA. TEKS/SELF-DRILLING SCREW, GRADE 5 (Fu=100 KSI, Fy=65 KSI)
INTO 1/8" THK. MIN. METAL STRUCTURE (6063-T6 MIN.)

TYPE "D": 5/16" TEKS/SELF-DRILLING SCREW, GRADE 5 (Fu=120 KSI, Fy=92 KSI)
INTO 1/8" THK. MIN. METAL STRUCTURE (6063-T6 MIN.)


- B2 - (2) TYPE "B" ANCHORS AT EACH SIDE OF MULLION OR JAMB
B3 - (3) TYPE "B" ANCHORS AT EACH SIDE OF MULLION OR JAMB
C2 - (2) TYPE "C" ANCHORS AT EACH SIDE OF MULLION OR JAMB
C3 - (3) TYPE "C" ANCHORS AT EACH SIDE OF MULLION OR JAMB
D4 - (4) TYPE "D" ANCHORS AT EACH SIDE OF MULLION OR JAMB



B2, C2



B3, C3



D4

ANCHOR THRU FRAME

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



REV N	DATE/REMARKS
REV 2	FBC 2023 UPDATE


ENGINEER:



MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd, 2023

FLORIDA APPROVAL:

FL #25679.2



SHEET TITLE:

A2

DRAWN: James	SHEET No: 13 OF 23
DATE: 08.03.23	
DWG: AD16-18	

ANCHOR DESIGN LOAD CAPACITIES				
NOMINAL DIMENSIONS		ANCHOR TYPES		
MULLION WIDTH	FRAME HEIGHT	B	E	F
(IN.)	(IN.)	DESIGN LOAD (PSF)		
36	78	142.8	150.0	150.0
42		122.4	150.0	150.0
48		107.1	141.7	150.0
54		95.2	125.9	150.0
60		85.7	113.4	144.2
66		77.9	103.0	131.0
72		71.4	94.5	120.2
36	84	132.6	150.0	150.0
42		113.6	150.0	150.0
48		99.4	131.6	150.0
54		88.4	117.0	148.8
60		79.5	105.3	133.9
66		72.3	95.7	121.8
72		66.3	87.7	111.6
36	90	123.7	150.0	150.0
42		106.1	140.3	150.0
48		92.8	122.8	150.0
54		82.5	109.2	138.9
60		74.2	98.2	125.0
66		67.5	89.3	113.6
72		61.9	81.9	104.2
36	96	116.0	150.0	150.0
42		99.4	131.6	150.0
48		87.0	115.1	146.5
54		77.3	102.3	130.2
60		69.6	92.1	117.2
66		63.3	83.7	106.5
72		58.0	76.8	97.7
42	102	93.6	123.8	150.0
48		81.9	108.4	137.9
54		72.8	96.3	122.6
60		65.5	86.7	110.3
66		59.6	78.8	100.3
72		54.6	72.2	91.9
36	108	103.1	136.4	150.0
42		88.4	117.0	148.8
48		77.3	102.3	130.2
54		68.7	91.0	115.8
60		61.9	81.9	104.2
66		56.2	74.4	94.7
72		51.6	68.2	86.8
36	114	97.7	129.3	150.0
42		83.7	110.8	141.0
48		73.3	96.9	123.4
54		65.1	86.2	109.7
60		58.6	77.6	98.7
66		53.3	70.5	89.7
72		48.8	64.6	82.2
36	120	92.8	122.8	150.0
42		79.5	105.3	133.9
48		69.6	92.1	117.2
54		61.6	81.9	104.2
60		55.7	73.7	93.8
66		50.6	67.0	85.2
72		46.4	61.4	78.1

ANCHOR DESIGN LOAD CAPACITIES				
NOMINAL DIMENSIONS		ANCHOR TYPES		
MULLION WIDTH (IN.)	FRAME HEIGHT (IN.)	B	E	F
DESIGN LOAD (PSF)				
36	126	88.4	117.0	148.8
42		75.8	100.2	127.6
48		66.3	87.7	111.6
54		58.9	78.0	99.2
60		53.0	70.2	89.3
66		48.2	63.8	81.2
72	132	44.2	58.5	74.4
36		84.4	111.6	142.1
42		72.3	95.7	121.8
48		63.3	83.7	106.5
54		56.2	74.4	94.7
60		50.6	67.0	85.2
66	138	46.0	60.9	77.5
36		80.7	106.8	135.9
42		69.2	91.5	116.5
48		60.5	80.1	101.9
54		53.8	71.2	90.6
60		48.4	64.1	81.5
66	144	44.0	58.2	74.1
36		77.3	102.3	130.2
42		66.3	87.7	111.6
48		58.0	76.8	97.7
54		51.6	68.2	86.8
60		46.4	61.4	78.1
36	150	74.2	75.0	75.0
42		63.6	75.0	75.0
48		55.7	73.7	75.0
54		49.5	65.5	75.0
60		44.5	58.9	75.0
36	156	71.4	75.0	75.0
42		61.2	75.0	75.0
48		53.5	70.8	75.0
54		47.6	63.0	75.0
36	162	68.7	75.0	75.0
42		58.9	75.0	75.0
48		51.6	68.2	75.0
54		45.8	60.6	75.0
36	168	66.3	75.0	75.0
42		56.8	75.0	75.0
48		49.7	65.8	75.0
54		44.2	58.5	74.4



ANCHOR TYPES (FOR "T" ANCHOR):

TYPE "B": 5/16" DIA. ULTRACON (Fu=177 KSI, Fy=155 KSI)
1 3/4" MIN. EMBED INTO fc'=3 KSI MIN. CONCRETE
3" MIN. EDGE DISTANCE, 6 1/2" MIN. O.C.

TYPE "E": 3/8" DIA. POWERS WEDGE BOLTS (Fu=120 KSI, Fy=92 KSI)
3" MIN. EMBED INTO fc'=3 KSI MIN. CONCRETE
4" MIN. EDGE DISTANCE, 6 1/2" MIN. O.C.

TYPE "F": 5/16" TEKS/SELF-DRILLING SCREW, GRADE 5 (Fu=120 KSI, Fy=92 KSI)
INTO 3/16" MIN THK ALUM. (6063-T6 MIN.) OR
1/8" THK. MIN. STEEL STRUCTURE

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT

Resistor
PRODUCT SERIES


REV#	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:

MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd. 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

A3

DRAWN: James	SHEET No:
DATE: 08.03.23	14 OF 23
DWG: AD16-18	

ANCHOR DESIGN LOAD CAPACITIES					
NOMINAL DIMENSIONS		ANCHOR TYPES			
MULLION WIDTH	FRAME HEIGHT	AA OR A	B	E	C
(IN.)	(IN.)	DESIGN LOAD (PSF)			
36	78	146.9	150.0	150.0	150.0
42		125.9	150.0	150.0	150.0
48		110.2	150.0	150.0	150.0
54		97.9	150.0	150.0	150.0
60		88.1	141.4	137.6	150.0
66		80.1	128.6	125.1	139.9
72	84	73.4	117.8	114.7	128.2
36		136.4	150.0	150.0	150.0
42		116.9	150.0	150.0	150.0
48		102.3	150.0	150.0	150.0
54		90.9	145.9	142.0	150.0
60		81.8	131.3	127.8	142.9
66	90	74.4	119.4	116.2	129.9
72		68.2	109.4	106.5	119.0
36		127.3	150.0	150.0	150.0
42		109.1	150.0	150.0	150.0
48		95.5	150.0	149.1	150.0
54		84.9	136.2	132.5	148.1
60	96	76.4	122.6	119.3	133.3
66		69.4	111.4	108.4	121.2
72		63.6	102.1	99.4	111.1
36		119.3	150.0	150.0	150.0
42		102.3	150.0	150.0	150.0
48		89.5	143.6	139.8	150.0
54	102	79.6	127.7	124.2	138.9
60		71.6	114.9	111.8	125.0
66		65.1	104.5	101.6	113.6
72		59.7	95.8	93.2	104.2
42		96.3	150.0	150.0	150.0
48		84.2	135.2	131.5	147.1
54	108	74.9	120.2	116.9	130.7
60		67.4	108.1	105.2	117.6
66		61.3	98.3	95.7	107.0
72		56.2	90.1	87.7	98.0
36		106.1	150.0	150.0	150.0
42		90.9	145.9	142.0	150.0
48	114	79.6	127.7	124.2	138.9
54		70.7	113.5	110.4	123.5
60		63.6	102.1	99.4	111.1
66		57.9	92.8	90.3	101.0
72		53.0	85.1	82.8	92.6
36		100.5	150.0	150.0	150.0
42	120	86.1	138.2	134.5	150.0
48		75.4	120.9	117.7	131.6
54		67.0	107.5	104.6	117.0
60		60.3	96.8	94.1	105.3
66		54.8	88.0	85.6	95.7
72		50.2	80.6	78.5	87.7
36	126	95.5	150.0	149.1	150.0
42		81.8	131.3	127.8	142.9
48		71.6	114.9	111.8	125.0
54		63.6	102.1	99.4	111.1
60		57.3	91.9	89.4	100.0
66		52.1	83.6	81.3	90.9
72		47.7	76.6	74.5	83.3

ANCHOR DESIGN LOAD CAPACITIES					
NOMINAL DIMENSIONS		ANCHOR TYPES			
MULLION WIDTH	FRAME HEIGHT	AA OR A	B	E	C
(IN.)	(IN.)	DESIGN LOAD (PSF)			
36	126	90.9	145.9	142.0	150.0
42		77.9	125.1	121.7	136.1
48		68.2	109.4	106.5	119.0
54		60.6	97.3	94.6	105.8
60		54.6	87.5	85.2	95.2
66		49.6	79.6	77.4	86.6
72	132	45.5	73.0	71.0	79.4
36		86.8	139.3	135.5	150.0
42		74.4	119.4	116.2	129.9
48		65.1	104.5	101.6	113.6
54		57.9	92.8	90.3	101.0
60		52.1	83.6	81.3	90.9
66	138	47.3	76.0	73.9	82.6
36		83.0	133.2	129.6	144.9
42		71.2	114.2	111.1	124.2
48		62.3	99.9	97.2	108.7
54		55.3	88.8	86.4	96.6
60		49.8	79.9	77.8	87.0
66	144	45.3	72.7	70.7	79.1
36		79.6	127.7	124.2	138.9
42		68.2	109.4	106.5	119.0
48		59.7	95.8	93.2	104.2
54		53.0	85.1	82.8	92.6
60		47.7	76.6	74.5	83.3
36	150	75.0	75.0	75.0	75.0
42		65.5	75.0	75.0	75.0
48		57.3	75.0	75.0	75.0
54		50.9	75.0	75.0	75.0
60		45.8	73.5	71.6	75.0
36	156	73.4	75.0	75.0	75.0
42		62.9	75.0	75.0	75.0
48		55.1	75.0	75.0	75.0
54		49.0	75.0	75.0	75.0
36	162	70.7	75.0	75.0	75.0
42		60.6	75.0	75.0	75.0
48		53.0	75.0	75.0	75.0
54		47.1	75.0	73.6	75.0
36	168	68.2	75.0	75.0	75.0
42		58.4	75.0	75.0	75.0
48		51.1	75.0	75.0	75.0
54		45.5	73.0	71.0	75.0


ANCHOR TYPES:
TYPE "AA": 1/4" DIA. ULTRACON+ (Fu=164 KSI, Fy=148 KSI)
T 1/2" MIN. EMBED INTO WOOD (SG=0.55 MIN.)
OR THRU 1X OR 2X WOOD BUCK INTO CONCRETE
W/ 1 3/4" MIN. EMBED INTO CONC.

TYPE "A": 1/4" DIA. ULTRACON+ (Fu=164 KSI, Fy=148 KSI)
T 3/4" MIN. EMBED INTO fc'=3 KSI MIN. CONCRETE
2 1/2" MIN. EDGE DISTANCE

TYPE "B": 5/16" DIA. ULTRACON (Fu=177 KSI, Fy=155 KSI)
T 3/4" MIN. EMBED INTO fc'=3 KSI MIN. CONCRETE
3" MIN. EDGE DISTANCE

TYPE "C": 1/4" DIA. TEKS/SELF-DRILLING SCREW, GRADE 5 (Fu=100 KSI, Fy=65 KSI)
INTO 1/8" THK. MIN. METAL STRUCTURE (GOG3-T6 MIN.)

TYPE "E": 3/8" DIA. POWERS WEDGE BOLTS (Fu=120 KSI, Fy=92 KSI)
3" MIN. EMBED INTO fc'=3 KSI MIN. CONCRETE
3" MIN. EDGE DISTANCE, 6 1/2" MIN. O.C.




GLASS & ALUMINUM SOLUTIONS™
http://www.trulite.com
403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:
Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



REV#	DATE/REMARKS
REV 2	FBC 2023 UPDATE


ENGINEER:
MCY ENGINEERING, INC.
GLAZING CONSULTANT
12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com



August 03rd. 2023
FLORIDA APPROVAL:
FL #25679.2

SHEET TITLE:
A4

DRAWN: James	SHEET No:
DATE: 08.03.23	15 OF 23
DWG: AD16-18	



PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT

Resistor
PRODUCT SERIES

REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:



MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd. 2023


FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

D1A


DRAWN: James	SHEET No: 17 OF 23
DATE: 08.03.23	
DWG: AD16-18	



D DETAIL
D2

E DETAIL
D2


F DETAIL
D2



MAX. FRAME WIDTH	MAX. GAP AT EACH SIDE
30 FT.	1-1/8"
≥ 60 FT.	1-1/8"

MAX. FRAME HEIGHT	GAP	
	MIN.	MAX.
96"	5/16"	1-1/8"
108"	5/16"	1-1/8"
120"	3/8"	1-1/8"
132"	3/8"	1-1/8"
144"	3/8"	1-1/8"
156"	1/2"	1-1/8"
168"	1/2"	1-1/8"

NOTE:
MULLIONS SHOWN IN DASHED LINES ARE NOT PART OF THIS APPROVAL.



G DETAIL
D2

GLASS & ALUMINUM SOLUTIONS™

<http://www.trulite.com>

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT

Resistor
PRODUCT SERIES

REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:

MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:

YIPING WANG
FLORIDA REGISTRATION
No. 55983
C.A.N. 28677
STATE OF FLORIDA
PROFESSIONAL ENGINEER

August 03rd. 2023



FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

D2

DRAWN: James	SHEET No:
DATE: 08.03.23	18 OF 23
DWG: AD16-18	



GLASS & ALUMINUM SOLUTIONS™

<http://www.trulite.com>

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT

Resistor
PRODUCT SERIES

REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:

MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:

YIPING WANG
FLORIDA REGISTRATION
No. 55983
C.A.N. 28677

August 03rd. 2023


FLORIDA APPROVAL:

FL #25679.2


SHEET TITLE:

D3


DRAWN: James	SHEET No:
DATE: 08.03.23	19 OF 23
DWG: AD16-18	



MULLION ANCHOR ("T" ANCHOR)
TOP VIEW



MULLION ANCHOR ("T" ANCHOR)
FRONT VIEW




MULLION ANCHOR ("T" ANCHOR)
3D VIEW


1
D4
DETAIL

SEE CHART ON
SHEET A4 FOR 2
ANCHOR OPTION


3/8" DIA. POWERS WEDGE
BOLTS 3" MIN. EMBED INTO
f_c'=3 KSI MIN. CONCRETE
4 1/2" MIN. EDGE
DISTANCE, 3" MIN. O.C.



DOOR JAMB ANCHOR ("T" ANCHOR)
TOP VIEW




MULLION ANCHOR ("T" ANCHOR)
FRONT VIEW




DOOR JAMB ANCHOR ("T" ANCHOR)
3D VIEW


2
D4
DETAIL



JAMB ANCHOR ("F" ANCHOR)
TOP VIEW



JAMB ANCHOR ("F" ANCHOR)
FRONT VIEW



JAMB ANCHOR ("F" ANCHOR)
3D VIEW

3
D4
DETAIL

Trulite
GLASS & ALUMINUM SOLUTIONS™

<http://www.trulite.com>

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT

Resistor
PRODUCT SERIES


REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:

MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd, 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

D4


DRAWN: James

DATE: 08.03.23

DWG: AD16-18

SHEET No:

20 OF 23



PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT

Resistor
PRODUCT SERIES

REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:



MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd, 2023




FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

PARTS

DRAWN: James	SHEET No:
DATE: 08.03.23	21 OF 23
DWG: AD16-18	



<http://www.trulite.com>

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE

ENGINEER:



MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd. 2023

FLORIDA APPROVAL:


FL #25679.2

SHEET TITLE:

PARTS

DRAWN: James	SHEET No:
DATE: 08.03.23	22 OF 23
DWG: AD16-18	

BILL OF MATERIALS				
ITEM	PART	DESCRIPTION	MATERIAL	REMARKS
1	82501	VERTICAL MULLION/JAMB	6063-T6	BONNELL
2	82508	OPEN BACK HEAD/SILL	6063-T6	BONNELL
3	82503	HEAD/SILL HORIZONTAL MULLION	6063-T6	BONNELL
4	82504	OPEN BACK JAMB	6063-T6	BONNELL
5	82505	FLAT FILLER	6063-T6	BONNELL
6	81009	9/16 GLAZING ADAPTER	6063-T6	BONNELL
7	81530	SHEAR CLIP	6063-T6	BONNELL
8	82001	PERIMETER PRESSURE BAR	6063-T6	BONNELL
9	81002	PRESSURE BAR	6063-T6	BONNELL
10	81005	SNAP COVER	6063-T6	BONNELL
11	81531	SHEAR CLIP FOR DOOR TRANSOM	6063-T6	BONNELL
12	81520	SPLICE SLEEVE/REINFORCEMENT	6063-T6	BONNELL
13	82590	JAMB ANCHOR ("F" ANCHOR)	6063-T6	BONNELL
14	82591	INTERMEDIATE MULLION ANCHOR ("T" ANCHOR)	6063-T6	BONNELL
15	05412	GLAZING GASKET	EPDM DURO 70 ±5	TREMCO/GRP
16	05414	PRESSURE GASKET	EPDM DURO 70 ±5	TREMCO/GRP
17	05413	GLAZING GASKET FOR DRY GLAZED	EPDM DURO 70 ±5	TREMCO/GRP
18A	H62D	SETTING BLOCK, 0.50" X 0.25" X 4"	EPDM DURO 85 ±5	TREMCO/GRP
19	23020	#14-16 X 7/8" HWH-AB MS	STEEL-ZINC COATED	VARIES
20	23021	#12-24 X 2" PPH-23 MS	STEEL-ZINC COATED	VARIES
21	23022	1/4-20 X 3/4" PPH-23 MS	STEEL-ZINC COATED	VARIES
22	23261	1/4-20 X 5/8" HWH	STEEL-ZINC COATED	VARIES
23	ST824	1 PC CHANNEL STEEL REINFORCEMENT 2" X 4 1/4" X 1/4"	A36 STEEL	VARIES
24	ST822	2 PCS CHANNEL STEEL REINFORCEMENT 1 1/2" X 4 1/4" X 1/4"	A36 STEEL	VARIES
25	ST821	2 PCS CHANNEL STEEL REINFORCEMENT 1 1/2" X 4 1/4" X 1/4" WITH 1" X 3" STEEL BAR	A36 STEEL	VARIES
27	V2108	GLAZING TAPE 0.375" X 0.25"	FOAM	ST. GOBAIN
27A	VK1826	GLAZING TAPE	FOAM	CAPITAL TAPE
28	DOWSIL790	SILICONE-PERIMETER SEALANT	SILICONE	DOW CORNING
29	-	DOWSIL -995	SILICONE	DOW CORNING
30	-	PROGLAZE SSG	SILICONE	TREMCO
31	-	SG-10	SILICONE	SIKASIL



8200 CURTAINWALL SYSTEM



GLASS & ALUMINUM SOLUTIONS™

<http://www.trulite.com>

403 WESTPARK COURT, SUITE 201
PEACHTREE CITY, GA 30269
p. 800-432-8132 | f. 954-724-2083

PRODUCT:

Series
8200 ALUMINUM
CURTAIN WALL
SMALL-MISSILE IMPACT



PRODUCT SERIES

REVN	DATE/REMARKS
REV 2	FBC 2023 UPDATE


ENGINEER:



MCY ENGINEERING, INC.
GLAZING CONSULTANT

12781 MIRAMAR PWY. STE. 301
MIRAMAR, FL. 33027
P: (305) 271-0117
Email: MCY@mcyengineering.com
www.MCYEngineering.com

STAMP:



August 03rd, 2023

FLORIDA APPROVAL:

FL #25679.2

SHEET TITLE:

BOM

DRAWN: James	SHEET No:
DATE: 08.03.23	23 OF 23
DWG: AD16-18	