


─ 1' MIN TYP 1 1/4" MIN TYP SCREW DEPTH 1/2" MAX HEAD JAMB





JAMB SCREW INSTALLATION




JAMB SCREW INSTALLATION METHOD:
- UNIT MUST NOT BE IN DIRECT CONTACT WITH EITHER CONCRETE
OR TREATED BUCK MATERIAL. IF SHIM SPACE IS LESS THAN
1/8' WRAPPING THE UNIT ON ALL 4 SIDES WITH WINDOW
FLASHING TAPE IS REQUIRED AS A BARRIER BETWEEN THE UNIT AND CONCRETE OR TREATED LUMBER.

- MINIMUM OF 2 PER SIDE.

- SECURE JAMBS AND HEAD JAMBS WITH #8 X 3"SCREWS.

- SECURE THE SILL WITH #8 X 3½" SCREWS. - SHIM AT EACH SCREW LOCATION.

UNIT	MAX FRAME SIZE	DP RATING	GLASS OPTION
UL WD CSMNT P RT IZ3	36 X 83 1/8	+65/-65	TYPE A
UL WD CSMNT P RT IZ3	72 % x 77 ½6	+65/-65	TYPE B



	TYPE	LAMINATED GLASS MAKE UP
ľ	Α	2.7mm(.11") ANN+ .090KURARAY PVB+ 2.7mm(.11") ANN
Ī	В	3. 9mm(.15") ANN+ .090KURARAY SGP+ 3.9mm(.15") ANN

NOTES: 1. THIS PRINT IS FOR STRUCTURAL PERFORMANCE ONLY. FOR FLASHING & \triangle SEALING INSTRUCTIONS, REFER TO THE INSTALLATION INSTRUCTIONS.

SEAUNG INSTRUCTIONS, REPER TO THE INGLESSION.

SHIMS

-PLACE A SHIM WITHIN 4-6 INCHES OF EACH CORNER AND SPACE ALL

OTHERS EVENLY A MAXIMUM OF 15" APART.

3. IF CHEMICALLY TREATED LUMBER IS USED FOR BUCK MATERIAL, FASTENERS

THE SHIP MIST RE A MINIMUM OF 0.90 0Z/FT^2 ZINC HOT DIPPED INTO THE BUCK MUST BE A MINIMUM OF 0.90 OZ/FT 2 ZINC HOT DIPPED GALVANIZED OR STAINLESS STEEL TYPE 304 OR 316.

	MAR	VIN.	RE
UNSPECIFIED TOLERANCES	PRODUCT	ULTIMATE CASE	MENT

RESEARCH & DEVELOPMENT

			AA = .03	l± .5	UNII IYPE:	UWCAPK	1123		
			XXX± .012						
			LINEAL:	FAB LINEAL:					
4		WOOD BUCK BY OTHERS	+ N/A		DWG TYPE:	INSTALL	ΔΤΙΩΝ		
3		#8 X 3.500 WOOD SCREW	- N/A		DESCRIPTION:				
2		NIHS	MATERIAL:					DWG NO: 00070225	
1		#8 X 3.000 WOOD SCREW		N/A		В	MISC	00070225	
I TEM	REF NO	DESCRIPTION		IN/A	APP:	SCALE: NA	DATE: 06/20/10	DWG BY: BORNEMAN, SKIP	SHEET: 1 OF 1

DECIMALS:

ANGLE DEG: CATEGORY:

NOTICE - CONFIDENTIAL INFORMATION

The information in this document is privileged and strictly confidential. The information contained herein shall be used only by Marvin Windows and Doors employees and by those agents or suppliers granted official written permission. If the reader of this document is not the intended recipient, or the employee or agent of the intended recipient, please delete this document from all data storage devices, and destroy all hard copies. Any unauthorized dissemination, distribution, copying or other use of the information contained in this document is strictly prohibited.