

1239 Jabara Ave. North Port, FL 34288 Ph. 941-380-1574 FBPE C.O.A. #29779

## **Evaluation Report IN0546-R2**

March 7, 2016

**Product Description:** Horizontal Slider Series 42-19, XOX 1/3-1/3-1/3 configuration

Manufacturer: Simonton Windows, 1 Cochrane Ave., Pennsboro, WV

**Statement of Compliance:** This report evaluates the above-listed product per the requirements of FAC Product Approval Rule 61G20-3.005 (4). This product complies with the requirements of the Florida Building Code outside the High Velocity Hurricane Zone. The product testing standards performed are outlined below.

## **Technical Documentation:**

- 1) This report, prepared by Lucas A. Turner, P.E., at 1239 Jabara Ave., North Port, FL
- 2) Installation drawing IN0546-R2, signed and sealed by Lucas A. Turner, P.E.
- **3)** Test Reports A6986.01-501-47-r0, B7718.01-501-47-r0, B7880.01-501-47-r1, and E0147.01-109-47-r0, from Architectural Testing, Inc., Springdale and York, PA, with testing performed: AAMA/WDMA/CSA 101/I.S.2/A440-05/08, ASTM E1886-05, and ASTM E1996-09/12
- 4) Supplemental Calculations to support IN0546-R2, signed and sealed by Lucas A. Turner, P.E.
- 5) Test Report ETC-97-264-4091.0, from ETC Laboratories, Rochester, NY, signed and sealed by J. L. Doldan, P.E., report used for PVC extrusion Dade master file #12-1037
  - Testing Performed: ASTM D1929-96 Ignition Temperature, ASTM D2843-93 Smoke Density, ASTM D635-96 Rate of Burning, ASTM G26-95 UV Exposure for 4500 hours, ASTM D638-96
- 6) Statement of equivalency of tested flame, smoke, UV, and tensile standards, with those required per FBC 2010 and Dade Plastics checklist #0445, signed and sealed by Lucas A. Turner, P.E.

**Installation:** Units must be installed according to installation drawing IN0546-R2.

## **Limitations of Use:** This product:

- May be used in the configuration, DP, product size, and with glazing as indicated in IN0546-R2
- Is large missile impact resistant (missile level C, wind zone 2) and does not require the use of shutters in windborne debris regions complying with missile level C, Wind Zone 2.
- May not be used in the High Velocity Hurricane Zone
- Requires white SimEx, Inc. PVC extrusions with current listing as an AAMA Certified Profile Licensee under AAMA 303

**Certification of Independence:** I do not have, nor do I intend to acquire, nor will I acquire, a financial interest in Simonton Windows or in any company manufacturing or distributing products for which this report is being issued. I do not have, nor do I intend to acquire, nor will I acquire, a financial interest in any other entity involved in the testing or approval process of this product.



ZZ 3/7/2016 Lucas A. Turner, P.E. FL PE #58201

Lucas A. Turner 2016-03-07 22:35-05:00