

BUILDING DROPS

A Perfect Solution in Every Drop! Certificate of Authorization: 29578 398 E. Dania Beach Blvd. Suite 338 Dania Beach, FL 33004 954.399.8478 PH 954.744.4738 FX contact@buildingdrops.com

Product Evaluation Report

of

JELD-WEN, inc. Design Pro / Smooth Pro Opaque (Non-Impact)

for

Florida Product Approval

Report No. 2749.2

Current Florida Building Code

Method: Category: Sub – Category: 1 – A (Certification Method) Exterior Door Assemblies Swinging Exterior Door Assemblies

Product: Material: Product Dimensions:

Design Pro/ Smooth Pro Fiberglass 12'-0" W x 6'-8" H (Nominal) 12'-0" W x 8'-0" H (Nominal)


Prepared for:

JELD-WEN, inc 3737 Lakeport Blvd. Klamath Falls, OR. 97601

Prepared by:

Hermes F. Norero, P.E. Florida Professional Engineer # 73778 Date: 11/17/2020

Contents: Evaluation Report Pages 1 – 4



Hermes F. Norero, P.E. Florida No. 73778



| Manufacturer: Product Category: Product Sub-Category: Compliance Method: Product Name: | | JELD-WEN, inc. | | | |
|--|-----------------|---|---|--|--|
| | | Exterior Door Swinging Exterior Door Assemblies | | | |
| | | | | State Product Approval Method (1)(a) Design Pro / Smooth Pro Opaque Non-Impact. 12'-0" W x 6'-8" H (Nominal) 12'-0" W x 8'-0" H (Nominal) | |
| | | Scope: | This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for JELD-WEN, inc. based on <u>Method 1a</u> of the State of Florida Product Approval, Department of Business and Professional Regulation - Florida Building Commission. | | |
| | | | | ero, P.E. does not have nor will acquire financial interest in the company manufacturing the product or in any other entity involved in the approval process of the product | |
| | This product h | nas been evaluated for use in locations adhering to the current Florida Building Code. | | | |
| | See Installatio | n Instructions provided by manufacturer for specific use parameters. | | | |
| Limits of Use: | | | | | |
| | • | roduct has been evaluated and is in compliance with the current Florida Building Code, <u>Jing</u> the "High Velocity Hurricane Zone" (HVHZ). | | | |
| | 2. Produ | ict anchors shall be as listed and spaced as shown on details. Anchor embedment into rate material shall be beyond wall dressing or stucco. | | | |
| | | used in areas requiring wind borne debris protection this product complies with er 16 of the current Florida Building Code and <u>does</u> require an impact resistant | | | |
| | 4. Site co | onditions that deviate from the details of manufacturer require further engineering sis by a licensed engineer or registered architect. | | | |

5. See Installation Instructions for size and design pressure limitations.

Hermes F Norero, P.E. Florida No.73778 Page **2** of **4**



Certification Agency: The manufacturer has demonstrated compliance of door products in accordance with the current Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity through **National Accreditation and Management Institute** (FBC Organization #: CER1773)

Performance Standards: The product described herein has been tested per:

- ASTM E283-04
- ASTM E330-02
- AAMA 1304-02
 - TAS 202-94

Referenced Data:

| 1. | Product Testing performed by (FBC Organization # TST1589 | Product Testing performed by National Certified Testing Laboratories FBC Organization # TST1589) | | |
|----|---|--|--|--|
| | Report # | Report Date: | | |
| | NCTL-210-3918-01 | 10/04/13 | | |
| | SJW2013-195 | 09/16/13 | | |
| | NCTL-210-3924-02 | 12/18/13 | | |
| | SJW2013-241 | 12/03/13 | | |
| | SJW2013-242 | 12/03/13 | | |
| | SJW2013-208-TAS | 11/13/13 | | |
| | SJW2013-209-TAS | 11/13/13 | | |
| | SJW2013-251 | 12/23/13 | | |
| | SJW2013-252 | 12/23/13 | | |
| | SJW2013-253 | 12/23/13 | | |
| | NCTL-210-3925-03 | 02/07/14 | | |
| | NCTL-210-3918-02 | 10/12/13 | | |
| | SJW2014-032 | 04/22/14 | | |
| | NCTL-210-3930-01 | 02/24/14 | | |
| | NCTL-210-3930-02 | 03/10/14 | | |
| | SJW2014-069 | 07/07/14 | | |
| | SJW2014-079 | 07/07/14 | | |
| 2. | Product Testing performed by Quality Testing Inc. | | | |

- Product Testing performed by Quality Testing Inc. (FBC Organization # TST7638)
 Report # Report Date: SJW2010-003 01/11/10
- Quality Assurance Entity
 National Accreditation & Management Institute (FBC Organization #QUA1789)



| | 4. | Component Material Testing of Dylite Expandable Polystyrene by Intertek Testing Services NA, Inc. <u>ASTM E84</u> Demort# 2112726647, 001 P1 - Demort Date: 02(12(00) |
|------------------|---|--|
| | | Report#: 3113726SAT-001 R1 Report Date: 03/13/09 |
| | 5. | Component Material Testing of Fiberglass SMC Skin |
| | | Element Materials Technology |
| | | <u>ASTM D635, ASTM D638, ASTM D1929, ASTM D2843, ASTM G155</u> |
| | | Report#: ESP010982P Report Date: 02/26/13 |
| Installation: | Refer to Installation Instructions (D015693) for anchor spacing and more details of the installation requirements. | |
| Design Pressure: | Refer to drawi | ng (D015693) for pressure information. |

Hermes F Norero, P.E. Florida No.73778 Page **4** of **4**