

## XEWR2.E313268 Thermal-device-protected Motors - Component

Page Bottom

## Thermal-device-protected Motors - Component

See General Information for Thermal-device-protected Motors - Component

USA SHUTTER CO, DBA MAESTROSHIELD L L C

1450 RAIL HEAD BLVD NAPLES, FL 34110 USA E313268

Motors, Model TMUS35S followed by 06/36 or13/15, 1.66 amp, 120 V; Class A insulated; Model TMUS35S followed by 06/17, 06/33 or 03/33, 0.97 amp, 120 V; Class A insulated; Model TMUS45 followed by S-20/13 or M-50/13, 2.20 amp, 120 V, Class A insulated; Model TMUS45 followed by S-20/19 or M-20/19, 2.3 amp, 120 V, Class A insulated; Model TMUS45 followed by S-10/32, S-30/13, M-30/13, S-50/04, M-50/04, 2.42 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A insulated; Model TMUS45 followed by S-40/19 or M-40/19, 3.05 amp, 120 V, Class A by S-40/13 or M-40/13, 1.92 amp, 120 V, Class A insulated; Model TMUS59 followed by S-60/14 or M-60/14, 2.41 amp, 120 V; Class A insulated; Model TMUS59 followed by S-80/19 or M-80/19, 4.26 amp, 120 V, Class A insulated; Model TMUS59 followed by S-80/14, M-80/14, S-100/11, M-100/14, 2.94 amp, 120 V, Class A insulated.



Marking: Company name or "E313268" or trademark

Last Updated on 2009-06-24

and model designation.

Questions?

Notice of Disclaimer

Page Top

Copyright © 2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

