

398 East Dania Beach Blvd. Suite 338 Dania Beach, FL 33004 954.399.8478 PH 954.744.4738 FX contact@buildingdrops.com

Product Evaluation Report

of

JELD-WEN, inc. **Contours Steel Door, Wood Edge** 6'-8" Outswing Impact Glazed Single or Double Door Unit

for

Florida Product Approval

Report No. 6785

Current Florida Building Code

Method: 1 - A (Certification)

Category: **Exterior Doors**

Swinging Exterior Door Assemblies Sub - Category:

> **Product: Contours Steel Door, Wood Edge**

Material: Wood/24 Ga. Steel

74" x 80.75" **Product Dimensions:**

Prepared for:

JELD-WEN, inc. 3737 Lakeport Blvd. Klamath Falls, OR. 97601


Prepared by:

Hermes Norero, P.E.

Florida Professional Engineer # 73778 Date: 04/13/2020

Contents:

Evaluation Report Pages 1-3



Florida No. 73778

Date: 04/13/2020 Report No: 6785

Manufacturer: JELD-WEN, inc.

Product Category: Exterior Doors

Product Sub-Category: Swinging Exterior Door Assemblies

Compliance Method: State Product Approval Method (1)(a)

Product Name: Contours Steel Door, Wood Edge

(Impact) 74" x 80.75"

Scope:

This is a Product Evaluation Report issued by Hermes Norero, P.E. (FL # 73778) for **JELD-WEN inc.** based on <u>Method 1a</u> of the State of Florida Product Approval, Florida Department of Business and Professional Regulation - Florida Building Commission.

Hermes Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building Code.

See Installation Instructions **JW0509-03**, signed and sealed by Hermes Norero, P.E. (FL # 73778) for specific use parameters.

Limits of Use:

- 1. This product has been evaluated and is in compliance with the current Florida Building Code, including the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and <u>does not</u> require an impact resistant covering.
- 4. Site conditions that deviate from the details of drawing **JW0509-03** require further engineering analysis by a licensed engineer or registered architect.
- 5. See Installation Instructions **JW0509-03** for size and design pressure limitations.

Date: 04/13/2020 Report No: 6785

Certification Agency:

The manufacturer has demonstrated compliance of products in accordance with the Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity through **National Accreditation & Management Institute, Inc.** (FBC Organization # CER1773).

Performance Standards:

The product described herein has been evaluated per:

- TAS 201-94
- TAS 202-94
- TAS 203-94

Referenced Data:

1. Product Testing performed by National Certified Testing Laboratory, Inc.

(FBC Organization # TST1589)

Report #: NCTL-210-3195-1, Report Date: 01/08/2013

TAS Report Engineer of Record: Gerard J. Ferrara, FL P.E. No. 11985

Report #: SJW2011-070, Report Date: 06/03/2011 TAS Report Engineer of Record: Kevin P. Tyra, FL P.E. No. 72805

2. Certification Agency

National Accreditation & Management Institute, Inc.

(FBC Organization # CER1773)

3. Material Certification

Miami-Dade RER – Product Control Section NOAEastman Chemical Co. – Saflex HP Interlayer

4. Component Material Testing of Dylite Expandable Polystyrene by

Intertek Testing Services NA, Inc.

ASTM E84

Report#: 3113726SAT-001 R1 Report Date: 03/13/2009

Installation:

Refer to Installation Instructions (JW0509-03) for anchor spacing and more details of the installation requirements.

Design Pressure:

Refer to Installation Instructions (**JW0509-03**) for design pressures based on size, configuration, and glass types.