

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Product Evaluation Report

of

Plyco Corporation Series 20EV Flush Steel Outswing Door (Non-HVHZ) (Non-Impact)

for

Florida Product Approval

FL# FL15336

Report No. 8805

Current Florida Building Code

Method:	1 – A (Certification)
Category:	Exterior Doors
Sub – Category:	Swinging Exterior Door Assemblies

Product:Series 20EV Flush Steel Outswing DoorMaterials:Aluminum 6063-T5 & CS-B SteelProduct Dimensions:See Installation Instructions, PCO008


Prepared for:

Plyco Corporation P.O. Box 386 500 Industrial Lake Road Elkhart Lake, WI 53020

Prepared by:

Hermes F. Norero, P.E. Florida Professional Engineer # 73778 Date: 9/7/2023

Contents: Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



 FL#:
 FL15336

 Report #:
 8805

 Date:
 9/7/2023

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Manufacturer:		Plyco Corporation
Product Catego	ory:	Exterior Doors
Product Sub-Ca	itegory:	Swinging Exterior Door Assemblies
Compliance Me	ethod:	State Product Approval Method (1)(a)
Product Name:		Series 20EV Flush Steel Outswing Door (Non-HVHZ) (Non-Impact)
Scope:	This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for Plyco Corporation based on <u>Method 1a</u> of the State of Florida Product Approval, Department of Business and Professional Regulation - Florida Building Commission.	
	manufacturing	ero, P.E. does not have nor will acquire financial interest in the company or distributing the product or in any other entity involved in the approval product named herein.
	This product ha Code.	as been evaluated for use in locations adhering to the current Florida Building
		n Instructions PCO008 , signed and sealed by Hermes F. Norero, P.E. (FL # cific use parameters.
Limits of Use:		
		oduct has been evaluated and is in compliance with the current Florida
	2. Produc	g Code, <u>excluding</u> the "High Velocity Hurricane Zone" (HVHZ). It anchors shall be as listed and spaced as shown on details. Anchor ment into substrate material shall be beyond wall dressing or stucco.
	3. When with Ch	used in areas requiring wind borne debris protection this product complies napter 16 of the current Florida Building Code and <u>does require</u> an impact nt covering.
	4. Site co	nditions that deviate from the details of drawing PCO008 require further ering analysis by a licensed engineer or registered architect.
	-	tallation Instructions PCO008 for size and design pressure limitations.

BUILDINGDROPS.COM

954.399.8478

٢

P

954.744.4738

CONTACT@BUILDINGDROPS.COM



398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Certification Agency:The manufacturer has demonstrated compliance of products in A with the Florida Building Code and State Rules for manufacturing quality assurance program audited by an approved quality assura through National Accreditation & Management Institute, Inc. (FBC Organization #: CER1773)

Performance Standards: The product described herein has been evaluated per:

• ASTM E330-14

Referenced Data:

- Product Testing performed by Element Wausau (FBC Organization # TST2613) Report #: ESP031518P-2458.8, Report Date: 10/30/19
- Certification Agency
 National Accreditation & Management Institute (FBC Organization # CER1773)

Installation:

Refer to Installation Instructions (**PCO008**) for anchor types, spacing, and more details of the installation requirements.

Design Pressure:

Refer to Installation Instructions (PCO008) for design pressure configurations.

