

## R W Building Consultants, Inc.

Consulting and Engineering Services for the Building Industry
P.O. Box 230 Valrico, FL 33595 Phone 813.659.9197

Florida Board of Professional Engineers Registry License No. 9813

Product	Evaluation R	eport	Report No.: FL-16216.1  Date: October 16, 2023
Product Category	Sub Category	Manufacturer	Product Name
Exterior Doors	Sliding Exterior Door Assemblies	Wincore Window Company, LLC. 250 Staunton Turnpike Parkersburg, WV 26104	8800 Series Vinyl Sliding Patio Door "Impact"

Scope:

This is a Product Evaluation report issued by R W Building Consultants, Inc. and Lyndon F. Schmidt, P.E. (System ID # 1998) for Wincore Window Company, LLC. based on Rule Chapter No. 61G20-3, Method 1D of the State of Florida Product Approval, Department of Business & Professional Regulation.

RW Building Consultants and Lyndon F. Schmidt, P.E. do not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

## Limitations:

- 1. This product has been evaluated and is in compliance with the 8th Edition (2023) Florida Building Code (FBC) structural requirements excluding the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment to base material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with FBC Sections 1609.1.2 & R301.2.1.2 and does not require an impact resistant covering. This product meets missile level "D" and includes Wind Zone 4 as defined in ASTM E1996 and FBC Sections 1609.1.2.2 & R301.2.1.2.1.
- 4. For 2x stud framing construction, anchoring of these units shall be the same as that shown for 2x buck masonry construction.
- 5. Site conditions that deviate from the details of drawing FL-16216.1 require further engineering analysis by a licensed engineer or registered architect.
- 6. See drawing FL-16216.1 for size and design pressure limitations.

**Test Standard** 

## Supporting Documents:

1. Test Report No.

	TEL 02800583	AAMA/WDMA/101/I.S.2/A440-08	Testing Evaluation Lab., Inc.	V. K. Wright
	TEL 02800584	ASTM E 1886-05 / E 1996-09	Testing Evaluation Lab.,Inc.	V. K. Wright
	NCTL 110-15906-1	AAMA/WDMA/101/I.S.2/A440-08	NCTL	Justin Bupp
	NCTL 110-15495-1	ASTM E 1886-05 / E 1996-05	NCTL	Robert H. Zeiders
2.	Miami-Dade NOA	Materials Testing		
	23-0717.30	SentryGlas® Interlayer (Kuraray America., Inc.)	)	
	23-0713.18	Saflex® PVB Interlayer (Eastman Chemical Con	mpany)	
3.	Drawing No.	Prepared by		Signed & Sealed by
	No. FL-16216.1	RW Building Consultants, Inc. (#9813)		Lyndon F. Schmidt, P.E.
4.	Calculations	Prepared by		Signed & Sealed by

ASTM E1300 Glass Load 5. Quality Assurance

Anchoring

Certificate of Participation issued by National Accreditation and Management Institute, certifying that Wincore Window Company, LLC. is manufacturing products within a quality assurance program that complies with ISO/IEC 17020 and Guide 53.

RW Building Consultants, Inc. (#9813)

RW Building Consultants, Inc. (#9813)

LYNDON F. SCHMIDT, State of Florida, Professional Engineer, License No. 43409 This item has been digitally signed and sealed by L. F. Schmidt on 10-18-23. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

**Testing Laboratory** 

Signed by

Lyndon F. Schmidt, P.E.

THIS PRODUCT APPROVAL IS VALID ONLY FOR THE STATE OF FLORIDA