

BUILDING DROPS

A Perfect Solution in Every Drop! Certificate of Authorization: 29578 398 E. Dania Beach Blvd. Suite 338 Dania Beach, FL 33004 954.399.8478 PH 954.744.4738 FX contact@buildingdrops.com

Product Evaluation Report

of

JELD-WEN, inc. Design Pro / Smooth Pro / Studio Fiberglass Opaque (Non-Impact) (HVHZ)

for

Florida Product Approval

Report No. 4657.3

Current Florida Building Code

Method: Category: Sub – Category: 1 – D (Engineering Method) Exterior Door Assemblies Swinging Exterior Door Assemblies

Product: Material: Product Dimensions: Design Pro/ Smooth Pro/ Studio Fiberglass 9'-0" W x 6'-8" H (Nominal) 9'-0" W x 8'-0" H (Nominal)

Prepared for:

JELD-WEN, inc 3737 Lakeport Blvd. Klamath Falls, OR. 97601

Prepared by: Hermes F. Norero, P.E. Florida Professional Engineer # 73778 Date: 09/13/2019

Contents: Evaluation Report Pages 1 – 4





Manufacturer: Product Category: Product Sub-Category: Compliance Method: Product Name:		JELD-WEN, inc. Exterior Door Swinging Exterior Door Assemblies State Product Approval Method (1)(d) Design Pro / Smooth Pro / Studio Opaque (Non-Impact) (HVHZ). 9'-0" X 6'-8" (Nominal) 9'-0" X 8'-0" (Nominal)				
						duct Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for JELD-WEN, inc. <u>ethod 1a</u> of the State of Florida Product Approval, Department of Business and Regulation - Florida Building Commission.
						prero, P.E. does not have nor will acquire financial interest in the company manufacturing ng the product or in any other entity involved in the approval process of the product in.
					This product	t has been evaluated for use in locations adhering to the current Florida Building Code.
					See Installat	ion Instructions provided by manufacturer for specific use parameters.
Limits of Use:						
		product has been evaluated and is in compliance with the current Florida Building Code, uding the "High Velocity Hurricane Zone" (HVHZ).				
	2. Proc	duct anchors shall be as listed and spaced as shown on details. Anchor embedment into strate material shall be beyond wall dressing or stucco.				
	Cha	en used in areas requiring wind borne debris protection this product complies with pter 16 of the current Florida Building Code and <u>does</u> require an impact resistant ering for Wind Zone 3.				
	4. Site	conditions that deviate from the details of manufacturer require further engineering ysis by a licensed engineer or registered architect.				

5. See Installation Instructions for size and design pressure limitations

Hermes F Norero, P.E. Florida No.73778 Page **2** of **4**



Certification Agency: The manufacturer has demonstrated compliance of door products in accordance with the current Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity through **National Accreditation and Management Institute** (FBC Organization #: CER1773)

Performance Standards:

The product described herein has been tested per:

- TAS 201-94
- TAS 202-94
- TAS 203-94

Referenced Data:

1.	Product Testing performed by National Certified Testing Laboratories (FBC Organization # TST1589)			
	Report #	Report Date:		
	NCTL-210-3916-01	08/30/13		
	NCTL-210-3925-03	02/07/14		
	NCTL-210-3916-02 w/ addendum	06/10/14		
	NCTL-210-3930-01	02/24/14		
	NCTL-210-3930-02	03/10/14		
	NCTL-310-19-038	03/29/19		
	TAS Report Engineer of Record: Gerard J. Ferrara, P.E.			
	Report #	Report Date:		
	SJW2013-194 w/ addendum	06/10/14		
	TAS Report Engineer of Record: Kevin P	eport Engineer of Record: Kevin P. Tyra, P.E.		
	Report #	Report Date:		
	SJW2013-196-TAS	09/13/13		
	SJW2013-246	12/17/13		
	SJW2013-251	12/23/13		
	SJW2013-252	12/23/13		
	SJW2013-253	12/23/13		
	SJW2014-032	04/22/14		
	SJW2014-073	06/26/14		
	SJW2014-077	06/27/14		
	SJW2014-072	06/27/14		
	SJW2014-080	07/03/14		
	TAS Report Engineer of Record: Robert	H. Zeiders, P.E.		
2.	Quality Assurance Entity National Accreditation & Management Institute			
	(FBC Organization #QUA1789)			
3.	Component Material Testing of Dylite Expandable Polystyrene by			

Hermes F Norero, P.E. Florida No.73778 Page **3** of **4**



Intertek Testing Services NA, Inc. <u>ASTM E84</u> Report#: 3113726SAT-001 R1 Report Date: 03/13/09

- Component Material Testing of Fiberglass SMC Skin
 Element Materials Technology
 <u>ASTM D635, ASTM D638, ASTM D1929, ASTM D2843, ASTM G155</u>
 Report#: ESP010982P Report Date: 02/26/13
- Installation: Refer to Installation Instructions (D015711) for anchor spacing and more details of the installation requirements.

Design Pressure: Refer to drawing (D015711) for pressure information.

Hermes F Norero, P.E. Florida No.73778 Page **4** of **4**