

R W Building Consultants, Inc.

Consulting and Engineering Services for the Building Industry P.O. Box 230 Valrico, FL 33595 Phone 813.659.9197

Florida Board of Professional Engineers Certificate of Authorization No. 9813

Product Evaluation Report

Report No.: Date:

FL-16663.18 August 12, 2015

Product Category	Sub Category	Manufacturer	Product Name
Exterior Doors	Swinging Exterior Door Assemblies	Clark Hall Iron Doors, Inc. 307-GW Tremont Ave. Charlotte, NC 28203 (704) 987-0777	Glazed Iron Double Door w/ Transom w/ & w/out Sidelites Inswing/Outswing - "Impact"

Scope:

This is a Product Evaluation report issued by R W Building Consultants, Inc. and Lyndon F. Schmidt, P.E. for Clark Hall Iron Doors, Inc. based on Rule Chapter No. 61G20-3, Method 1D of the State of Florida Product Approval, Department of Business & Professional Regulation.

RW Building Consultants and Lyndon F. Schmidt, P.E. do not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

Limitations:

- 1. This product has been evaluated and is in compliance with the 5th Edition (2014) Florida Building Code (FBC) structural requirements including the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment to base material shall be beyond wall dressing or
- 3. When used in the "HVHZ", this product complies with Section 1626 of the Florida Building Code and does not require an impact resistant covering.
- 4. For 2x stud framing construction, anchoring of these units shall be the same as that shown for 2x buck masonry construction.
- 5. Site conditions that deviate from the details of drawing FL-16663.18 require further engineering analysis by a licensed engineer or registered architect.
- 6. This product does not meet the water infiltration requirements for the "HVHZ" and shall be installed only in non-habitable areas or at habitable locations protected by an overhang or canopy such that the angle between the edge of canopy or overhang to sill is less than 45 degrees.
- 7. All steel shall be protected as specified in Section 2222.6 of the FBC.
- 8. See drawing FL-16663.18 for size and design pressure limitations.

Supporting Documents:

<u>rest Standard</u>	Testing Laboratory	Signed by
TAS 201, 202 & 203-94	Testing Evaluation Lab., Inc.	William Shelton, P.E.
	<u>Test Standard</u> TAS 201, 202 & 203-94	The state of the s

2. Miami-Dade NOA **Materials Testing**

11-0624.02 DuPont SentryGlas Interlayer

3. Drawing No. Prepared by Signed & Sealed by

RW Building Consultants, Inc. (CA #9813) No. FL-16663.18 Lyndon F. Schmidt, P.E. 4. Calculations Prepared by Signed & Sealed by Lyndon F. Schmidt, P.E.

Anchor RW Building Consultants, Inc. (CA #9813) ASTM E 1300 Glass Load Prepared and Signed by Lyndon F. Schmidt, P.E.

5. Quality Assurance

Certificate of Participation issued by National Accreditation and Management Institute, certifying that Clark Hall Iron Doors, Inc. is manufacturing products within a quality assurance program that complies with ISO/IEC 17020 and Guide 53.

Lyndon F. Schmidt, P.E. 8/18/2015

FL PE No. 43409

Sheet 1 of 1