

398 E. Dania Beach Blvd.
Suite 338
Dania Beach, FL 33004
954.399.8478 PH
954.744.4738 FX
contact@buildingdrops.com

Product Evaluation Report

of

JELD-WEN, inc.
Design Pro / Smooth Pro
Glazed (Impact)

for

Florida Product Approval

Report No. 6271.2

Current Florida Building Code

Method: 1 – A (Certification Method)
Category: Exterior Door Assemblies

Sub – Category: Swinging Exterior Door Assemblies

Product: Design Pro/ Smooth Pro

Material: Fiberglass

Product Dimensions: 12'-0" W x 6'-8" H (Nominal)

12'-0" W x 8'-0" H (Nominal)

Prepared for:

JELD-WEN, inc 3737 Lakeport Blvd. Klamath Falls, OR. 97601

Prepared by:

Hermes F. Norero, P.E.
Florida Professional Engineer # 73778
Date: 09/13/2019

Contents:

Evaluation Report Pages 1 – 3



Date: 09/13/2019 Report No: 6271.2

Manufacturer: JELD-WEN, inc.

Product Category: Exterior Door

Product Sub-Category: Swinging Exterior Door Assemblies

Compliance Method: State Product Approval Method (1)(a)

Product Name: Design Pro / Smooth Pro

Glazed (Impact).

12'-0" X 6'-8" (Nominal) 12'-0" X 8'-0" (Nominal)

Scope:

This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for **JELD-WEN, inc.** based on <u>Method 1a</u> of the State of Florida Product Approval, Department of Business and Professional Regulation - Florida Building Commission.

Hermes F Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building Code.

See Installation Instructions provided by manufacturer for specific use parameters.

Limits of Use:

- 1. This product has been evaluated and is in compliance with the current Florida Building Code, excluding the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and <u>does not</u> require an impact resistant covering for Wind Zone 3. An impact covering is required for Wind Zone 4.
- 4. Site conditions that deviate from the details of manufacturer require further engineering analysis by a licensed engineer or registered architect.
- 5. See Installation Instructions for size and design pressure limitations

Certification Agency:

The manufacturer has demonstrated compliance of door products in accordance with the current Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity through **National Accreditation and Management Institute** (FBC Organization #: CER1773)

Date: 09/13/2019 Report No: 6271.2

Performance Standards:

The product described herein has been tested per:

- ASTM E283-04
- ASTM E330-02
- ASTM E1886-05
- ASTM E1996-06
- AAMA 1304-02
- TAS 202-94

Referenced Data:

1. Product Testing performed by **National Certified Testing Laboratories** (FBC Organization # TST1589)

NCTL-210-3918-01 SJW2013-195 NCTL-210-3924-02 12/18/13 SJW2013-241 SJW2013-242 SJW2013-208-TAS SJW2013-209-TAS SJW2013-234 SJW2013-235 SJW2013-251 SJW2013-252 SJW2013-252 SJW2013-253 NCTL-210-3924-01 NCTL-210-3925-03 SJW2014-032 NCTL-210-3930-01 NCTL-210-3930-02 O3/10/14	Report #	Report Date:
NCTL-210-3924-02 12/18/13 SJW2013-241 12/03/13 SJW2013-242 12/03/13 SJW2013-208-TAS 11/13/13 SJW2013-209-TAS 11/13/13 SJW2013-234 12/09/13 SJW2013-235 11/26/13 SJW2013-251 12/23/13 SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	NCTL-210-3918-01	10/04/13
SJW2013-241 12/03/13 SJW2013-242 12/03/13 SJW2013-208-TAS 11/13/13 SJW2013-209-TAS 11/13/13 SJW2013-234 12/09/13 SJW2013-235 11/26/13 SJW2013-251 12/23/13 SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-195	09/16/13
SJW2013-242 12/03/13 SJW2013-208-TAS 11/13/13 SJW2013-209-TAS 11/13/13 SJW2013-234 12/09/13 SJW2013-235 11/26/13 SJW2013-251 12/23/13 SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	NCTL-210-3924-02	12/18/13
SJW2013-208-TAS 11/13/13 SJW2013-209-TAS 11/13/13 SJW2013-234 12/09/13 SJW2013-235 11/26/13 SJW2013-251 12/23/13 SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-241	12/03/13
SJW2013-209-TAS 11/13/13 SJW2013-234 12/09/13 SJW2013-235 11/26/13 SJW2013-251 12/23/13 SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-242	12/03/13
SJW2013-234 12/09/13 SJW2013-235 11/26/13 SJW2013-251 12/23/13 SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-208-TAS	11/13/13
SJW2013-235 11/26/13 SJW2013-251 12/23/13 SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-209-TAS	11/13/13
SJW2013-251 12/23/13 SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-234	12/09/13
SJW2013-252 12/23/13 SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-235	11/26/13
SJW2013-253 12/23/13 NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-251	12/23/13
NCTL-210-3924-01 12/18/13 NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-252	12/23/13
NCTL-210-3925-03 02/07/14 SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	SJW2013-253	12/23/13
SJW2014-032 04/22/14 NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	NCTL-210-3924-01	12/18/13
NCTL-210-3930-01 02/24/14 NCTL-210-3930-02 03/10/14	NCTL-210-3925-03	02/07/14
NCTL-210-3930-02 03/10/14	SJW2014-032	04/22/14
• •	NCTL-210-3930-01	02/24/14
CDA/2014 0C0 07/07/44	NCTL-210-3930-02	03/10/14
5JW2014-069 07/07/14	SJW2014-069	07/07/14
SJW2014-079 07/07/14	SJW2014-079	07/07/14
NCTL-310-19-038 03/29/19	NCTL-310-19-038	03/29/19

2. Product Testing performed by **Quality Testing Inc.**

(FBC Organization # TST7638)

Report # Report Date: SJW2010-003 01/11/10

3. Quality Assurance Entity

National Accreditation & Management Institute

(FBC Organization #QUA1789)



Date: 09/13/2019 Report No: 6271.2

Installation: Refer to Installation Instructions (D015701) for anchor spacing and more details of the

installation requirements.

Design Pressure: Refer to drawing **(D015701)** for pressure information