

L. Roberto Lomas P.E.

1432 Woodford Rd.
Lewisville, NC 27023
434-688 0609
rlomas@lrlomaspe.com

Engineering Evaluation Report

Report No.: 513308C

Manufacturer: Eastern Architectural Systems
16341 Domestic Ave.
FT Myers, FL 33912

Product Line: Series 176 SS Vinyl Horizontal Sliding Window – XOX – ¼ - ½ - ¾

Compliance:

The above mentioned product has been evaluated for compliance with the requirements of the Florida Department of Business and Professional Regulation for Statewide Acceptance per Rule 61G20-3.005 method 1(a). The product listed herein complies with requirements of the Florida Building Code.

Supporting Technical Documentation:

1. Approval document: drawing number 08-02536 Revision B, prepared, signed and sealed by Luis Roberto Lomas P.E.
2. Test report No.: CTLA 3005W-2A signed and sealed by Ramesh Patel P.E.
Certified Testing Laboratories, Orlando, FL.
AAMA/WDMA/CSA 101/I.S.2/A440
Design pressure: +50.0/-65.0psf (Through frame installation)
+55.0/-60.0psf (Fin installation)
Water penetration resistance 10.5psf
ASTM E1886/ E1996 Large Missile Impact, Level D, Wind Zone 4
Cyclic Load Test, +70.0/-85.0psf (Through frame and fin installation) design pressure
3. Test report No.: CTLA 3005W-2D signed and sealed by Ramesh Patel P.E.
Certified Testing Laboratories, Orlando, FL
TAS 202
Design pressure: +50.0/-65.0psf (Through frame installation)
+55.0/-60.0psf (Fin installation)
Water penetration resistance 10.5psf
TAS 201/TAS203 Large Missile Impact, Level D, Wind Zone 4
Cyclic Load Test, +70.0/-85.0psf (Through frame and fin installation) design pressure
4. Anchor calculations, report number 513308-1A, prepared, signed and sealed by Luis Roberto Lomas P.E.

Limitations and Conditions of use:

- Maximum design pressure: +50.0/-65.0psf (Through frame installation)
+55.0/-60.0psf (Fin installation)
- Maximum unit size: 111" X 63"
- Approved Configurations: XOX (1/4 – 1/2 – 1/4)
- Units must be glazed per ASTM E1300 according to glazing details in approval drawing.
- This product is rated to be used in the HVHZ.
- This product is impact resistant and does not require impact protection in wind borne debris regions.
- Frame material to be extruded vinyl.

Installation:

Units must be installed in accordance with manufacturer's installation instructions and approval document 08-02536 Revision B.

Certification of Independence:

Please note that I don't have nor will acquire a financial interest in any company manufacturing or distributing the product(s) for which this report is being issued. Also, I don't have nor will acquire a financial interest in any other entity involved in the approval process of the listed product(s).

