



Project No.: 27290.01-107-16
Project Name: Architectural Fiberglass
Outswing Opaque High Dam Sill
Date: 9/29/2023
Page 1 of 17

PRODUCT APPROVAL SUPPORTING CALCULATIONS

Series/Model Architectural Fiberglass Outswing Opaque High Dam Sill

REPORT No.: 27290.01-107-16

RENDERED TO: Jeld-Wen Windows & Doors
3737 Lakeport Blvd
Klamath Falls, Oregon

PREPARED BY: Michael D. Stremmel, P.E.
Molimo, LLC
1410 Eden Road
York, Pennsylvania 17402

DATE: 9/29/2023

This item has been digitally signed and sealed by Michael D. Stremmel, PE on the date adjacent to the seal.

Printed copies of this document are not considered signed and sealed and the signature must be verified on electronic copies.

Michael D. Stremmel, P.E.
Senior Project Engineer
FL PE 65868
FL REG 37122

It is a violation to alter this document in any way unless acting under the direction of a licensed professional engineer.



Project No.: 27290.01-107-16
Project Name: Architectural Fiberglass
Outswing Opaque High Dam Sill
Date: 9/29/2023
Page 2 of 17

SCOPE:

Molimo, LLC was contracted by Jeld-Wen Windows & Doors to evaluate alternate installation methods for their Architectural Fiberglass Outswing Opaque High Dam Sill. The evaluation is based on physical testing and product certifications.

Reference standards utilized in this project include:

Florida Building Code. International Code Council.

ANSI/AWC National Design Specification (NDS) for Wood Construction. American Wood Council.

AISI S100 North American Specification for the Design of Cold-Formed Steel Structural Members. American Iron and Steel Institute.

ICC-ES Report ESR-1976 ITW Buildex TEKS Self-Drilling Fasteners. ICC Evaluation Service.

NOA 21-0201.06 *Tapcon Concrete and Masonry Anchors with Advanced Threadform Technology.* Miami-Dade County Product Control Section.

The anchorage analysis presented herein does not address the water resistance, water penetration, or air infiltration performance of the installation method or the installed product. In addition, the analyses rely on the assumption that the building substrate is capable of withstanding the incurred loads.



Project No.: 27290.01-107-16
Project Name: Architectural Fiberglass
Outswing Opaque High Dam Sill
Date: 9/29/2023
Page 3 of 17

Certification of Independence

In accordance with Rule 61G20-3 Florida Administrative Code, Molimo, LLC hereby certifies the following:

- Molimo, LLC does not have, nor does it intend to acquire or will it acquire, a financial interest in any company manufacturing or distributing products tested or labeled by the agency.
- Molimo LLC is not owned, operated or controlled by any company manufacturing or distributing products it tests or labels.
- Michael D. Stremmel, P.E. does not have nor will acquire, a financial interest in any company manufacturing or distributing products for which the reports are being issued.
- Michael D. Stremmel, P.E. does not have, nor will acquire, a financial interest in any other entity involved in the approval process of the product.



Project No.: 27290.01-107-16
Project Name: Architectural Fiberglass
 Outswing Opaque High Dam Sill
Date: 9/29/2023
 Page 4 of 17

ANALYSES:

Summary of Test Results

Table 1 summarizes the various Architectural Fiberglass Outswing Opaque High Dam Sill products and their corresponding performance levels which have been established by testing or product certification.

Table 1: Summary of Test Results

Series/Model	Test Report Number	Size (W x H)	Performance
Architectural Fiberglass Outswing Opaque High Dam Sill	Intertek Report No. H9983.01-301-47-R0 (Rev. 0, 2/16/18)	72-3/8" x 80-7/16"	+50 / -50 psf Wind Zone 3 Impacts

Testing documented in Table 1 was conducted by Intertek of Fresno, California (Florida Department of Business & Professional Regulation Test Lab No. TST2609, IAS Certificate of Accreditation TL-264).

As-Tested Installation Analysis

For air/water/structural testing, the test specimen was secured to a Douglas-Fir wood test buck with #8 wood screws (1-1/2" min. embedment) through the threshold and 20 ga steel straps at the head and jambs with two #8 wood screws into the frame and two #8 wood screws (1-1/2" min. embedment) through the strap into the wood test buck. The as tested installation method is evaluated on Pages 5 through 9. These capacities will be used to prove acceptable anchors and substrates for the product.

Alternate Anchorages

Calculations on Pages 10 through 16 determine the design capacity of alternate installation anchorages for the product.

Anchorages Requirements

As-tested spacing must be maintained. It must be determined that the anchorages are not overloaded for the approved product size and design pressures. Calculations presented on Page 17 show the alternate anchorages are acceptable for the established product performance.

Anchorage requirements established by this report are accurately presented in Drawing D015317.

As Tested Installation – Strap Anchor to Wood

Anchor: (2)#8 x 1-1/2" Flat head screw securing the strap to the substrate
No shim space was utilized

Details: 20 gauge (0.036" thick) 33 KSI steel strap anchor w/ two #8 x 1/2" screws
securing the strap to the frame
0.719" thick wood frame

Substrate: Douglas-Fir 2x Wood Substrate (G = 0.42 min.)

Wood Screw Capacity (Shear – Wood Buck Anchor)

$$Z' = \underline{123 \text{ lb}} \quad (\text{See Page 6})$$

Wood Screw Capacity (Shear – Frame Anchor)

$$Z' = \underline{63 \text{ lb}} \quad (\text{See Page 7})$$

Bearing Capacity (of #8 screw on frame)

$$P_b = F_e D t / K_D = (3,350 \text{ psi})(0.164")(0.719") / (10(0.164) + 0.5) = \underline{184 \text{ lb}}$$

Bearing Capacity (of strap anchor)

$$P_b = 2.7 D t F_{tu} = 2.7(0.164")(0.036")(45,000 \text{ psi}) = 717 \text{ lb}$$

$$P_{\text{allow}} = 717 \text{ lb} / 3.0 = \underline{239 \text{ lb}}$$

Design Capacity of the Connection = 63 lb x 2 = 126 lb

Lateral Design Strength of Wood Connections

Data

Fastener

Fastener	=	#8 Wood Screw
Shank Dia	=	0.164 in.
Root Dia.	=	0.131 in.
F_{yb}	=	90,000 psi
Fastener length	=	1.500 in.

Project: Architectural Fiberglass Outswing
 Opaque High Dam Sill

Comments: Strap Anchor Detail
 1-1/2" min embedment

Main Member

Material	=	SPF
G	=	0.42
θ	=	90
F_e	=	3,350 psi
Thickness	=	1.500 in.

Side Member

Material	=	ASTM A 653, Grade 33 Steel
G	=	N/A
θ	=	90
F_{es}	=	61,850 psi
Thickness	=	0.036 in.

Calculations

Lateral Bearing Factors

D	=	0.131 in.	k_1	=	0.7981
ℓ_m	=	1.300 in.	k_2	=	0.5198
K_θ	=	1.25	k_3	=	21.94
K_D	=	2.20	R_d	=	2.20 (Mode I _m , I _s)
R_e	=	0.054	R_d	=	2.20 (Mode II)
R_t	=	36.11	R_d	=	2.20 (Mode III _m , III _s , IV)

Lateral Design Values, Z

Mode I _m	=	259 lbf
Mode I _s	=	133 lbf
Mode II	=	106 lbf
Mode III _m	=	122 lbf
Mode III _s	=	77 lbf
Mode IV	=	108 lbf

<== Minimum Value

Adjustment Factors

C_D	=	1.6	C_Δ	=	1.0
Wet Service Factor			Is fastener installed in end grain?		No
Fabrication/In-Service		Dry/Dry	C_{eg}	=	1.00
C_M	=	1.0	Is fastener part of a diaphragm?		No
In service temperature		$T \leq 100^\circ\text{F}$	C_{di}	=	1.0
C_t	=	1.0	Is fastener toe-nailed?		No
C_g	=	1.0	C_{tn}	=	1.00

Adjusted Design Value, Z'

Z'	=	123 lbf
----	---	---------

Lateral Design Strength of Wood Connections

Data

Fastener

Fastener	=	#8 Wood Screw
Shank Dia	=	0.164 in.
Root Dia.	=	0.131 in.
F_{yb}	=	90,000 psi
Fastener length	=	0.500 in.

Project: Architectural Fiberglass Outswing
 Opaque High Dam Sil
Comments: Strap Anchor Detail
 Door Frame Anchor

Main Member

Material	=	SPF
G	=	0.42
θ	=	90
F_e	=	3,350 psi
Thickness	=	0.719 in.

Side Member

Material	=	ASTM A 653, Grade 33 Steel
G	=	N/A
θ	=	90
F_{es}	=	61,850 psi
Thickness	=	0.036 in.

Calculations

Lateral Bearing Factors

D	=	0.131 in.
l_m	=	0.464 in.
K_θ	=	1.25
K_D	=	2.20
R_e	=	0.054
R_t	=	12.89

k_1	=	0.2978
k_2	=	0.9211
k_3	=	21.94
R_d	=	2.20 (Mode I _m , I _s)
R_d	=	2.20 (Mode II)
R_d	=	2.20 (Mode III _m , III _s , IV)

Lateral Design Values, Z

Mode I _m	=	93 lbf
Mode I _s	=	133 lbf
Mode II	=	39 lbf
Mode III _m	=	77 lbf
Mode III _s	=	77 lbf
Mode IV	=	108 lbf

<===== Minimum Value

Adjustment Factors

C_D	=	1.6
Wet Service Factor		
Fabrication/In-Service	=	Dry/Dry
C_M	=	1.0
In service temperature	=	$T \leq 100^\circ\text{F}$
C_t	=	1.0
C_g	=	1.0

C_Δ	=	1.0
Is fastener installed in end grain?	=	No
C_{eg}	=	1.00
Is fastener part of a diaphragm?	=	No
C_{di}	=	1.0
Is fastener toe-nailed?	=	No
C_{tn}	=	1.00

Adjusted Design Value, Z'

Z'	=	63 lbf
----	---	--------



Project No.: 27290.01-107-16
Project Name: Architectural Fiberglass
Outswing Opaque High Dam Sill
Date: 9/29/2023
Page 8 of 17

As-Tested Installation – Through Threshold to Wood Substrate

Anchor: #8 Wood Screw

Details: 0.719" thick wood frame (G = 0.42)
No shim space was utilized

Substrate: Douglas-Fir wood substrate (G = 0.46)

Wood Screw Capacity (Shear)

$Z' = \underline{\underline{111 \text{ lb}}}$

(See Following Page)

Design Capacity of the Connection = 111 lb

Lateral Design Strength of Wood Connections

Data

Fastener	
Fastener	= #8 Wood Screw
Shank Dia	= 0.164 in.
Root Dia.	= 0.131 in.
F_{yb}	= 90,000 psi
Fastener length	= 2.250 in.

Project: Architectural Fiberglass Outswing
 Opaque High Dam Sill
Comments: As-Tested - Thru-Threshold
 1-1/2" min embedment

Main Member	
Material	= Douglas Fir (South)
G	= 0.46
θ	= 90
F_e	= 4,000 psi
Thickness	= 1.500 in.

Side Member	
Material	= SPF
G	= 0.42
θ	= 90
F_{es}	= 3,350 psi
Thickness	= 0.719 in.

Calculations

Lateral Bearing Factors

D	= 0.131 in.
l_m	= 1.367 in.
K_θ	= 1.25
K_D	= 2.20
R_e	= 1.194
R_t	= 1.90

k_1	= 0.7419	
k_2	= 1.2034	
k_3	= 1.29	
R_d	= 2.20	(Mode I _m , I _s)
R_d	= 2.20	(Mode II)
R_d	= 2.20	(Mode III _m , III _s , IV)

Lateral Design Values, Z

Mode I _m	= 326 lbf
Mode I _s	= 143 lbf
Mode II	= 106 lbf
Mode III _m	= 116 lbf
Mode III _s	= 69 lbf
Mode IV	= 82 lbf

<== Minimum Value

Adjustment Factors

C_D	= 1.6
Wet Service Factor	
Fabrication/In-Service	Dry/Dry
C_M	= 1.0
In service temperature	$T \leq 100^\circ\text{F}$
C_t	= 1.0
C_g	= 1.0

C_Δ	= 1.0
Is fastener installed in end grain?	No
C_{eg}	= 1.00
Is fastener part of a diaphragm?	No
C_{di}	= 1.0
Is fastener toe-nailed?	No
C_{tn}	= 1.00

Adjusted Design Value, Z'

Z'	= 111 lbf
----	-----------

Alternate Installation – Through Frame to Wood

Anchor: #8 Wood Screw

Details: 1-1/4" thick wood frame (G = 0.42)
1/4" max shim space

Substrate: Spruce-Pine-Fir wood substrate (G = 0.42)

Wood Screw Capacity (Shear)

$$Z' = \underline{125 \text{ lb}}$$

(See Following Page)

Bending of #8 x 1-1/2" flat head screw

$$L = 1/4" \text{ (maximum shim space)}$$

$$S = \pi d^3 / 32 = \pi (0.131")^3 / 32 = 0.000221 \text{ in}^3$$

$$F_b = (1.3)(0.6 F_y) = (1.3)(0.6)(90,000 \text{ psi}) = 70,200 \text{ psi} \quad (1.3 \text{ for weak axis bending})$$

$$F_b = M / S = (V) (L/2) / S \quad (L/2 \text{ for guided bending})$$

$$V = 2 S F_b / L = (2)(0.000221 \text{ in}^3)(70,200 \text{ psi}) / 1/4"$$

$$V = \underline{124 \text{ lb}}$$

Design Capacity of the Connection = 125 lb

Lateral Design Strength of Wood Connections

Data

Fastener	
Fastener	= #8 Wood Screw
Shank Dia	= 0.164 in.
Root Dia.	= 0.131 in.
F_{yb}	= 90,000 psi
Fastener length	= 2.750 in.

Project: Architectural Fiberglass Outswing
 Opaque High Dam Sill
Comments: Thru-Frame Installation
 1-1/2" min embedment

Main Member	
Material	= SPF
G	= 0.42
θ	= 90
F_e	= 3,350 psi
Thickness	= 1.500 in.

Side Member	
Material	= SPF
G	= 0.42
θ	= 90
F_{es}	= 3,350 psi
Thickness	= 1.250 in.

Calculations

Lateral Bearing Factors

D	= 0.131 in.
l_m	= 1.336 in.
K_θ	= 1.25
K_D	= 2.20
R_e	= 1.000
R_t	= 1.07

k_1	= 0.4289	
k_2	= 1.1252	
k_3	= 1.14	
R_d	= 2.20	(Mode I _m , I _s)
R_d	= 2.20	(Mode II)
R_d	= 2.20	(Mode III _m , III _s , IV)

Lateral Design Values, Z

Mode I _m	= 267 lbf
Mode I _s	= 249 lbf
Mode II	= 107 lbf
Mode III _m	= 100 lbf
Mode III _s	= 95 lbf
Mode IV	= 78 lbf

<===== Minimum Value

Adjustment Factors

C_D	= 1.6
Wet Service Factor	
Fabrication/In-Service	Dry/Dry
C_M	= 1.0
In service temperature	$T \leq 100^\circ\text{F}$
C_t	= 1.0
C_g	= 1.0

C_Δ	= 1.0
Is fastener installed in end grain?	No
C_{eg}	= 1.00
Is fastener part of a diaphragm?	No
C_{di}	= 1.0
Is fastener toe-nailed?	No
C_{tn}	= 1.00

Adjusted Design Value, Z

Z'	= 125 lbf
----	-----------

Alternate Installation – Through-Frame to Concrete

Anchor: 3/16" Tapcon Anchor
- 1-1/4" min embedment
- 2-1/2" min edge distance
- 3" min anchor spacing
- 1/4" max shim space

Details: Through the Wood Frame
- 0.719" thick

Substrate: 3,000 psi Concrete

Anchor Capacity (Shear of 3/16" Tapcon)

$$P_{ss} / \Omega = \underline{181 \text{ lb}} \quad (\text{NOA-No. 21-0201.06})$$

Bearing Capacity (of Wood frame)

$$P_b = F_e D t / K_D = (3,350 \text{ psi})(0.170")(0.719") / (10(0.170) + 0.5) = \underline{194 \text{ lb}}$$

Bending Capacity (of 3/16" Tapcon)

$$L = 1/4" \text{ (maximum shim space)}$$

$$S = \pi d^3 / 32 = \pi (0.170")^3 / 32 = 0.000482 \text{ in}^3$$

$$F_b = (1.3)(0.6 F_y) = (1.3)(0.6)(137,000 \text{ psi}) = 106,860 \text{ psi} \quad (1.3 \text{ for weak axis bending})$$

$$F_b = M / S = (V) (L/2) / S \quad (L/2 \text{ for guided bending})$$

$$V = 2 S F_b / L = (2)(0.000482 \text{ in}^3)(106,860 \text{ psi}) / 1/4"$$

$$V = \underline{412 \text{ lb}}$$

Design Capacity of the Connection = 181 lb

Qualifies 1/4" Tapcon if longer length anchor is required to achieve minimum embedment

Alternate Installation – Through-Frame to CMU Block

Anchor: 3/16" Tapcon Anchor
- 1-1/4" min embedment
- 2-1/2" min edge distance
- 3" min anchor spacing
- 1/4" max shim space

Details: Through the Wood Frame
- 0.719" thick

Substrate: CMU Block

Anchor Capacity (Shear of 3/16" Tapcon)

$$P_{ss} / \Omega = \underline{135 \text{ lb}} \quad (\text{NOA-No. 21-0201.06})$$

Bearing Capacity (of Wood frame)

$$P_b = F_e D t / K_D = (3,350 \text{ psi})(0.170")(0.719") / (10(0.170) + 0.5) = \underline{194 \text{ lb}}$$

Bending Capacity (of 3/16" Tapcon)

$$L = 1/4" \text{ (maximum shim space)}$$

$$S = \pi d^3 / 32 = \pi (0.170")^3 / 32 = 0.000482 \text{ in}^3$$

$$F_b = (1.3)(0.6 F_y) = (1.3)(0.6)(137,000 \text{ psi}) = 106,860 \text{ psi} \quad (1.3 \text{ for weak axis bending})$$

$$F_b = M / S = (V) (L/2) / S \quad (L/2 \text{ for guided bending})$$

$$V = 2 S F_b / L = (2)(0.000482 \text{ in}^3)(106,860 \text{ psi}) / 1/4"$$

$$V = \underline{412 \text{ lb}}$$

Design Capacity of the Connection = 135 lb

Qualifies 1/4" Tapcon if longer length anchor is required to achieve minimum embedment

Alternate Installation – Strap Anchor to Concrete

Anchor: 3/16" Tapcon Anchor
 - 1-1/4" min embedment
 - 2-1/2" min edge distance
 - 3" min anchor spacing
 - 1/4" max shim space

Details: 20 gauge (0.036" thick) 33 KSI steel strap anchor w/ two #8 screws securing the strap to the frame
 0.719" thick wood frame

Substrate: 3,000 psi Concrete

Anchor Capacity (Shear of 3/16" Tapcon)

$$P_{ss} / \Omega = \underline{181 \text{ lb}} \quad (\text{NOA-No. 21-0201.06})$$

Bearing Capacity (of 3/16" Tapcon on strap anchor)

$$P_b = 2.7 D t F_{tu} = 2.7(0.170")(0.036")(45,000 \text{ psi}) = 743 \text{ lb}$$

$$P_{\text{allow}} = 743 \text{ lb} / 3.0 = \underline{247 \text{ lb}}$$

Bearing Capacity (of #8 screw on frame)

$$P_b = F_e D t / K_D = (3,350 \text{ psi})(0.164")(0.719") / (10(0.164) + 0.5) = \underline{184 \text{ lb}}$$

Bearing Capacity (of #8 screw on strap anchor)

$$P_b = 2.7 D t F_{tu} = 2.7(0.164")(0.036")(45,000 \text{ psi}) = 717 \text{ lb}$$

$$P_{\text{allow}} = 717 \text{ lb} / 3.0 = \underline{239 \text{ lb}}$$

Bending Capacity (of 3/16" Tapcon)

$$L = 1/4" \text{ (maximum shim space)}$$

$$S = \pi d^3 / 32 = \pi (0.170")^3 / 32 = 0.000482 \text{ in}^3$$

$$F_b = (1.3)(0.6 F_y) = (1.3)(0.6)(137,000 \text{ psi}) = 106,860 \text{ psi} \quad (1.3 \text{ for weak axis bending})$$

$$F_b = M / S = (V) (L/2) / S \quad (L/2 \text{ for guided bending})$$

$$V = 2 S F_b / L = (2)(0.000482 \text{ in}^3)(106,860 \text{ psi}) / 1/4"$$

$$V = \underline{412 \text{ lb}}$$

Design Capacity of the Connection = 181 lb (one concrete anchor per strap)

Qualifies 1/4" Tapcon if longer length anchor is required to achieve minimum embedment

Alternate Installation – Strap Anchor to CMU Block

Anchor: 3/16" Tapcon Anchor
- 1-1/4" min embedment
- 2-1/2" min edge distance
- 3" min anchor spacing
- 1/4" max shim space

Details: 20 gauge (0.036" thick) 33 KSI steel strap anchor w/ two #8 screws securing the strap to the frame
0.719" thick wood frame

Substrate: CMU Block

Anchor Capacity (Shear of 3/16" Tapcon)

$$P_{ss} / \Omega = \underline{135 \text{ lb}} \quad (\text{NOA-No. 21-0201.06})$$

Bearing Capacity (of 3/16" Tapcon on strap anchor)

$$P_b = 2.7 D t F_{tu} = 2.7(0.170")(0.036")(45,000 \text{ psi}) = 743 \text{ lb}$$

$$P_{\text{allow}} = 743 \text{ lb} / 3.0 = \underline{247 \text{ lb}}$$

Bearing Capacity (of #8 screw on frame)

$$P_b = F_e D t / K_D = (3,350 \text{ psi})(0.164")(0.719") / (10(0.164) + 0.5) = \underline{184 \text{ lb}}$$

Bearing Capacity (of #8 screw on strap anchor)

$$P_b = 2.7 D t F_{tu} = 2.7(0.164")(0.036")(45,000 \text{ psi}) = 717 \text{ lb}$$

$$P_{\text{allow}} = 717 \text{ lb} / 3.0 = \underline{239 \text{ lb}}$$

Bending Capacity (of 3/16" Tapcon)

$$L = 1/4" \text{ (maximum shim space)}$$

$$S = \pi d^3 / 32 = \pi (0.170")^3 / 32 = 0.000482 \text{ in}^3$$

$$F_b = (1.3)(0.6 F_y) = (1.3)(0.6)(137,000 \text{ psi}) = 106,860 \text{ psi} \quad (1.3 \text{ for weak axis bending})$$

$$F_b = M / S = (V) (L/2) / S \quad (L/2 \text{ for guided bending})$$

$$V = 2 S F_b / L = (2)(0.000482 \text{ in}^3)(106,860 \text{ psi}) / 1/4"$$

$$V = \underline{412 \text{ lb}}$$

Design Capacity of the Connection = 135 lb (one concrete anchor per strap)

Qualifies 1/4" Tapcon if longer length anchor is required to achieve minimum embedment

Alternate Installation – Strap Anchor to Wood (Cap Installation)

Anchor: One #8 x 1-1/2" Flat head screw securing the strap to the substrate

Details: 20 gauge (0.036" thick) 33 KSI steel strap anchor w/ two #8 screws securing the strap to the frame
0.719" thick wood frame
1/4" max shim space

Substrate: Spruce-Pine-Fir 2x Wood Substrate (G = 0.42 min.)

Wood Screw Capacity (Withdrawal)

$$W' = 1.6(82 \text{ lb/in})(1.5 \text{ in}) = \underline{197 \text{ lb}}$$

Pull-over Capacity (of #8 screw on strap)

$$P_{\text{nov}} = 1.5 t d F_{\text{tu}} = 1.5 (0.036")(0.332")(45,000 \text{ psi}) = 806 \text{ lb}$$

$$P_{\text{allow}} = 806 \text{ lb} / 3.0 = \underline{268 \text{ lb}}$$

Bearing Capacity (of #8 screw on frame)

$$P_b = F_e D t / K_D = (3,350 \text{ psi})(0.164")(0.719") / (10(0.164) + 0.5) = \underline{184 \text{ lb}}$$

Bearing Capacity (of #8 screw on strap anchor)

$$P_b = 2.7 D t F_{\text{tu}} = 2.7(0.164")(0.036")(45,000 \text{ psi}) = 717 \text{ lb}$$

$$P_{\text{allow}} = 717 \text{ lb} / 3.0 = \underline{239 \text{ lb}}$$

Design Capacity of the Connection = 184 lb (one screw)

Anchorage Requirements

Series/Model: Architectural Fiberglass Outswing Opaque High Dam Sill
Test Unit Size: 72-3/8" x 80-7/16"
Design Pressure: +50.0 / -50.0 psf

Anchor Strap to Wood Substrate Installation Method (As Tested)

Anchor Strap installation method to wood substrate and Threshold anchor to wood substrate is validated by the test wit

Through Threshold Anchor Capacity = 111 lb / anchor

Anchor Strap Capacity = 126 lb / anchor

Alternate Installation Methods

Thru-Frame Anchor to Wood = 125 lb / anchor

Through-Frame to Concrete = 181 lb / anchor

Through-Frame to CMU Block = 135 lb / anchor

Strap Anchor to Concrete = 181 lb / anchor

Strap Anchor to CMU Block = 135 lb / anchor

Strap Anchor to Wood (Cap Installation) = 184 lb / anchor

Minimum Alternate Installation Capacity = 125 lb / anchor

125 lb ~ 126 lb (< 1% difference OK)

Alternate Anchorages OK at tested spacing



Project No.: 27290.01-107-16
Project Name: Architectural Fiberglass
Outswing Opaque High Dam Sill
Date: 9/29/2023

Revision Log

Rev. #	Date	Page(s)	Revision(s)
0	9/29/2023	All	Original Report Issue