

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Product Evaluation Report

of

All Seasons Commercial E2500/E3250/E4000 Project Out Window (Non-HVHZ) (Non-Impact)

for

Florida Product Approval

FL# 17125

Report No. 9094

Current Florida Building Code

Method: 1 – A (Certification)

Category: Windows
Sub – Category: Projected

Product: E2500/E3250/E4000

Project Out Window

Materials: 6063-T5 Aluminum

Product Dimensions: See Installation Instructions, 8097-10

Prepared for:


All Seasons Commercial 400 Ambassador Row Longview, TX 75064

Prepared by:

Hermes F. Norero, P.E.
Florida Professional Engineer # 73778
Date: 2/23/2024

Contents:

Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



FL#: FL17125 Report #: 9094 Date: 2/23/2024

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Manufacturer: **All Seasons Commercial**

Product Category: Windows

Product Sub-Category: Projected

State Product Approval Method (1)(a) **Compliance Method:**

Product Name: E2500/E3250/E4000 Project Out Window

(Non-HVHZ) (Non-Impact)

Scope: This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for All

> Seasons Commercial based on Method 1a of the State of Florida Product Approval, Department of Business and Professional Regulation - Florida Building Commission.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building Code.

See Installation Instructions 8097-10, signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.

Limits of Use:

- 1. This product has been evaluated and is in compliance with the current Florida Building Code, excluding the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and does require an impact resistant covering.
- Site conditions that deviate from the details of installation instructions 8097-10 4. require further engineering analysis by a licensed engineer or registered architect.
- 5. See Installation Instructions **8097-10** for size and design pressure limitations.



FL#: FL17125 **Report #:** 9094 2/23/2024 Date:

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Certification Agency: The manufacturer has demonstrated compliance of manufacture of products

in accordance with the Florida Building Code for manufacturing under an

approved certification agency through National Accreditation &

Management Institute (FBC Organization # CER1773).

Performance Standards: The product described herein has been evaluated per:

AAMA/WDMA/CSA 101/I.S.2/A440-08

Referenced Data:

1. Product Testing performed by Architectural Testing, Inc. (FBC

Organization # TST1910)

Report #: Report Date: A5248.01-801-44-R1 08/14/13

2. Certification Agency:

National Accreditation & Management Institute

(FBC Organization #CER1773)

Installation:

Refer to Installation Instructions (8097-10) for anchor types, spacing, and more details of the

installation requirements.

Design Pressure:

Refer to Installation Instructions (8097-10) for design pressure configurations.







