

398 East Dania Beach Blvd.
Suite 338
Dania Beach, FL 33004
954.399.8478 PH
954.744.4738 FX
contact@buildingdrops.com

Product Evaluation Report

of

JELD-WEN, inc. Siteline or W-5500 Wood Casement/Awning Mullions

for

Florida Product Approval

Report No. 6279

Current Florida Building Code

Method: 1-D (Engineering Evaluation)

Category: Windows
Sub – Category: Mullions

Product: Siteline or W-5500 Wood Casement/Awning

Mullions

Material: Wood (Pine)

Prepared for:

JELD-WEN, inc. 3737 Lakeport Blvd. Klamath Falls, OR. 97601

Prepared by:

Hermes F. Norero, P.E.

Florida Professional Engineer # 73778 Date: 06/11/19

Contents:

Evaluation Report Pages 1 – 3



Date: 06/11/19 Report No: 6279

Manufacturer: JELD-WEN, inc.

Product Category: Windows

Product Sub-Category: Mullions

Compliance Method: State Product Approval Method (1)(d)

Product Name: Siteline or W-5500 Wood Casement/Awning Mullions

Scope: This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for JELD-WEN inc.

based on Method 1d of the State of Florida Product Approval, Department of Business and

Professional Regulation.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the Current Florida Building Code (FBC).

See Installation Instructions **JW061**, signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.

Limits of Use:

- 1. This product has been evaluated and is in compliance with the Current Florida Building Code, excluding the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the Current Florida Building Code and <u>does not</u> require an impact resistant covering in Wind Zones 3 or less provided window assemblies are minimum Wind Zone 3 impact rated. In Wind Zone 4, units shall require impact resistant protection.
- 4. Site conditions that deviate from the details of drawing **JW061** require further engineering analysis by a licensed engineer or registered architect.
- 5. See Installation Instructions **JW061** for size and design pressure limitations.

Date: 06/11/19 Report No: 6279

Quality Assurance:

The manufacturer has demonstrated compliance of products in accordance with the Florida Building Code and Florida Product Approval system for manufacturing under a quality assurance program audited by an approved quality assurance entity through **Window and Door Manufacturers Association.** (FBC Organization # QUA2515)

Performance Standards:

The product described herein has been tested per:

AAMA 450-10

Referenced Data:

1. Product Testing performed by Architectural Testing, Inc./Intertek

(FBC Organization # TST2609)

Report: F4259.01-301-47-r0, Report Date: 04/12/16 Report: F4261.01-301-47-r0, Report Date: 03/10/16

2. Quality Assurance

Window and Door Manufacturers Association

(FBC Organization #: QUA2515)

3. ICC Evaluation Report, ESR-1539

Installation:

Refer to Installation Instructions (**JW061**) for anchor spacing and more details of the installation requirements.

Design Pressure:

Refer to Installation Instructions (**JW061**) for design pressures dependent on mull assembly, configuration, and size of units.