

## R W Building Consultants, Inc.

Consulting and Engineering Services for the Building Industry P.O. Box 230 Valrico, FL 33595 Phone 813.659.9197

Florida Board of Professional Engineers Registry License No. 9813

## **Product Evaluation Report**

Report No.:

FL-21132.9

Date:

July 20, 2020

Product Category	Sub Category	Manufacturer	Product Name	
Exterior Doors	Swinging Exterior Door Assemblies	118 Industrial Drive Wood Edge Glazed Steel Si	Profiles and Traditions Wood Edge Glazed Steel Single Door Inswing/Outswing "Impact"	

Scope:

This is a Product Evaluation report issued by R W Building Consultants, Inc. and Lyndon F. Schmidt, P.E. for Therma Tru Corporation based on Rule Chapter No. 61G20-3, Method 1D of the State of Florida Product Approval, Department of Business & Professional Regulation.

RW Building Consultants and Lyndon F. Schmidt, P.E. do not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

## Limitations:

- 1. This product has been evaluated and is in compliance with the 7th Edition (2020) Florida Building Code (FBC) structural requirements excluding the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment to base material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with FBC Sections 1609.1.2 & R301.2.1.2 and does not require an impact resistant covering. This product meets missile level "D" and includes Wind Zone 4 as defined in ASTM E1996 and FBC Sections 1609.1.2.2 & R301.2.1.2.1.
- 4. For 2x stud framing construction, anchoring of these units shall be the same as that shown for 2x buck masonry construction.
- 5. Site conditions that deviate from the details of drawing FL-21132.9 require further engineering analysis by a licensed engineer or registered architect.
- 6. See drawing FL-21132.9 for size and design pressure limitations.

## Supporting Documents:

<ol> <li>Test Report No.</li></ol>	<u>Test Standard</u>	<u>Testing Laboratory</u> Testing Evaluation Laboratories Testing Evaluation Laboratories	Signed by
TEL 06-0717-1	ASTM E330(02) E331(00) , TAS 201/203-94		Wendell W. Haney, P.E.
TEL 01460145	ASTM E330(02) E1886(02) E1996(02)		V.K. Wright
2. Miami-Dade NOA	Material		

Miami-Dade NOA

17-0712.05 Saflex PVB Interlayers (Eastman Chemical Co.)

3. Drawing No. Prepared by No. FL-21132.9 RW Building Consultants, Inc. (CA #9813) 4. Calculations Prepared by

RW Building Consultants, Inc. (CA #9813)

5. Quality Assurance

Anchoring

Certificate of Participation issued by National Accreditation and Management Institute, certifying that Therma Tru Corporation is manufacturing products within a quality assurance program that complies with ISO/IEC 17020 and Guide 53.

Signed & Sealed by Lyndon F. Schmidt, P.E.

Signed & Sealed by

Lyndon F. Schmidt, P.E.

Lyndon F. Schmidt, P.E. FL PE No. 43409 7/20/2020