

R W Building Consultants, Inc.

Consulting and Engineering Services for the Building Industry P.O. Box 230 Valrico, FL 33595 Phone 813.659.9197 Florida Board of Professional Engineers Registry License No. 9813

Product	Evaluation R	eport	Report No.: Date:	FL-30037.2 July 25, 2023	
Product Category	Sub Category	Manufacturer	Product N	Product Name	
Exterior Doors	Swinging Exterior Door Assemblies	Wincore Windows & Doors 250 Staunton Turnpike Parkersburg, WV 26104	Opaque Fiberglass Doors Doubles w/ or w/out Sidelites Inswing / Outswing - "Impact"		

Scope:

pe: Product Evaluation report issued by R W Building Consultants, Inc. & Lyndon F. Schmidt, P.E. (System ID # 1998) for Wincore Windows & Doors, based on Rule Chapter No. 61G20-3, Method 1D of the State of Florida Product Approval, Department of Business & Professional Regulation.

RW Building Consultants and Lyndon F. Schmidt, P.E. do not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

Limitations:

- 1. This product has been evaluated and is in compliance with the 8th Edition (2023) Florida Building Code structural requirements excluding the "High Velocity Hurricane Zone".
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment to base material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with FBC Sections 1609.1.2 & R301.2.1.2 and does not require an impact resistant covering. This product meets missile level "D" and includes Wind Zone 4 as defined in ASTM E1996 and FBC Sections 1609.1.2.2 & R301.2.1.2.1.
- 4. For 2x stud framing construction, anchoring of these units shall be the same as that shown for 2x buck masonry construction.
- 5. Site conditions that deviate from the details of drawing FL-30037.2 require further engineering analysis by a licensed engineer or registered architect.

Testing Laboratory

Testing Evaluation Lab., Inc. V. K. Wright Testing Evaluation Lab., Inc. V. K. Wright

Testing Evaluation Lab., Inc. V. K. Wright

Testing Evaluation Lab., Inc. William B. Shelton, P.E.

6. See drawing FL-30037.2 for size and design pressure limitations.

Supporting	Documents:
------------	------------

1. Test Report No.	Test Standard
TEL 01391141	ASTM E330-02, 1886-05, 1996-06
TEL 01391144	ASTM E330-02, 1886-05, 1996-06
TEL 03851482	TAS 201, 202 & 203-94
TEL 01311994	ASTM E330-02, 1886-05, 1996-09

2. Miami-Dade NOA	Materials Testing

23-0713.18

Materials Testing Saflex® PVB Interlayer (Eastman Chemical Company)

Drawing No. No. FL-30037.2

RW Building Consultants, Inc. (#9813)

4. <u>Calculations</u> Anchoring ASTM E 1300 Glass Load RW Building Consultants, Inc. (#9813) RW Building Consultants, Inc. (#9813)

Prepared by

5. Quality Assurance

Certificate of Participation issued by National Accreditation and Management Institute, certifying that Wincore Windows & Doors is manufacturing products within a quality assurance program that complies with ISO/IEC 17020 and Guide 53.

> LYNDON F. SCHMIDT, State of Florida, Professional Engineer, License No. 43409 This item has been digitally signed and sealed by L. F. Schmidt on 10-19-23. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies. THIS PRODUCT APPROVAL IS VALID ONLY FOR THE STATE OF FLORIDA

Sheet 1 of 1

Signed & Sealed by Lyndon F. Schmidt, P.E.

Signed by

<u>Signed & Sealed by</u> Lyndon F. Schmidt, P.E.