

Evaluation Report "Pro-Cut® Starter Roll" Roof Underlayments

Manufacturer:

Atlas Roofing Corporation

2000 RiverEdge Parkway

Suite 800

Atlanta, GA 30328

(770) 946-4571

for

Florida Product Approval

FL 38571.1 R2

Florida Building Code 8th Edition (2023)

Method: 1 - D

Category: Roofing

Sub - Category: Underlayment

Products: "Pro-Cut® Starter Roll"

Description: Self-Adhered Underlayment

Prepared by:

James L. Buckner, P.E., SECB

Florida Professional Engineer # 31242

Florida Evaluation ANE ID: 1916


Project Manager: Diana Galloway

Report No. 23-578-ProCut-ER

(Revises 23-537-ProCut-ER, FL38571.1 R1)

Date: 08/16/2023

This item has been electronically signed and sealed by James L. Buckner, P.E., on this date using a Digital Signature. Printed copies of this document are not considered signed and sealed, and the signature must be verified on any electronic copies.



Date: 2023.08.16
'10:53:44 -04'00

Contents:

Evaluation Report

Pages 1 – 5

Manufacturer: Atlas Roofing Corporation
 2000 RiverEdge Parkway
 Suite 800
 Atlanta, GA 30328
 (770) 946-4571
www.atlasroofing.com

Product Category: Roofing

Product Sub-Category: Underlayment

Compliance Method: State Product Approval Rule 61G20-3.005 (1) (d)

PRODUCTS				
Product Name	Standard	Thickness (Nominal)	Roll Dimensions	Description
Pro-Cut® Starter Roll	ASTM D 1970	50 mils	7.2" x 33.5' (20.1 sqft) rolls	Self-adhering, fiberglass-mat reinforced, modified asphalt granular mineral surface with a release liner and one sealing tab line on the black granular surface; located nominally within 1-1/2" of edge.
Pro-Cut® Starter Roll	ASTM D 1970	50 mils	9" x 33.5' (25.1 sqft) rolls	Self-adhering, fiberglass-mat reinforced, modified asphalt granular mineral surface with a release liner and one sealing tab line on the black granular surface; located nominally within 1-1/2" of edge.

Substrate(s): Plywood Deck
 (Design of support is outside the scope of this evaluation)

Installation:

General Installation Instructions:

- Product to be applied directly to a clean dry surface.
- Dust, dirt, oil, grease, moisture, debris and other loose materials or contaminants must be removed prior to application.
- Check that all nails in deck are not protruding and re-fasten any loose decking panels.
- Prime Substrate with asphalt base primer.
- Cut the membrane to appropriate length.
- Peel back the release sheet, align the membrane and press into place onto roof deck.
- Apply with selvedge on upward slope.
- Overlap end laps a minimum of 6". Side laps must be a minimum of 3".
- Store product in the carton in a dry place until ready to use. Keep product out of direct sunlight.
- Protect membrane from damage during construction.

- Apply membrane only in fair weather when the air, surface and membrane are at a minimum temperature of: 40° F

Installation shall comply with FBC including Sections 1507.1.1.1, 1507.1.1.2 and applicable code sections of the current FBC, this report (subject to the Limitations and Conditions of Use listed in this Evaluation Report) and manufacturer's installation instructions as a supplemental guide for attachment.

Performance Standards: The product described herein has demonstrated compliance with:

- **ASTM D 1970-17a** – *Specification Self-adhering Polymer Modified Bituminous Sheet Materials Used as Steep Roof Underlayment for Ice Dam Protection*

Standards Equivalency: The ASTM D 1970-01 standard version used to test the product meets the prescribed standards in ASTM D 1970-17a standard version adopted by the Florida Building Code 8th Edition (2023) for use as evaluated in this report.

Code Compliance: The product(s) described herein have demonstrated compliance with the performance standards listed above as referenced in the Florida Building Code 8th Edition (2023).

Evaluation Report Scope: This product has been evaluated in compliance with the building envelope requirements of the Florida Building Code, as related to the scope section to Florida Product Approval Rule 61G20-3.001

Product Limitations and Conditions of Use:

- Deck shall be in compliance with applicable building code.
- Minimum slope shall be 2:12 or greater.
- Installation is limited to use with approved roof coverings that are mechanically fastened through the underlayment and is attached to the sheathing or rafters.
- Products not intended for use under metal roofing unless approved by metal roof manufacturer.

General Limitations and Conditions of Use:

- Scope of "Limitations and Conditions of Use" for this evaluation:
This evaluation report for "Optional Statewide Approval" contains technical documentation, specifications and installation method(s) which include "Limitations and Conditions of Use" throughout the report in accordance with Rule 61G20-3.005. Per Rule 61G20-3.004, the Florida Building Commission is the authority to approve products under "Optional Statewide Approval".
- Option for application outside "Limitations and Conditions of Use"
Rule 61G20-3.005(1)(e) allows engineering analysis for "project specific approval by the local authorities having jurisdiction in accordance with the alternate methods and materials authorized in the Code". Any modification of the product as evaluated in this report and approved by the Florida Building Commission is outside the scope of this evaluation and will be the responsibility of others.
- This report is a building code product evaluation per FLPE rule (FAC) 61G15-36 to comply with Florida product approval rule (FAC) 61G20-3. This evaluation

report is part of the Florida Building Commission approval for the listed code related criteria. This report by James Buckner, P.E. and CBUGK Engineering is not a design certification of code compliance construction submittal documentation, per FBC section 107, for any individual structure, site specific or permit design.

- Design of support system is outside the scope of this report.
- Fire Classification is outside the scope of Rule 61G20-3, and is therefore not included in this evaluation.
- This evaluation report does not evaluate the use of this product for use in the High Velocity Hurricane Zone code section. (Dade & Broward Counties)

Quality Assurance:


The manufacturer has demonstrated compliance of roof panel products in accordance with the Florida Building Code and Rule 61G20-3.0005 (3) for manufacturing under a quality assurance program audited by an approved quality assurance entity through Keystone Certifications, Inc. (FBC Organization ID# QUA 1824).

Referenced Data:

1. ASTM D 1970-01 Test
By PRI Construction Materials Technologies, Inc.
(FBC Organization ID# TST 1556)
Report No. MFM-030-02-01, Date: 6/30/10
2. ASTM D 1970-15a Test
By PRI Construction Materials Technologies, Inc.
(FBC Organization ID# TST 1556)
Project No. 117T0064, Date: 1/30/23
3. Equivalency of Test Standard Certification
By James L. Buckner, P.E. @ CBUGK Engineering
(FBC Organization # ANE 1916)
4. Quality Assurance
Keystone Certifications, Inc. (FBC Organization ID# QUA 1824)
Atlas Roofing Corporation
5. Authorization to Use Engineering Data
Letter, dated 4/19/2021
6. Certification of Independence
By James L. Buckner, P.E. @ CBUGK Engineering
(FBC Organization # ANE 1916)
7. Engineering Analysis
By CBUGK Engineering

**Atlas Roofing Corporation
Product Illustrations**

**Pro-Cut[®]
Starter Roll**



Pro-Cut[®] Starter Roll