

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

# **Product Evaluation Report**

of

Pella Corporation
Impervia 2.0 Sliding Patio Door
(Non-HVHZ) (Impact)

for

Florida Product Approval

FL# FL39352

Report No. 8635

### **Current Florida Building Code**

Method: 1 – A (Certificate)

**Category:** Exterior Doors

Sub – Category: Sliding Exterior Door Assemblies

**Product:** Impervia 2.0 Sliding Patio Door

(Non-HVHZ) (Impact)

Materials: Fiberglass Composite

Product Dimensions: See Installation Instructions, PLA005

## **Prepared for:**

Pella Corporation 102 Main St. Pella, IL 502190

# Prepared by:


Hermes F. Norero, P.E.

Florida Professional Engineer # 73778 Date: 7/13/2023

Contents:

Evaluation Report F

Pages 1 – 4



Hermes F. Norero, P.E. Florida P.E. No. 73778



398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Manufacturer: Pella Corporation

**Product Category:** Exterior Doors

**Product Sub-Category:** Sliding Exterior Door Assemblies

**Compliance Method:** State Product Approval Method (1)(a)

Product Name: Impervia 2.0 Sliding Patio Door

(Non-HVHZ) (Impact)

Scope: This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for Pella

Corporation based on Method 1a of the State of Florida Product Approval, Department of

Business and Professional Regulation - Florida Building Commission.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building Code.

See Installation Instructions **PLA005**, signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.

### **Limits of Use:**

- This product has been evaluated and is in compliance with the current Florida Building Code, <u>excluding</u> the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and <u>does not require</u> an impact resistant covering in Wind Zone 2 or less.
- 4. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and <u>does require</u> an impact resistant covering in Wind Zone 3 or more.
- 5. Site conditions that deviate from the details of installation instructions **PLA005** require further engineering analysis by a licensed engineer or registered architect.
- 6. See Installation Instructions **PLA005** for size and design pressure limitations.



954.399.8478



954.744.4738

FL#:

Date:

FL39352

Report No: 8635

7/13/2023



FL#: FL39352 Date: 7/13/2023 Report No: 8635

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

The manufacturer has demonstrated compliance of manufacture of products **Certification Agency:** 

> in accordance with the Florida Building Code for manufacturing under an approved certification agency through Window & Door Manufacturers

**Association** (FBC Organization #: CER1508)

**Performance Standards:** The product described herein has been evaluated per:

ASTM E1886-13a

ASTM E1996-17

AAMA/WDMA/CSA 101/I.S./A440-11/17

Referenced Data:

1. Product Testing performed by **Element Materials Technology** 

(FBC Organization # TST9610)

Dated: Report: ESP039102P.C2-3 05/13/23 ESP035050P.3B 02/20/21

2. Material Certification

Miami Dade County Notice of Acceptance (NOA)

Current NOA for PVB Interlayer by Kuraray America, Inc.

3. Certification Agency

**Window & Door Manufacturers Association** 

(FBC Organization #: CER1508)

Installation:

Refer to Installation Instructions (PLA005) for anchor spacing and more details of the

installation requirements.

**Design Pressure:** 

Refer to Installation Instructions (PLA005) for design pressures based on size, configuration,

and glass types.









FL#: FL39352 Date: 7/13/2023 Report No: 8635

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

#### **Equivalence of Test Standards:**

Various test standards have been evaluated for differences in test methodology, if any, between tested editions of the test standards listed below and those editions referenced in the current Florida Building Code. Pella Corporation has tested their products to the following test standard edition(s):

- 1) ASTM E1886-19
- 2) ASTM E1996-20

Chapter 35 of the current Florida Building Code references the following editions of the above mentioned test standards:

- 1) ASTM E1886-13a
- 2) ASTM E1996-17

After review of the above mentioned referenced standards and editions, it has been found that the results and tests carried out meet the requirements for compliance. All referenced standards have been found to be equivalent.





