

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

# **Product Evaluation Report**

of

JELD-WEN, inc.
Siteline Clad Sliding Patio Door
(WZ3)(Impact)

for

**Florida Product Approval** 

FL# FL41624

Report No. 7392

## **Current Florida Building Code**

Method: 1 – D (Engineering Evaluation)

**Category:** Exterior Doors

Sub – Category: Sliding Exterior Door Assemblies

**Product:** Siteline Clad Sliding Patio Door

Material: Aluminum Clad Wood

Product Dimensions: 95.25" x 95.5"

### **Prepared for:**


JELD-WEN, inc. 3737 Lakeport Blvd. Klamath Falls, OR 97601

### Prepared by:

Hermes F. Norero, P.E.
Florida Professional Engineer # 73778
Date: 8/11/2022

Contents:

Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

FL#: FL41624 Date: 8/11/2022 Report No: 7392

Manufacturer: JELD-WEN, inc.

**Product Category:** Exterior Doors

**Product Sub-Category:** Sliding Exterior Door Assemblies

**Compliance Method:** State Product Approval Method (1)(d)

Product Name: Siteline Clad Sliding Patio Door

(WZ3)(Impact)

Scope:

This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for **JELD-WEN, inc.** based on <u>Method 1d</u> of the State of Florida Product Approval, Florida Department of Business & Professional Regulation - Florida Building Commission.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building Code.

See Installation Instructions **D015969**, signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.

#### **Limits of Use:**

- 1. This product has been evaluated and is in compliance with the current Florida Building Code, **excluding** the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and <u>does not</u> require an impact resistant covering in Wind Zones 3 or less.
- 4. When used in areas requiring wind borne debris protection this product <u>does</u> require an impact resistant covering in Wind Zone 4.
- 5. Site conditions that deviate from the details of Installation Instructions **D015969** require further engineering analysis by a licensed engineer or registered architect.
- 6. See Installation Instructions **D015969** for size and design pressure limitations.



398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

FL#: FL41624 Date: 8/11/2022 Report No: 7392

**Quality Assurance Entity:** The manufact

The manufacturer has demonstrated compliance of products in accordance with the Florida Building Code for manufacturing under a Quality Assurance Entity through **Window and Door Manufacturers Association** (FBC Organization #QUA2515).

**Performance Standards:** 

The product described herein has been evaluated per:

AAMA/WDMA/CSA 101/I.S.2/A440-11

ASTM E1886-13aASTM E1996-14a

Referenced Data:

1. Product Testing performed by National Certified Testing Laboratories, Inc.

(FBC Organization # TST1589)

Report: SJW2015-151, Report Date: 1/22/2016 Report: L5342.01-301-47-R0 Report Date: 10/26/20

2. Product Testing performed by Architectural Testing, Inc. (an Intertek

company) - Fresno, CA

(FBC Organization # TST2609)

Report: N4953.01-301-47 RO, Report Date: 04/19/2022

3. Quality Assurance Entity

**Windows and Door Manufactures Association** 

(FBC Organization # QUA2515)

Installation:

Refer to Installation Instructions (**D015969**) for anchor types, spacing and more details of the installation requirements.

**Design Pressure:** 

Refer to Installation Instructions (**D015969**) for design pressure configurations.





