

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

# **Product Evaluation Report**

of

Drutex S.A.
IGLO Energy Classic Balcony Door
(HVHZ)(Impact)

for

**Florida Product Approval** 

FL# FL41838

Report No. 8896

**Current Florida Building Code** 

Method: 1 − D (Engineering Evaluation)

**Category:** Exterior Doors

Sub – Category: Swinging Exterior Door Assemblies

Product: IGLO Energy Classic Balcony Door

(HVHZ)(Impact)

Materials: uPVC

**Product Dimensions:** See Installation Instructions, DRU016

## **Prepared for:**

Drutex S.A. Leborska 31, 77-100 Bytow, Poland


## **Prepared by:**

Hermes F. Norero, P.E.

Florida Professional Engineer # 73778 Date: 10/17/2023

**Contents:** 

Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



FL#: FL41838

Report #: 8896

Date: 10/17/2023

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Manufacturer: Drutex S.A.

**Product Category:** Exterior Doors

**Product Sub-Category:** Swinging Exterior Door Assemblies

**Compliance Method:** State Product Approval Method (1)(d)

Product Name: IGLO Energy Classic Balcony Door

(HVHZ)(Impact)

Scope: This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for **Drutex** 

**S.A.** based on Method 1d of the State of Florida Product Approval, Department of Business

and Professional Regulation - Florida Building Commission.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval

process of the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building

Code.

See Installation Instructions **DRU016**, signed and sealed by Hermes F. Norero, P.E. (FL #

73778) for specific use parameters.

### **Limits of Use:**

- 1. This product has been evaluated and is in compliance with the current Florida Building Code, **including** the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and <u>does not require</u> an impact resistant covering.
- 4. Site conditions that deviate from the details of installation instructions **DRU016** require further engineering analysis by a licensed engineer or registered architect.
- 5. See Installation Instructions **DRU016** for size and design pressure limitations.



**FL#:** FL41838 **Report #:** 8896 Date: 10/17/2023

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

**Quality Assurance:** The manufacturer has demonstrated compliance of manufacture of products

> in accordance with the Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity

through Keystone Certifications, Inc. (FBC Organization # QUA1824).

**Performance Standards:** The product described herein has been evaluated per:

TAS 201-94

TAS 202-94

TAS 203-94

AAMA/WDMA/CSA 101/I.S.2/A440-17

ASTM E1886-13a

ASTM E1996-17

### Referenced Data:

1. Product Testing Performed by Intertek, Inc. - West Palm Beach, FL

(FBC Organization #TST1527)

Report: Dated: P0215.01-450-18 01/13/2023 Report Signed & Sealed by Tyler Westerling, FL P.E. No. 72012

2. Product Testing Performed by Blackwater Testing Lab

(FBC Organization #TST14034)

Report: Dated: BW-DRU-23-014 05/16/2023 BW-DRU-23-016 06/05/2023 Reports Signed & Sealed by Roberto Archila, FL P.E. No. 53306

3. **Quality Assurance** 

> **Keystone Certification, Inc.** (FBC Organization #QUA1824)

#### Installation:

Refer to Installation Instructions (DRU016) for anchor types, spacing, and more details of the installation requirements.

### **Design Pressure:**

Refer to Installation Instructions (DRU016) for design pressure configurations.



954.399.8478



**954.744.4738**