

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Product Evaluation Report

of

Drutex S.A. IGLO Energy Classic Balcony Door (Non-HVHZ) (Non-Impact)

for

Florida Product Approval

FL# FL41838

Report No. 8898

Current Florida Building Code

Method:	1 – D (Engineering Evaluation)	
	Exterior Doors	
Category:		
Sub – Category:	Swinging Exterior Door Assemblies	
Duradurati		

Product:

Materials: Product Dimensions: IGLO Energy Classic Balcony Door (Non-HVHZ) (Non-Impact) uPVC See Installation Instructions, DRU008


Prepared for:

Drutex S.A. Leborska 31, 77-100 Bytow, Poland

Prepared by:

Hermes F. Norero, P.E. Florida Professional Engineer # 73778 Date: 10/17/2023

Contents: Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



 FL#:
 FL41838

 Report #:
 8898

 Date:
 10/17/2023

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Manufacturer:		Drutex S.A.			
Product Category:		Exterior Doors			
Product Sub-Category:		Swinging Exterior Door Assemblies			
Compliance Method:		State Product Approval Method (1)(d)			
Product Name:		IGLO Energy Classic Balcony Door (Non-HVHZ) (Non-Impact)			
Scope:	This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for Drutex S.A. based on <u>Method 1d</u> of the State of Florida Product Approval, Department of Business and Professional Regulation - Florida Building Commission.				
	Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.				
	This product has been evaluated for use in locations adhering to the current Florida Building Code.				
	See Installation Instructions DRU008 , signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.				
Limits of Use:					
		s product has been evaluated and is in compliance with the current Florida ilding Code, <u>excluding</u> the "High Velocity Hurricane Zone" (HVHZ).			
		ct anchors shall be as listed and spaced as shown on details. Anchor Iment into substrate material shall be beyond wall dressing or stucco.			
	with	en used in areas requiring wind borne debris protection this product complies Chapter 16 of the current Florida Building Code and <u>does require</u> an impact stant covering.			
		conditions that deviate from the details of installation instructions DRU008 irre further engineering analysis by a licensed engineer or registered architect.			
	5. See	Installation Instructions DRU008 for size and design pressure limitations.			

\$ 954.399.8478

0

954.744.4738

Page 2 of 3

BUILDINGDROPS.COM



FL#:FL41838Report #:8898Date:10/17/2023

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Quality Assurance:	The manufacturer has demonstrated compliance of manufacture of products in accordance with the Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity through Keystone Certifications, Inc. (FBC Organization # QUA1824).			
Performance Standards:	The product described herein has been evaluated per:			
	• AAMA/WDMA/CSA 101/I.S.2/A440-17			
Referenced Data:	1.	Product Testing Performed by Intertek, Inc. – V (FBC Organization # TST1527) Report: P0215.01-450-18	West Palm Beach, FL Dated: 12/16/2022	
	2.	Quality Assurance Keystone Certification, Inc. (FBC Organization #QUA1824)		

Installation:

Refer to Installation Instructions (**DRU008**) for anchor types, spacing, and more details of the installation requirements.

Design Pressure:

Refer to Installation Instructions (DRU008) for design pressure configurations.

