

## R W Building Consultants, Inc.

Consulting and Engineering Services for the Building Industry P.O. Box 230 Valrico, FL 33595 Phone 813.659.9197

Florida Board of Professional Engineers Registry License No. 9813

Product Evaluation Report

Report No.:

FL-46173.10

Date:

April 24, 2024

Product Category	Sub Category	Manufacturer	Product Name
Exterior Doors	Swinging Exterior Door Assemblies	Therma Tru Corporation 118 Industrial Drive Edgerton, OH 43517 Phone 419.298.1740	"VERIS V3" Glazed Aluminum Door Double w/ or w/out Sidelites Outswing - "Impact"

Scope:

This is a Product Evaluation report issued by R W Building Consultants, Inc. and Lyndon F. Schmidt, P.E. for Therma Tru Corporation based on Rule Chapter No. 61G20-3, Method 1D of the State of Florida Product Approval, Department of Business & Professional Regulation.

RW Building Consultants and Lyndon F. Schmidt, P.E. do not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

## Limitations:

- 1. This product has been evaluated and is in compliance with the 8th Edition (2023) Florida Building Code (FBC) structural requirements including the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment to base material shall be beyond wall dressing or stucco.
- 3. When used in the "HVHZ", this product complies with Section 1626 of the FBC and does not require an impact resistant covering.
- 4. For 2x stud framing construction, anchoring of these units shall be the same as that shown for 2x buck masonry construction.
- 5. Site conditions that deviate from the details of drawing FL-46173.10 require further engineering analysis by a licensed engineer or registered architect.
- 6. This product does not meet the water infiltration requirements for the "HVHZ" and shall be installed only in non-habitable areas or at habitable locations protected by an overhang or canopy such that the angle between the edge of canopy or overhang to sill is less than 45
- 7. Aluminum components, including fasteners, shall meet the requirements of FBC Section 2003.
- 8. Gaskets shall comply with FBC Section 2411.3.4.
- 9. See drawing FL-46173.10 for size and design pressure limitations.

## Supporting Documents:

1. Test Report No. **Test Standard Testing Laboratory** Signed by TEL 01463794 TAS 201, 202 & 203-94 Testing Evaluation Lab. William Shelton, P.E.

2. Miami-Dade NOA **Material** 

23-0717.30 SentryGlas® Interlayer (Kuraray)

3. Drawing No. Prepared by

No. FL-46173.10 RW Building Consultants, Inc. (#9813) Lyndon F. Schmidt, P.E.

4. Calculations Prepared by

Signed & Sealed by Anchoring RW Building Consultants, Inc. (#9813) Lyndon F. Schmidt, P.E.

ASTM E 1300 Glass Load RW Building Consultants, Inc. (#9813)

## 5. Quality Assurance

Certificate of Participation issued by National Accreditation and Management Institute, certifying that Therma Tru Corporation is manufacturing products within a quality assurance program that complies with ISO/IEC 17020 and Guide 53.

> LYNDON F. SCHMIDT, State of Florida, Professional Engineer, License No. 43409 This item has been digitally signed and sealed by L. F. Schmidt on 4-25-24. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Signed & Sealed by

THIS PRODUCT APPROVAL IS VALID ONLY FOR THE STATE OF FLORIDA