

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Product Evaluation Report

of

Drutex S.A. MB-79N SI Tilt & Turn Window (Non-HVHZ)(Non-Impact)

for

Florida Product Approval

FL# FL46728

Report No. 9151

Current Florida Building Code

Method: Category: Sub – Category: 1 – D (Engineering Evaluation) Windows Dual Action


Product: Materials: Product Dimensions: MB-79N SI Tilt & Turn Window Aluminum 6063-T5 See Installation Instructions, DRU036

Prepared for:

Drutex S.A. Leborska 31, 77-100 Bytow, Poland

Prepared by: Hermes F. Norero, P.E. Florida Professional Engineer # 73778 Date: 4/1/2024

Contents: Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



 FL#:
 FL46728

 Report #:
 9150

 Date:
 4/1/2024

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Manufacturer:		Drutex S.A.			
Product Category:		Windows			
Product Sub-Category: Compliance Method:		Dual Action			
		State Product Approval Method (1)(d)			
Product Name:		MB-79N SI Tilt & Turn Window (Non-HVHZ) (Non-Impact)			
Scope:	S.A. bas	Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for Drutex eed on <u>Method 1d</u> of the State of Florida Product Approval, Department of Business fessional Regulation - Florida Building Commission.			
	Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.				
	This pro Code.	oduct has been evaluated for use in locations adhering to the current Florida Building			
		n Instructions DRU036 , signed and sealed by Hermes F. Norero, P.E. (FL # cific use parameters.			
Limits of Use:					
	1.	This product has been evaluated and is in compliance with the current Florida Building Code, excluding the "High Velocity Hurricane Zone" (HVHZ).			
	2.	Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.			
	3.	When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and <u>does require</u> an impact resistant covering.			
	4.	Site conditions that deviate from the details of installation instructions DRU036 require further engineering analysis by a licensed engineer or registered architect.			
	5.	See Installation Instructions DRU036 for size and design pressure limitations.			

BUILDINGDROPS.COM

954.399.8478

2

0

CONTACT@BUILDINGDROPS.COM

954.744.4738



 FL#:
 FL46728

 Report #:
 9150

 Date:
 4/1/2024

1900 NE MIAMI CT. SUITE 2-15, MIAMI, FL 33132

Quality Assurance:	The manufacturer has demonstrated compliance of manufacture of produce in accordance with the Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity through Keystone Certifications, Inc. (FBC Organization # QUA1824).			
Performance Standards:	The product described herein has been evaluated per:			
	• AAMA/WDMA/CSA 101/I.S.2/A440-17			
Referenced Data:	1. 2.	Product Testing Performed by Blackwater Test (FBC Organization # TST14034) Report: BW-DRU-23-047-002 Quality Assurance Keystone Certification, Inc. (FBC Organization #QUA1824)	t ing Lab Dated: 11/20/2023	

Installation:

Refer to Installation Instructions (**DRU036**) for anchor types, spacing, and more details of the installation requirements.

Design Pressure:

Refer to Installation Instructions (DRU036) for design pressure configurations.

